

MATERIAL SAFETY DATA SHEET

IDENTITY (as used on label): KERACARE STYLING SPRITZ (MEDIUM HOLD)

SECTION I

MANUFACTURER: AVLON INDUSTRIES, INC. DATE ISSUED: JUNE, 20, 2006
ADDRESS: 1999 N. 15th AVE., MELROSE PARK, IL, 60160
EMERGENCY TELEPHONE NUMBER: 1-800-535-5053 (INFOTRAC)
TELEPHONE NUMBER FOR INFORMATION: (708) 563-0363

Material Safety Data Sheet May be used to comply with OSHA'S Hazard Communication Standard 29 CFR 1910, 1200 Standard must be consulted for specific requirements.

Occupational Safety and Health Administration U.S. Department of Labor((Non) Mandatory) Form
Approved OMB No. 1218-0072

Section II Hazardous Ingredients/Identity Information

OSHA ACGIH TLV Other Limits 55% VOC'S by volume

Hazardous Components Specific Chemical Identity:

Common Name(s)

SD Alcohol 40

Follow label directions and caution statement.

Section III – Physical/Chemical Characteristics

Boiling Point: < 212⁰F

Specific Gravity: 0.900 – 0.930

Vapor Pressure (mm Hg): N/A

Melting Point: N/A

Vapor Density (AIR =1): Not Know

pH: @ 25⁰C 6.0 – 7.0

Solubility in Water: SOLUBLE

Appearance and Odor: A light blue clear liquid with berry odor

Section IV – Fire and Explosion Hazard Data

Flashing Point : (method : Pensky Martens “closed cup”) = 21°C (70°F)

Flammable Limits: LEL (Uel)

Flammable

Extinguishing Media: Use water fog, foam, dry chemicals or carbon monoxide

Special Fire Fighting Procedures:

Unusual Fire and Explosion Hazards: Avoid oxidizing material

