BioSilk Molding Silk

Page 1 of 5 Revision Date: 10/19/2004

MSDS Number: 0030

2

4

1	PRODUCT AND COMPANY IDENTIFICATION	
Manufacturer	Vendor	

Manuacturer	Vendor
2-2-0 Laboratories, Inc.	Farouk Systems, Inc. 250 Pennbright
2375 3rd Street	Suite 150
Riveside, CA 92607	Houston, Texas 77090
Contact: W.M Fruscella Telephone Number: 800-424-9300 FAX Number: E-Mail: Web	Contact: EHS Department Telephone Number: 1-800-237-9175 FAX Number: 281-885-5512 E-Mail: ehsdept@farouk.com Web www.farouk.com

Product Name:	BioSilk Molding Silk
Revision Date:	10/19/2004
MSDS Number:	0030
Synonyms:	Molding Silk
Product Use:	Toiletry, Cosmetic Applications

FIRST AID MEASURES

COMPOSITION/INFORMATION ON INGREDIENTS

Purified Water	±55%
Dimethicone	±1.0%
Dicapropylyl Maleate	±2.5%
Propylene Glycol	±2.0%

estion
alation
ne.
sed improperly, this product may cause dizziness, headache and difficulty in breathing.
/ cause slight irritation to the skin.
/ cause burning and irritation to the eyes.
cause irritation to the digestive tract and cause cramps/diarrhea.

Inhalation:	None.
Skin Contact:	Wash with soap and water. Avoid contact with skin rashes or open sores.
Eye Contact:	Remove any contact lenses, if necessary, and immediately flush eyes with plenty of water for 15 minutes. Seek medical attention if necessary.
Ingestion:	Wash mouth out and drink plenty of water. Seek medical attention if necessary.

BioSilk Molding Silk

Page 2 of 5 Revision Date: 10/19/2004

MSDS Number: 0030

5

6

7

8

FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: Not applicable. FLAMMABLE LIQUIDS: Not available. AUTO IGNITION TEMP: None. FLAMMABLE CLASS:

None. BURNING RATE OF SOLID: Not available

GENERAL HAZARDS: Evacuate personnel downwind of fire to avoid inhalation of fumes and smoke.

EXTINGUISHING METHODS: Chemical type foam, CO2(Carbon Dioxide), Dry Chemical, Water Fog

HAZARDOUS COMBUSTION PRODUCTS: Cabon Monoxide and unidentifed organic compounds may be formed during combustion.

FIRE FIGHTING PROCEDURES: This product is not flammable. However, hazardous decomposition and combustion products may be formed in a fire situation. Cool exposed containers with water spray to prevent overheating.

FIRE FIGHTING EQUIPMENT: Respiratory and eye protection are required for fire fighting personnel. Full protective equipment (Bunker Gear) and self contained breathing apparatus (SCBA) should be used for all indoor fires and significant outdoor fires. For small outdoor fires, which may be easily extinguished with a portable fire extinguisher, use of a SCBA may not be needed.

ACCIDENTAL RELEASE MEASURES

SMALL SPILL: When a spill occurs, use absorbent material on the substance. Dispose of the material according to all local, state and federal regulations. Always use an absorbent material when cleaning up a spill.

ENVIRONMENTAL PRECAUTIONS: Avoid run-off or release into sewers, stormdrains and waterways.

GENERAL PRECAUTIONS: Remove containers away from flammable materials.

HANDLING AND STORAGE

Handling Precautions: Use appropriate personal protective equipment as specified in Section 8. Handle in a manner consistent with good household/personal techniques and practices. Keep containers/bottles securely sealed when not in use. Store in cool/dry conditions that do

Storage Requirements: not exceed room temperature. Try to store product in temperatures between 40°F to 120°F.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: These recommendations provide general guideance for handling this product safely. Because specific use conditions may vary, safety procedures should be developed for each specific application of this product. When developing procedures, always consider potential waste, disposal and personal safety issues. EYES AND FACE: For reasonable foreseeable uses of this product, eye and face protection is not **Protective Equipment:** required. SKIN: For reasonable foreseeable uses of this product, skin protection is not required. RESPIRATORY: For reasonable foreseeable uses of this product, respiratory protection is not required.

EXPOSURE GUIDELINES: Overexposure is unlikely. Since all parameters cannot be foreseen, the use of engineering controls to reduce exposure may be necessary.

BioSilk Molding Silk

Page 3 of 5 Revision Date: 10/19/2004

MSDS Number: 0030

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Light, tan paste
Physical State:	Paste
Odor:	Pleasant, perfume fragrance
pH:	4.85
Vapor Pressure:	N/A
Vapor Density:	N/A
Percent Volati	ile: 60%

Boiling Point: >212°F Freezing/Melting Pt.: >77°F Solubility: Soluble in water. Spec Grav./Density: 0.963

10	STABILITY A	ND REACTIVITY
Stability:		YES
Conditions to avoid:		Extreme temperatures.
Materials to avoid (incompatability):		Strong oxidizing agents.
Hazardous Decomposition products:		None known.
Hazardous Polymerization:		Will Not Occur.

11

TOXICOLOGICAL INFORMATION

ACUTE: DERMAL LD50: Not available. ORAL LD50: Not available. INHALATION LC50: Not available. EYE EFFECTS: This product may cause irritation to eyes if not used under normal conditions. TARGET ORGANS: NONE. SENSITIZATIONS: Not available. CARCINOGENICITY: IARC: Listed by IARC - No. NTP: Listed by NTP - No. OSHA: Listed by OSHA - No.

MUTAGENICITY: Not available. **REPRODUCTIVE EFFECTS: None.** TERATOGENIC EFFECTS: Not available.

12 **ECOLOGICAL INFORMATION**

ENVIRONMENTAL DATA: Not available. ECOTOXICOLOGICAL INFO: Not available. DISTRIBUTION: Not available. CHEMICAL FATE INFO: Not available.

BioSilk Molding Silk

 Page
 4
 of
 5

 Revision Date:
 10/19/2004

MSDS Number: 0030

13

15

DISPOSAL CONSIDERATIONS

US EPA Waste Number and Descriptions:

DISPOSAL METHOD: Controlled release of diluted product into a biological wastewater treatment plant. COMPONENT WASTE NUMBER: No EPA Waste Numbers are applicable for this product's components. DISPOSAL INSTRUCTIONS: Dispose of waste material according to local, state and federal rules and regulations.

14 TRANSPORT INFORMATION

This product is not regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

DOT CLASSIFICATION: Shipping Name: BioSilk Molding Silk Class: None. Non-regulated, non-hazardous

IMDG CLASSIFICATION: Shipping Name: BioSilk Molding Silk Class: None. Non-regulated, non-hazardous

IATA CLASSIFICATION: Shipping Name: BioSilk Molding Silk Class: None. Non-regulated, non-hazardous

1-800-424-9300 Inside the United States CHEMTREC

REGULATORY INFORMATION

1-703-527-3887

Outside the United States

UNITED STATES: SARA TITLE III (Superfund Amendments and Reauthorization Act) 311/312 HAZARD CATEGORIES Fire: No. Pressure Generating: No. Reactivity: No. Acute: No. 313 REPORTABLE INGREDIENTS: Not applicable. TITLE III NOTES: None. CERCLA(Comprehensive Response, Compensation, and Liability Act) CERCLA RQ: None. TSCA(Toxic Substance Release Act) TSCA REGULATORY: All ingredients are listed in the TSCA Inventory. CANADA: WHMIS(WORKER HAZARDOUS MATERIAL INFORMATION SYSTEM) This product is WHMIS controlled. CANADIAN INGREDIENT DISCLOSURE LIST: Propylene Glycol CANADIAN ENVIRONMENTAL PROTECTION ACT: All intentional ingredients are listed on the DSL(Domestic Substance List). EUROPEAN COMMUNITY: EU REGULATORY: All intentional ingredients are listed on the European's EINECS Inventory. STATE REGULATIONS: Not available. LOCAL REGULATIONS: Not available.

BioSilk Molding Silk

Page 5 of 5 Revision Date: 10/19/2004

MSDS Number: 0030

16	OTHER INFORMATION
NFPA CODES: Hazard Scale: 0 = Normal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe	
NFPA RATING: FLAMMABILITY: 0 HEALTH: 1	

SPECIAL: None HMIS RATING: FLAMMABILITY: 0 HEALTH: 1 PHYSICAL HAZARD: 0 PERSONAL PROTECTION: N/A

REACTIVITY: 0

Disclaimer: Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

END OF MSDS DOCUMENT