CHI Infra High Lift Color - RO

MSDS Number: 0356 Revision Date: 10/5/2004

Page 1 of 5

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Farouk Systems, Inc. 250 Pennbright Suite 150 Houston, Texas 77090

Contact: EHS Department

Telephone Number: 1-800-237-9175
FAX Number: 281-885-5512
E-Mail: ehsdept@farouk.com
Web www.farouk.com

Product Name: CHI Infra High Lift Color - RO

Revision Date: 10/5/2004

MSDS Number: 0356

Synonyms: CHI Infra High Lift Color - RO Product Use: Toiletry, Cosmetic Applications

2 COMPOSITION/INFORMATION ON INGREDIENTS

Potassium Persulfate ≥30.0% Sodium Metasilicate ≥5.0% Mineral Oil ≥31.0%

3 HAZARDS IDENTIFICATION

Route of Entry: Eyes

Ingestion Inhalation Skin

Target Organs: None.

Inhalation: Misuse of this product may cause dizziness. Skin Contact: May cause skin irritation if used incorrectly.

Eye Contact: May cause itching and burning if not used properly.

Ingestion: May cause irritation to the digestive tract.

4 FIRST AID MEASURES

Inhalation: Remove to fresher air supply.

Skin Contact: Wash with soap and water for 15 minutes.

Eye Contact: Remove any contact lenses, if necessary, and immediately flush eyes with plenty of water for 15 minutes.

Seek medical attention if necessary.

Ingestion: Wash mouth out and drink plenty of water. Seek medical attention if necessary.

CHI Infra High Lift Color - RO

Page 2 of 5

MSDS Number: 0356 Revision Date: 10/5/2004

5

FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD:

Not applicable.

FLAMMABLE LIQUIDS:

Not available.

AUTO IGNITION TEMP:

None.

FLAMMABLE CLASS:

None.

BURNING RATE OF SOLID:

Not available

GENERAL HAZARDS: Evacuate personnel downwind of fire to avoid inhalation of fumes and smoke.

EXTINGUISHING METHODS: Chemical type foam, Dry Chemical, Water Fog

HAZARDOUS COMBUSTION PRODUCTS: None.

FIRE FIGHTING PROCEDURES: This product is not flammable. However, hazardous decomposition and combustion products may be formed in a fire situation. Cool exposed containers with water spray to prevent overheating.

FIRE FIGHTING EQUIPMENT: Respiratory and eye protection are required for fire fighting personnel. Full protective equipment (Bunker Gear) and self contained breathing apparatus (SCBA) should be used for all indoor fires and significant outdoor fires. For small outdoor fires, which may be easily extinguished with a portable fire extinguisher, use of a SCBA may not be needed.

6

ACCIDENTAL RELEASE MEASURES

SMALL SPILL: When a spill occurs, use absorbent material on the substance. Dispose of the material according to all local, state and federal regulations. Always use an absorbent material when cleaning up a spill.

ENVIRONMENTAL PRECAUTIONS: Avoid run-off or release into sewers, stormdrains and waterways.

GENERAL PRECAUTIONS: Remove containers away from flammable materials.

7

HANDLING AND STORAGE

Handling Precautions: Use appropriate personal protective equipment as specified in Section 8. Handle in a manner

consistent with good household/personal techniques and practices.

Storage Requirements: Keep containers/bottles securely sealed when not in use. Store in cool/dry conditions that do

not exceed room temperature. Try to store product in temperatures between 40°F to 90°F.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: These recommendations provide general guideance for handling this product safely. Because

specific use conditions may vary, safety procedures should be developed for each specific application of this product. When developing procedures, always consider potential waste,

disposal and personal safety issues.

Protective Equipment: EYES AND FACE: For reasonable foreseeable uses of this product, eye and face protection is not

required.

SKIN: For reasonable foreseeable uses of this product, skin protection is not required.

RESPIRATORY: For reasonable foreseeable uses of this product, respiratory protection is not

required.

EXPOSURE GUIDELINES: Overexposure is unlikely. Since all parameters cannot be foreseen, the use of engineering controls to reduce exposure may be necessary.

CHI Infra High Lift Color - RO

MSDS Number: 0356 Revision Date: 10/5/2004

Page 3 of 5

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Orange color

Physical State:CremeBoiling Point:N/AOdor:Pleasant, fragranceFreezing/Melting Pt.:N/A

pH: 10.5 - 11.5 **Solubility:** Soluble in water.

Vapor Pressure: N/A Spec Grav./Density: N/A

Vapor Density: N/A

10 STABILITY AND REACTIVITY

Stability: YES
Conditions to avoid: None.

Materials to avoid (incompatability): Keep away from strong acids, reducing chemicals and heavy metals.

Hazardous Decomposition products: Releases oxygen which may intensify a fire.

Hazardous Polymerization: Will Not Occur.

11 TOXICOLOGICAL INFORMATION

ACUTE:

DERMAL LD50: Not available.
ORAL LD50: Not available.
INHALATION LC50: Not available.

EYE EFFECTS: This product may cause irritation to eyes if not used under normal conditions.

TARGET ORGANS: NONE.

SENSITIZATIONS: Not available.

CARCINOGENICITY:

IARC: Listed by IARC - No. NTP: Listed by NTP - No. OSHA: Listed by OSHA - No. MUTAGENICITY: Not available.

REPRODUCTIVE EFFECTS: None.

TERATOGENIC EFFECTS: Not available.

12 ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Not available. ECOTOXICOLOGICAL INFO: Not available.

DISTRIBUTION: Not available.

CHEMICAL FATE INFO: Not available.

CHI Infra High Lift Color - RO

MSDS Number: 0356 Revision Date: 10/5/2004

Page 4 of 5

13

DISPOSAL CONSIDERATIONS

US EPA Waste Number and Descriptions:

DISPOSAL METHOD: Controlled release of diluted product into a biological wastewater treatment plant. COMPONENT WASTE NUMBER: No EPA Waste Numbers are applicable for this product's components.

DISPOSAL INSTRUCTIONS: Dispose of waste material according to local, state and federal rules and regulations.

14

TRANSPORT INFORMATION

This product is regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

Shipping Name: Consumer Commodity DOT CLASSIFICATION:

Class: ORM-D

IMDG CLASSIFICATION: Shipping Name: Oxidizing Liquid, nos(Potassium Persulfate mixture) -

UN3139, PG III Class: 5.1 - Oxidizer

Shipping Name: Oxidizing Liquid, nos (Potassium Persulfate mixture) -IATA CLASSIFICATION:

UN3139, PG III

Class: 5.1 - Oxidizer

Pkg Inst - Y514

1-800-424-9300 1-703-527-3887

Inside the United States Outside the United States

CHEMTREC

15

REGULATORY INFORMATION

UNITED STATES:

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 HAZARD CATEGORIES

Fire: No.

Pressure Generating: No.

Reactivity: No.

Acute: No.

313 REPORTABLE INGREDIENTS: Not applicable.

TITLE III NOTES: None.

CERCLA(Comprehensive Response, Compensation, and Liability Act)

CERCLA RQ: None.

TSCA(Toxic Substance Release Act)

TSCA REGULATORY: All ingredients are listed in the TSCA Inventory.

CANADA:

WHMIS(WORKER HAZARDOUS MATERIAL INFORMATION SYSTEM)

This product is WHMIS controlled.

CANADIAN INGREDIENT DISCLOSURE LIST: Sodium Metasilicate.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All intentional ingredients are listed on the DSL(Domestic Substance List).

EUROPEAN COMMUNITY:

EU REGULATORY: All intentional ingredients are listed on the European's EINECS Inventory.

STATE REGULATIONS: Not available. LOCAL REGULATIONS: Not available.

CHI Infra High Lift Color - RO

MSDS Number: 0356 Revision Date: 10/5/2004

Page 5 of 5

16

OTHER INFORMATION

NFPA CODES: Hazard Scale: 0 = Normal

1 = Slight

2 = Moderate

3 = Serious

4 = Severe

NFPA RATING: FLAMMABILITY: 0 HEALTH: 1 **REACTIVITY: 0** SPECIAL: None

HMIS RATING: FLAMMABILITY: 0

HEALTH: 1

PHYSICAL HAZARD: 0

PERSONAL PROTECTION: N/A

Disclaimer: Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

END OF MSDS DOCUMENT