

# MATERIAL SAFETY DATA SHEET (MSDS)

**PRODUCT IDENTITY (as indicated on label)**

**PRODUCT CODE**

**Headbanger Spray Wax**

## Section 1 Company Identification

Distributor's Name TIGI Linea, LP	Emergency Telephone Number CHEMTREC (800) 424-9300
Address (Number, Street, City, State, and ZIP Code) 2311 Midway Road Carrollton, Texas 75006	Telephone Number for Information (972) 931-1567
	Date Prepared July 18, 2005

## Section 2 Hazardous Ingredients/Identity Information

Hazardous Components [Specific Chemical Identity; Common Name(s)]	CAS Number	Vapor Pressure	OSHA PEL	ACGIH TLV
Isobutane	50%	75-28-5	PEL 88 ppm	TLV est

NE = not established for this material

Regulated under CA VOC: no greater than 55% (w/w)

## Section 3 Hazards Identification

EMERGENCY OVERVIEW Type of Hazard: Inhalation

### POTENTIAL HEALTH EFFECTS

Inhalation: Slight to severe irritation  
Skin Contact: Practically non-irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dryness. Skin Absorption: none to Slight  
Eye Contact: May cause mild to severe eye irritation  
Ingestion: None known at this time.  
Chronic Effects and Medical Conditions Aggravated By Overexposure: None known at this time  
Carcinogenicity: NTP: N/A IARC: N/A OSHA: N/A

## Section 4 First Aid Measures

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention.  
SKIN: Thoroughly wash exposed area. If irritation persists, seek medical attention  
EYES: Flush with copious amounts of water for 15 minutes. If irritation persists, seek medical attention  
INGESTION: DO NOT induce vomiting. Get medical attention IMMEDIATELY.

## Section 5 Fire Fighting Measures

FLAMMABILITY CLASSIFICATION: **Flammable (Aerosol)** FLASH POINT: < 20°F (Tag closed Cup)

UNUSUAL FIRE AND EXPLOSION HAZARDS: Aerosols will burst at temperatures above 130°C (55°C). containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure build up which could result in container rupture

SPECIAL FIRE FIGHTING PROCEDURES: Use Self-contained breathing apparatus. Water may be used on containers exposed to intense heat to prevent vapor pressure build up and container rupture. Keep containers cooled with water and remove them from danger as soon as possible. If aerosols are bursting, stay clear until bursting is completed. Aerosols can be projectiles when bursting.

**NFPA 30B Storage Classification of Aerosol: Level 2**

# MATERIAL SAFETY DATA SHEET (MSDS)

**PRODUCT IDENTITY (as indicated on label)**

**PRODUCT CODE**

## Headbanger Spray Wax

### Section 6 Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep sources of ignition and hot metals isolated from the spill. Small leaks can be mopped or wiped up immediately. Remove material to out of doors. Large leaks should be handled as follows: Evacuate area. Contain liquid; transfer to closed containers. Keep out of water supplies.

DISPOSAL METHOD: dispose of according to federal, state and locals regulations. Disposal should be carried out under EPA state and federal laws

### Section 7 Handling and Storage

USAGE PRECAUTIONS: Product is **Flammable**. Do not puncture or burn even after use. Keep away from heat, sparks, or flame. Extinguish pilot lights, cigarettes or other sources of ignition. Use with adequate ventilation.

STORAGE PRECAUTIONS: Keep containers cool in temperatures below 120°F. Keep containers dry, closed and upright when not in use.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Maintain personal hygiene and good housekeeping .

### Section 8 Exposure Controls and Personal Protection

RESPIRATION CONTROL: If used with adequate ventilation, no protective equipment is necessary. In enclosed spaces if exposure limits are exceeded use a NIOSH approved cartridge respirator.

VENTILATION: A well ventilated room with adequate air circulation.

PROTECTIVE GLOVES: Wear chemical resistant gloves and other clothing as required to minimize prolonged or repeated contact with skin.

EYE AND FACE PROTECTION: Chemical goggles if likelihood of eye contact

HYGENIC WORK PRACTICES: Wash well with soap and water after use of product.

### Section 9 Physical and Chemical Properties

BOILING RANGE: N/A	VAPOR DENSITY(Concentrate): <u>  X  </u> HEAVIER <u>  </u> LIGHTER, THAN AIR (= 1)	
PERCENT VOLATILE PER w/w: 50%	EVAPORATION RATE(concentrate): (n-Butyl Acetate = 1) Greater than 1 Slower than Ethyl Ether	
pH: N/A (Concentrate)	WEIGHT PER GALLON: 6.83 +/- 0.1 (Concentrate)	SPECIFIC GRAVITY: 0.82 (H <sub>2</sub> O=1)
SOLUBILITY IN WATER: Insoluble		VISCOSITY: N/A

APPEARANCE: hazy liquid  
ODOR: characteristic

