

Fantastic Finish Finishing Spritz 55% VOC

1. Product and company identification

Product name	:	Fantastic Finish Finishing Spritz 55% VOC
Manufacturer	:	Zotos International, INC 100 Tokeneke Road, Darien, CT 06820 www.zotos.com
Validation date	:	8/12/2014.
In case of emergency		(800) 584-8038 [24 Hours]
Telephone number		(203) 656-7859 [8:30 a.m 5:00 p.m.]
Transportation Emergency		Contact: CHEMTREC 1-800-424-9300 [US/Canada 24 Hours]
Product type	:	Liquid.

2. Hazards identification

Emergency overview

NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Additional information on toxicological endpoints is available from the supplier upon request

Color	: Colorless to light yellow.
Odor	: Characteristic. Fragrance-like.
Hazard statements	: FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.
Precautionary measures	: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.
OSHA/HCS status	: None.
Potential acute health effec	<u>s</u>
Inhalation	: May cause respiratory irritation. Avoid breathing vapor.
Ingestion	: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.
Skin	: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Mild irritant
Eyes	: May cause slight transient irritation.
Potential chronic health effe	ects
Chronic effects	: No known significant effects or critical hazards.
Carcinogenicity	: Contains material which can cause cancer.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Over-exposure signs/sympt	<u>oms</u>
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation redness

2. Hazards identification

Eves

Eyes	: Adverse symptoms may include the following: pain or irritation watering redness
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
Alcohol Denat.	64-17-5	54.80
Canada		,

Name	CAS number	%
Alcohol Denat.	64-17-5	54.80

<u>Mexico</u>

						Cla	assific	ation
Name	CAS number	UN number	%	IDLH	н	F	R	Special
Alcohol Denat.	64-17-5	UN1993	54.80	3300 ppm	2	3	0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measu	ures
Eye contact	 In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
Skin contact	: Remove contaminated clothing and shoes. Wash with plenty of soap and water.
Inhalation	: Move affected person to fresh air.
Ingestion	: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Treat symptomatically. Never give anything by mouth to an unconscious person. Call a physician.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product	:	Flammable liquid. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.
Extinguishing media	:	Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Special exposure hazards	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective equipment for fire-fighters	:	Immediately contact emergency personnel. Flammable material In case of insufficient ventilation, wear suitable respiratory equipment.

6. Accidental release measures

Personal precautions	: Flammable. Keep away from ignition sources such as heat/sparks/open flame I smoking. Do not get in eyes. Keep out of reach of children.	No
Environmental precautions	: Leaking packages should be placed in open containers outdoors away from any s of ignition	ource
Methods for cleaning up	: Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Place spilled material in an appropriate container for disposal. A contact with skin, wash immediately with plenty of water.	

7. Handling and storage

Handling	: Keep away from ignition sources such as heat/sparks/open flame No smoking. Use only in well-ventilated areas. Avoid contact with ignition and heat sources and oxidizers. Do not spray on an open flame or other ignition source. Keep out of reach of children.
Storage	: Avoid increased storage temperature. Keep away from ignition sources such as heat/ sparks/open flame No smoking. Avoid contact with ignition and heat sources and oxidizers. Store away from oxidizing agents. Store in cool/well-ventilated place.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits	
Alcohol Denat.	ACGIH TLV (United States, 6/2013). STEL: 1000 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours. NIOSH REL (United States, 4/2013). TWA: 1000 ppm 10 hours. TWA: 1900 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1000 ppm 8 hours. TWA: 1000 ppm 8 hours.	

<u>Canada</u>

8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Alcohol Denat.	US ACGIH 6/2013 AB 4/2009 BC 7/2013 ON 1/2013 QC 12/2012	- 1000 - - 1000	- 1880 - - 1880	- - - -	1000 - 1000 1000 -	- - - -	- - - -	- - - -	- - - -	- - -	

<u>Mexico</u>

Occupational exposure limits

Ingredient	Exposure limits
Alcohol Denat.	NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 1000 ppm 8 hours. LMPE-PPT: 1900 mg/m ³ 8 hours.

Consult local authorities for acceptable exposure limits.

 worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Eyes Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Skin Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. 	Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Personal protectionRespiratory: Chemical splash goggles. Protective clothing must be worn.Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.Eyes: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection: chemical splash goggles.Skin: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.Environmental exposure controls: Emissions from ventilation or work process equipment so the process equipment will be necessary to reduce emissions to acceptable levels.	Engineering measures	: In case of insufficient ventilation, wear suitable respiratory equipment.
Respiratory: Chemical splash goggles. Protective clothing must be worn.Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.Eyes: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection: chemical splash goggles.Skin: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	Hygiene measures	: When using do not eat, drink or smoke.
Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.Eyes: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.Skin: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing For the greatest protection rom static discharges, clothing should include anti-static overalls, boots and gloves.Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	Personal protection	
 worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Eyes Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Skin Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Environmental exposure comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. 	Respiratory	: Chemical splash goggles. Protective clothing must be worn.
 assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Skin Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. 	Hands	during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the
 Environmental exposure controls Environmental exposure controls performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. 	Eyes	assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the
controlsthey comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	Skin	handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static
Other protection : Not available.		they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment
	Other protection	: Not available.

9. Physical and chemical properties

Physical state	: Liquid. [Viscous liquid.]
Flash point	: Closed cup: 25°C (77°F)
Color	: Colorless to light yellow.
Odor	: Characteristic. Fragrance-like.
рН	: 4.5 to 5.5
Boiling/condensation point	: 78.333°C (173°F)
Relative density	: 0.986 to 1

10. Stability and reactivity

Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
Conditions to avoid	: Store away from oxidizing agents. Avoid contact with ignition and heat sources. Keep away from direct sunlight.
Incompatible materials	: Separate from oxidizing materials.
Hazardous decomposition products	: Products of combustion
Possibility of hazardous reactions	: Not available.

11. Toxicological information

United States

Acute toxicity

Product/ingredient name	Result	Dose	Exposure
Alcohol Denat.	•	124700 mg/m³ 7 g/kg 7 g/kg	4 hours - -

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Score	Exposure	Observation
Alcohol Denat.	Eyes - Mild irritant	-	24 hours 500	-
			milligrams	
	Eyes - Moderate irritant	-	0.066666667	-
			minutes 100	
			milligrams	
	Eyes - Moderate irritant	-	100	-
			microliters	
	Eyes - Severe irritant	-	500	-
			milligrams	
	Skin - Mild irritant	-	400	-
			milligrams	
	Skin - Moderate irritant	-	24 hours 20	-
			milligrams	
	Eyes - Moderate irritant	-	0.066666667	-
			minutes 100	
			milligrams	
	Eyes - Moderate irritant	-	100	-
			microliters	
	Eyes - Severe irritant	-	500	-
			milligrams	

11. Toxicological information

			Sk	in - Mild irrita	nt	_		400	-	
			JK	ni - wiiu ii iid	i it	-		milligrams	-	
			Sk	in - Moderate	irritant	-		24 hours 20	-	
								milligrams		
Conclusion/Summary	:	Not available.								
<u>Sensitizer</u>										
Conclusion/Summary	:	Not available.								
Carcinogenicity										
Conclusion/Summary	:	No carcinoge	nic	effect.						
Classification										
Product/ingredient name		ACGIH		IARC	EPA	NIO	SH	NTP	C	OSHA
ethanol		A3		1	-	-		-	-	
Mutagenicity					<u>I</u>				I	
Conclusion/Summary		Not available.								
Teratogenicity										
Conclusion/Summary		Not available.								
Reproductive toxicity	1	Not available.								
Conclusion/Summary		Not available.								
Canada	1									
Acute toxicity										
Product/ingredient name				Result			Dose	•	Ехро	sure
Alcohol Denat.				LC50 Inhala	tion Vapor		1247	00 mg/m³	4 hou	
				LD50 Oral	1		7 g/k	g	-	
				LD50 Oral			7 g/k	g	-	
Conclusion/Summary	:	Not available.								
Chronic toxicity										
Conclusion/Summary	1	Not available.								
Irritation/Corrosion										
Product/ingredient name			R	esult		•	core	Exposure	Oh	servation
Alcohol Denat.				55uit		50				Scivation
				es - Mild irrita	Int	-		24 hours 500		
			Ey	es - Mild irrita		-		milligrams	-	
			Ey			-		milligrams 0.066666667	-	
			Ey	es - Mild irrita		-		milligrams	-	
			Ey Ey	es - Mild irrita	e irritant	-		milligrams 0.066666667 minutes 100 milligrams 100	-	
			Ey Ey Ey	es - Mild irrita es - Moderate es - Moderate	e irritant e irritant	-		milligrams 0.066666667 minutes 100 milligrams 100 microliters	-	
			Ey Ey Ey	es - Mild irrita es - Moderate	e irritant e irritant	- - - -		milligrams 0.066666667 minutes 100 milligrams 100 microliters 500	-	
			Ey Ey Ey	es - Mild irrita es - Moderate es - Moderate	e irritant e irritant ritant			milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400	-	
			Ey Ey Ey Sk	es - Mild irrita es - Moderate es - Moderate es - Severe in in - Mild irrita	e irritant e irritant ritant nt			milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400 milligrams	-	
			Ey Ey Ey Sk	es - Mild irrita es - Moderate es - Moderate es - Severe in	e irritant e irritant ritant nt			milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400 milligrams 24 hours 20	-	
ethanol			Ey Ey Ey Sk	es - Mild irrita es - Moderate es - Moderate es - Severe in in - Mild irrita	e irritant e irritant ritant nt irritant	-		milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400 milligrams	-	
ethanol			Ey Ey Ey Sk Sk	es - Mild irrita es - Moderate es - Moderate es - Severe ir in - Mild irrita in - Moderate es - Mild irrita	e irritant e irritant ritant nt irritant nt			milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400 milligrams 24 hours 20 milligrams 24 hours 500 milligrams	-	
ethanol			Ey Ey Ey Sk Sk	es - Mild irrita es - Moderate es - Moderate es - Severe in in - Mild irrita in - Moderate	e irritant e irritant ritant nt irritant nt			milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 24 hours 20 milligrams 24 hours 500 milligrams 0.0666666667	-	
ethanol			Ey Ey Ey Sk Sk	es - Mild irrita es - Moderate es - Moderate es - Severe ir in - Mild irrita in - Moderate es - Mild irrita	e irritant e irritant ritant nt irritant nt	-		milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 24 hours 20 milligrams 24 hours 500 milligrams 0.066666667 minutes 100	-	
ethanol			Ey Ey Ey Sk Ey Ey	es - Mild irrita es - Moderate es - Moderate es - Severe ir in - Mild irrita in - Moderate es - Mild irrita	e irritant e irritant ritant nt irritant int e irritant	-		milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 24 hours 20 milligrams 24 hours 500 milligrams 0.0666666667	-	
ethanol			Ey Ey Ey Sk Ey Ey	es - Mild irrita es - Moderate es - Moderate es - Severe in in - Mild irrita in - Moderate es - Mild irrita es - Moderate	e irritant e irritant ritant nt irritant e irritant e irritant	-		milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400 milligrams 24 hours 20 milligrams 0.066666667 minutes 100 milligrams 100 milligrams	-	
ethanol			Ey Ey Ey Sk Ey Ey	es - Mild irrita es - Moderate es - Moderate es - Severe ir in - Mild irrita in - Moderate es - Mild irrita es - Moderate	e irritant e irritant ritant nt irritant e irritant e irritant	-		milligrams 0.066666667 minutes 100 milligrams 100 microliters 500 milligrams 400 milligrams 24 hours 20 milligrams 24 hours 500 milligrams 0.066666667 minutes 100 milligrams 100	-	

 Fantastic Finish Finishing Spritz 55% VOC

 11. Toxicological information

 Skin - Mild irritant
 milligrams 400

 Skin - Moderate irritant
 400

 Skin - Moderate irritant
 milligrams 24 hours 20

 Conclusion/Summary
 :
 Not available.

 Sensitizer

Conclusion/Summary : Not available. Carcinogenicity

Conclusion/Summary : Not available.

Classification						
Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanol	A3	1	-	-	-	-

Mutagenicity

Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
<u>Mexico</u>	

Acute toxicity

Product/ingredient name	Result	Dose	Exposure
Alcohol Denat.	LC50 Inhalation Vapor	124700 mg/m³	4 hours
	LD50 Oral	7 g/kg	-
	LD50 Oral	7 g/kg	-

Conclusion/Summary	: Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Score	Exposure	Observation
Alcohol Denat.	Eyes - Mild irritant	-	24 hours 500	-
			milligrams	
	Eyes - Moderate irritant	-	0.066666667	-
			minutes 100	
			milligrams	
	Eyes - Moderate irritant	-	100	-
			microliters	
	Eyes - Severe irritant	-	500	-
			milligrams	
	Skin - Mild irritant	-	400	-
			milligrams	
	Skin - Moderate irritant	-	24 hours 20	-
			milligrams	
ethanol	Eyes - Mild irritant	-	24 hours 500	-
			milligrams	
	Eyes - Moderate irritant	-	0.066666667	-
			minutes 100	
			milligrams	
	Eyes - Moderate irritant	-	100	-
			microliters	

	ritz 55% VC					
11. Toxicological in	nforma	tion				
		Eyes - Seve	re irritant	-	500	-
		Skin - Mild ir	ritant	_	milligrams 400	_
					milligrams	
		Skin - Mode	rate irritant	-	24 hours 20	-
Conclusion/Summary	: Not avail				milligrams	
Conclusion/Summary Sensitizer	. NUL avai					
Conclusion/Summary	: Not avail	able				
Carcinogenicity	i riot ara					
Conclusion/Summary	: Not avail	able.				
Classification						
Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanol	A3	1	-	-	-	-
Mutagenicity	1		I	1		
matagomony	: Not avail	able.				
Conclusion/Summary	·					
	i not avai					
Conclusion/Summary	: Not avail	able.				
Conclusion/Summary Teratogenicity		able.				

12. Ecological information

THE FOLLOWING DATA IN THIS SECTION IS SOURCED FROM PUBLICLY AVAILABLE DATABASES AND NOT THE REPRESENTATION OF ANY DATA COLLECTED BY ZOTOS INTERNATIONAL OR ITS AFFILIATES.

Ecotoxicity

: No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Alcohol Denat.	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
Conclusion/Summary	Not available.		•
Persistence/degradability			
Conclusion/Summary	: Not available.		

Conclusion/Summary	: Not available
<u>Canada</u>	

Aquatic ecotoxicity

12. Ecological information

Product/ingredient name	Result	Species	Exposure
Alcohol Denat.	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks

Conclusion/Summary

Persistence/degradability

Conclusion/Summary : Not available.

: Not available.

<u>Mexico</u>

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Alcohol Denat.	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
Conclusion/Summary	: Not available.		

Persistence/degradability

Conclusion/Summary : Not available.

13. Disposal considerations

Waste disposal	: Dispose of according to all federal, state and local applicable regulations.
Contaminated packaging	: Waste must be disposed of according to applicable regulations. This material and its container must be disposed of as hazardous waste. Recycle, if possible. Dispose of empty containers and waste safely.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

14. Transpor	t informa	tion				
Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1993	Flammable liquids, n.o.s. (Alcohol Denat.	3	11		Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: 5 L Cargo aircraft Quantity limitation: 60 L Special provisions IB2, T7, TP1, TP8, TP28
TDG Classification	UN1993	FLAMMABLE LIQUID, N.O. S. (Alcohol Denat., ethanol)	3	II		Explosive Limit and Limited Quantity Index 1 Passenger Carrying Road or Rail Index 5 Special provisions 16
Mexico Classification	UN1993	LIQUIDO INFLAMABLE, N. E.P. (Alcohol Denat., ethanol)	3	11		Special provisions 274
ADR/RID Class	UN1993	FLAMMABLE LIQUID, N.O. S. (Alcohol Denat., ethanol)	3	11		Hazard identification number 33Limited quantity LQ4Special provisions 601 274 640CTunnel code (D/E)
		9507				10/42

Fantastic Finish Fir	nishing Spritz	55% VOC				
14. Transpo	rt inform	ation				
IMDG Class	UN1993	FLAMMABLE LIQUID, N.O. S. (Alcohol Denat., ethanol)	3	II		Emergency schedules (EmS) F-E, _S-E_ Special provisions 274
IATA-DGR Class	UN1993	Flammable liquid, n.o.s. (Alcohol Denat., ethanol)	3	II	Y	Passenger and Cargo AircraftQuantity limitation: 5 L Packaging instructions: 305Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 307Packaging instructions: 307Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions: Y305Special provisions A3

PG* : Packing group

15. Regulatory info	ormation
United States	
HCS Classification	: Flammable liquid Irritating material Carcinogen Target organ effects
U.S. Federal regulations	: TSCA : Exempt
	SARA 302/304: No products were found. SARA 311/312 Hazards identification: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
State regulations	
Massachusetts	: The following components are listed: ETHYL ALCOHOL; ETHYL ALCOHOL

15. Regulatory information

New York	: None of the components are listed.
New Jersey	 The following components are listed: ETHYL ALCOHOL; ALCOHOL; ETHYL ALCOHOL; ALCOHOL
Pennsylvania	The following components are listed: DENATURED ALCOHOL; DENATURED ALCOHOL
<u>California Prop. 65</u>	
	ION 65: The following statement is made in order to comply with the California Safe Drinking nent Act of 1986. This product is not known to the State of California to cause cancer.
United States inventory (TSCA 8b)	: Not determined.
<u>Canada</u>	
WHMIS (Canada)	: Class B-2: Flammable liquid Class D-2B: Material causing other toxic effects (Toxic).
<u>Canadian lists</u>	
Canadian NPRI	: The following components are listed: Ethanol; Ethanol
CEPA Toxic substances	: None of the components are listed.
Canada inventory	: Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

<u>Mexico</u>

Classification



International regulations Chemical Weapons Convention List Schedule I Chemicals	: Not listed
Chemical Weapons Convention List Schedule II Chemicals	: Not listed
Chemical Weapons Convention List Schedule III Chemicals	: Not listed

2

16. Other information

Hazardous Material	:			
Information System (U.S.A.)				
	Health	2		



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

16. Other information

The customer is responsible for determining the PPE code for this material.

÷.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing	: 8/12/2014.
Date of issue	: 8/12/2014.
Date of previous issue	: No previous validation.
Version	: 0.01
Prepared by	: Regulatory Affairs Group

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.