

B-9806D

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1. SDS Revision Date: 10/4/2016

	1. PRODUCT & COMPANY IDENTIFICATION				
1.1	Product Name:	GIBS Brawler Bantam Weight Hairs Spray			
1.2	Chemical Name:	Aerosol			
1.3	Synonyms:	Gibs Brawler Bantam Weight Hair Spray 55%VOC – B9806D			
1.4	Trade Names:	Brawler Bantam Weight Hair spray			
1.5	Product Uses & Restrictions	Professional and Cosmetic Use			
1.6	Distributor's Name:	KIK Custom Products			
1.7	Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA			
1.8	Emergency Phone:	CHEMTEL: +1 (800) 255-3924			
1.9	Business Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954			

#### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

<u>Classification:</u> Aerosol level 1; Category 2 Flammable aerosol; Eye Irrit. 2

<u>Hazard Statements</u> (H): H-223 – Flammable Aerosol. H229 – Pressurized container: may burst if heated. H320 – Causes eye irritation.

Precautionary Statement (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P410+P412 – Protect from sunlight. Do no expose to temperature exceeding 50°C (122 °F). P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.



### 3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
ETHANOL (SD ALCOHOL 40B)	64-17-5	200-578-6	30-60	Flam. Liq. 2; H225
DIFLUOROETHANE (R-152a)	75-37-6	200-866-1	30-45	Flam. Gas 1; H220

### 4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		<u>Eyes:</u>	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes.  Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Ingestion: depr		If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
			May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
Eyes: Moderately irritating to the eyes.			Moderately irritating to the eyes.
		Inhalation:	Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion,



B-9806D

			and difficulty breathing. Inhalation of concentrated	vapors can cause n	nervous system	n depression			
			(e.g., drowsiness, dizziness, headaches, nausea).						
4.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and cer						
		Skin	Prolonged contact with skin may result in bleaching a						
		<u>SKIII.</u>	Skin: allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas.						
		Overexposure in eyes, may cause redness, itching and watering (risk of serious damage to eyes)							
		Contact may cause mild eye irritation including stinging, watering and redness.							
		Inhalation:	Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing.						
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.							
4.5	Chronic Health Effects:	No harmful or cl be irritating to s symptoms in so allergic dermati	nronic health effects are expected to occur from a sing kin and mucous membrane of the eye and respiratory me sensitive individuals. May also induce skin sensitiz tis.	system. Overexpo	osure may trig	ger asthma-like			
4.6	Target Organs:	Eyes, skin, respi		115 41 511					
4.7	Medical Conditions		zards may be delayed. Most common symptoms	HEALTH	,	1			
	Aggravated by Exposure		g properties to eyes, respiratory system and skin.  Diogical conditions (such as eczema) and respiratory	PHYSICAL HAZA		3			
		_	as bronchial asthma and/or bronchitis) may be	PROTECTIVE EC		В			
		exacerbated.		EYES	SK				
					IN				
5.2	Extinguishing Methods:		vith water until the fire has been extinguished. n, CO <sub>2</sub> , Dry Chemical			<b>A.5</b>			
	Firefighting Procedures:	demand_ and fu spray to cool fire from fire contro waterway. Firef contained breat	ear MSHA/NIOSH approved self-contained breathing a full protective gear. Keep containers cool until well afte e-exposed surfaces and to protect personnel. Fight fir I or dilution from entering sewers, drains, drinking wa ighters must use full bunker gear including NIOSH-app hing apparatus to protect against potential hazardous products and oxygen deficiencies.	er the fire is out. Le upwind. Preventer supply, or any proved positive pre	Jse water t runoff natural	10			
5.3	Firefighting Procedures:	demand_ and fu spray to cool fir from fire contro waterway. Firef contained breat decomposition p	ear MSHA/NIOSH approved self-contained breathing a ill protective gear. Keep containers cool until well afte e-exposed surfaces and to protect personnel. Fight fir I or dilution from entering sewers, drains, drinking wa ighters must use full bunker gear including NIOSH-app hing apparatus to protect against potential hazardous	er the fire is out. Use upwind. Preventer supply, or any proved positive precombustion or	Jse water t runoff natural	10			
	Spills:	demand_ and fu spray to cool fire from fire control waterway. Fireformal contained breat decomposition produced decomposition produced Equipment (PPE Small spills Weat combustible materials (e.g., produced) materials (e.g., produced) container. Large spills: Keeterelease. Isolate	ear MSHA/NIOSH approved self-contained breathing a sill protective gear. Keep containers cool until well after e-exposed surfaces and to protect personnel. Fight fir I or dilution from entering sewers, drains, drinking was ighters must use full bunker gear including NIOSH-apphing apparatus to protect against potential hazardous products and oxygen deficiencies.  5. ACCIDENTIAL RELEASE MEASUR any spill or leak, individuals involved in spill cleanup measurements.	er the fire is out. Use upwind. Preventer supply, or any proved positive precombustion or  ES  Bust wear appropriate and place into a field. Sweep up mat stic container or provey from spill. Staymel out of area. S	Jse water t runoff natural essure self- iate Personal F ctive eyewear a container for erial using nor clastic liner wit y upwind and a	. Use a non- r later disposal. n-sparking hin another away from spill o ease if it can be			
5.3		demand_ and fuspray to cool firm from fire control waterway. Firefunction contained breat decomposition per decompositio	ear MSHA/NIOSH approved self-contained breathing a sill protective gear. Keep containers cool until well after e-exposed surfaces and to protect personnel. Fight fir I or dilution from entering sewers, drains, drinking was ighters must use full bunker gear including NIOSH-apphing apparatus to protect against potential hazardous products and oxygen deficiencies.  5. ACCIDENTIAL RELEASE MEASUR any spill or leak, individuals involved in spill cleanup m.).  7. appropriate personal protective equipment including terial such as vermiculite or sand to soak up the product or a material such as "speedy dry" to soak up material satic brooms, shovels, dustpans) and place into a plate procedure in the product of t	er the fire is out. Use upwind. Preventer supply, or any proved positive precombustion or  ES  The substitute of the sub	Jse water t runoff natural essure self- iate Personal F ctive eyewear a container for erial using nor clastic liner wit y upwind and a	. Use a non- r later disposal. n-sparking hin another away from spill o ease if it can be			
5.3		demand_ and fuspray to cool firm from fire control waterway. Firefus contained breat decomposition per section of the section	ear MSHA/NIOSH approved self-contained breathing a self protective gear. Keep containers cool until well after e-exposed surfaces and to protect personnel. Fight fir I or dilution from entering sewers, drains, drinking was righters must use full bunker gear including NIOSH-app hing apparatus to protect against potential hazardous products and oxygen deficiencies.  6. ACCIDENTIAL RELEASE MEASUR any spill or leak, individuals involved in spill cleanup m.).  7. appropriate personal protective equipment including terial such as vermiculite or sand to soak up the product or a material such as "speedy dry" to soak up material satic brooms, shovels, dustpans) and place into a pla procedure incompatible materials (e.g., organics such as oil) aw immediate hazard area and keep unauthorized personal	er the fire is out. Use upwind. Preventer supply, or any proved positive precombustion or  ES  Thust wear appropriate and place into a field. Sweep up mat stic container or proved positive precombustion or proved	Jse water t runoff natural essure self- iate Personal F ctive eyewear a container for erial using nor elastic liner wit y upwind and a stop spill or rel protection as container as container	. Use a non- r later disposal. n-sparking hin another away from spill o ease if it can be onditions			



B-9806D

		Use and store in a cool dry	well-ventilate	nd locatio	n le a loc	al evhaust	ventilation	fans) av	vay from	heat and direct
7.2	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and dire storage and Handling: Storage and Handling:									
		physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 2.								
7.3	Special Precautions:	Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.								
		8. EXPOSURE CO	NTROLS	8 PE	RSON/	AL PRO	TECTIO	N		
8.1	Exposure Limits:		ACGI			NOHSC			SHA	OTHER
0.1	Ppm (mg/m³)		71001			1101150		0.	,,,,,	T
	, ,		<b></b>	6751	56 T1444	50 0 <del>7</del> 51	EC DEAL	551	C <del></del> E1	
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	
		Chemical Name(s)								
		ETHANOL(SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	
		DIFLOROETHANE (R-152a)	1000	NA	1000	NA	NA	NE	NA	
8.2	Ventilation & Engineering Controls	General mechanical (e.g., far exhaust ventilation to effecti product.	•				•			-
8.3	Respiratory Protection:	No special respiratory protection instances where dusts of the use only protection authorized Canadian CAS Standard Z94.4 States, or Australia.	his product a ed by 29 CFR	re genera §1910.13	ated, and r 84, applical	espiratory ble U.S. Sta	protection te regulation	is neede ons, or th	d, ie	
3.4	Eye Protection:	None required under normal conditions of use. Avoid eye contact. Safety glasses should be used when handling or using large quantities of this product (e.g., ≥ 1 gallon (3.8 L)).								
3.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., $\geq 1$ gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.								
3.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs.), eye wash station and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.								
									•	
		9. PHYSIC	AL & CH	<b>EMIC</b>	AL PRO	PERTII	ES			
9.1	Appearance:	Aerosol, clear misty spray of	liquid							
9.2	Odor:	Fresh Floral								
9.3	Odor Threshold	NA								
9.4	pH:	NA								
9.5	Melting/Freezing Point	NA								
9.6	Initial Boiling Point/ Boiling Range:	NA								
9.7	Flashpoint:	-30 °F (-34 °C) TCC for propel	lant only 25	6 °E 12 °C	) FDA mo+l	hod 1010 /	concentrate	e Only)		
).7	Upper/Lower	NA	iani Uniy. 35.	U 1 (2 C	, LFA IIIEU	100 TOTO (	concentiati	e orny)		
	Flammability limits									
.9	Vapor Pressure:	@ 20 °C (68° F) – Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar								
.10	Vapor Density	>1			-					
	Relative Density:	0.81-0.85								
	Solubility:	Soluble								-
.13	Partition Coefficient (log Pow):	NA								
9.14	Autoignition Temperature:	NA								
9.15	Decomposition	NA								
	Temperature.									



B-9806D

9.16	Viscosity:	Aerosol at ambient temperature						
9.17	Other Information:	Evaporation Rate >1: Percent Volatile 55%						
		10. STABILITY & REACTIVITY						
10.1	Stability:	Stable at normal temperatures.						
10.2		Stable at normal temperatures.						
10.2	Decomposition	Oxides of carbon (CO, CO <sub>2</sub> ) and sulfur (SO <sub>2</sub> )						
	Products:							
10.3								
20.5	Polymerization:	Will not occur.						
10.4	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.						
	Incompatible Substances							
	· · · · · · · · · · · · · · · · · · ·							
		11. TOXICOLOGICAL INFORMATION						
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingesti on: YES						
11.2	Toxicity Data:	This product was not tested on animals. Toxicology data, found in scientific literature, is available and not presented in						
		this document. <u>Hydrofluorocarbon-152a:</u> LC <sub>50</sub> (inh, 2 h, mouse): 977 g/m <sup>3</sup>						
11.3	Acute Toxicity:	See Section 4.4						
11.4	Chronic Toxicity:	See Section 4.5						
11.5	Suspected Carcinogen:	No.						
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.						
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.						
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.						
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.						
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.						
11.7	Irritancy of Product:	See Section 4.3						
11.8	Biological Exposure	NA .						
	Indices:	NA						
11.9	Physician	Treat symptomatically.						
	Recommendations:	Treat symptomatically.						
		12. ECOLOGICAL INFORMATION						
12.1		There is no specific data available for this product.						
12.2	Effects on Plants &	There is no specific data available for this product.						
	Animals							
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.						
		13. DISPOSAL CONSIDERATIONS						
12.1	W	T						
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with						
		local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed						
12.2	facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.  3.2 Special Considerations: U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)							
13.2	Special Considerations.	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)						
		14. TRANSPORTATION INFORMATION						
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or						
		CONSUMER COMMODITY, ORM-D (IP VOL $\leq$ 1.0 L) – until 12/31/2020						
14.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or						
	, ,	ID8000, CONSUMER COMMODITY, ORM-D (IP VOL < 0.5 I=L)						
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)						
	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or						
MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"								
14.5	.5 ADR/RID (EU): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)							
	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL < 1.0 L)						
	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)						



B-9806D

		15. REGULATORY INFORM	IATION				
	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requirements.					
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.					
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.					
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2270 kg; 5000 lbs.					
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics)					
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List.  WHMIS Class B5 (Flammable Aerosol)					
15.7	State Regulatory Information:	Ethanol is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Pennsylvania Right-to-Know list (PA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ).  Difluoroethane can be found on the following state criteria lists: MA and NJ.  No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).					
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Ethanol:</u> Flammable (F). <u>Risk Phrases</u> *: 11 – Flammable. <u>Safety Phrases</u> (S): 2-7-16 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking.					
		16. OTHER INFORMAT	ION				
16.1	Other Information:	<b>AND VAPOR. CAUSES EYE IRRITATION.</b> Keep away from he sources. No Smoking. Do not spray on an open flame or ot	ther ignition source. Do not pierce or burn, even after use. and water after handling. Use only in a well ventilated area. to temperature exceeding 50 °C (122 °F). IF INHALED: hing. IF IN EYES: Rinse cautiously with water for several				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.					
16.4	Prepared By:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA Tel: +1 (770) 534-0300 Fax: +1 (770) 534-8954 http://www.kikcorp.com	KIK CUSTOM PRODUCTS				




B-9806D

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.

SDS Revision Date: 10/4/2016





B-9806D

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.

SDS Revision Date: 10/4/2016

