SAFETY DATA SHEET

I.C.E. HAIR SPIKER Styling Glue

Section 1. Identification

Product Name	: I.C.E. HAIR SPIKER Styling Glue
Other means of identification	: Not available.
Recommended use	: Hair Care Product
Restrictions on use	: Use only as directed on the product label.
Manufacturer	: Zotos International, INC 100 Tokeneke Road, Darien, CT 06820 www.zotos.com
Validation date	: 3/12/2015.
In case of emergency	: (800) 584-8038 [24 Hours]
<u>Telephone number</u>	: (203) 656-7859 [8:30 a.m 5:00 p.m.]
Transportation Emergency	: Contact: CHEMTREC 1-800-424-9300 [US/Canada 24 Hours]
Product type	: Liquid.

Section 2. Hazards identification

Emergency overview

NOT EXPECTED TO PRO INSTRUCTIONS FOR USE	DUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED E ARE FOLLOWED.		
OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).		
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 4		
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 92.7%		
GHS label elements			
Signal word	: Warning		
Hazard statements	: Combustible liquid.		
Precautionary statements			
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.		
Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from flames and hot surfaces No smoking.		
Response	: Not applicable.		
Storage	: Store in a well-ventilated place. Keep cool.		
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. 		
Hazards not otherwise classified	: None known.		

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

United States

Name	%	CAS number
Octadecan-1-ol, ethoxylated	3.80	9005-00-9
Ethyl alcohol	2.00	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. May cause eye irritation.
Inhalation	: Move affected person to fresh air.
Skin contact	 Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. Discontinue use of product Apply cold compresses to affected areas to relieve any discomfort Seek medical attention if irritation persists.
Ingestion	: Have conscious person drink several glasses of water or milk. Do not induce vomiting. Get medical attention if adverse health effects persist or are severe.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Section 5. Fire-fighting measures

Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if
for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for co	nta	ainment and cleaning up		
Small spill	:	Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble.		

Large spill : Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	contae adequ and us explos	appropriate personal protective equipment (see Section 8). Do not ingest. Avoid ct with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with ate ventilation. Wear appropriate respirator when ventilation is inadequate. Store se away from heat, sparks, open flame or any other ignition source. Use sion-proof electrical (ventilating, lighting and material handling) equipment. Use on-sparking tools.
Advice on general occupational hygiene	handle equip	I, drinking and smoking should be prohibited in areas where this material is ed, stored and processed. Remove contaminated clothing and protective ment before entering eating areas. See also Section 8 for additional information giene measures.
Conditions for safe storage, including any incompatibilities	direct (see S	in accordance with local regulations. Store in original container protected from sunlight in a dry, cool and well-ventilated area, away from incompatible materials section 10) and food and drink. Eliminate all ignition sources. Separate from ng materials.

Section 8. Exposure controls/personal protection

United States

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits			
Ethyl alcohol	STEL: 1000 ppm 15 minute OSHA PEL 1989 (United St TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours. NIOSH REL (United States, TWA: 1000 ppm 10 hours. TWA: 1900 mg/m³ 10 hours. TWA: 1900 mg/m³ 10 hours. TWA: 1000 ppm 8 hours.	ACGIH TLV (United States, 6/2013). STEL: 1000 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013).		
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exorter engineering controls to keep worker exposure to airborne contar recommended or statutory limits. The engineering controls also need vapor or dust concentrations below any lower explosive limits. Use expendituation equipment.	minants below any to keep gas,		
Environmental exposure controls	they comply with the requirements of environmental protection legisla	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
ndividual protection measure	<u>lres</u>			
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical p eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contami Wash contaminated clothing before reusing. Ensure that eyewash sta showers are close to the workstation location.	period. nated clothing.		
Eye/face protection	: Safety eyewear complying with an approved standard should be used assessment indicates this is necessary to avoid exposure to liquid spl gases or dusts. If contact is possible, the following protection should the assessment indicates a higher degree of protection: safety glasse shields.	ashes, mists, be worn, unless		
Skin protection				
Hand protection	: Wear suitable gloves.			
Body protection	 Personal protective equipment for the body should be selected based performed and the risks involved and should be approved by a specia handling this product. 			
Other skin protection	 Appropriate footwear and any additional skin protection measures sho based on the task being performed and the risks involved and should specialist before handling this product. 			
Other skin protection	: Appropriate footwear and any additional skin protection measures sho based on the task being performed and the risks involved and should specialist before handling this product.			

Section 8. Exposure controls/personal protection

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid. [Viscous liquid.]
Color	: Clear. Colorless.
Odor	: Odorless.
рН	: 3 to 4.5
Boiling point	: >100°C (>212°F)
Flash point	: Closed cup: 70°C (158°F)
Relative density	: 0.99 to 1.1

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

United States

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl alcohol	LC50 Inhalation Vapor	Rat	124700 mg/m³	4 hours
	LD50 Oral	Rat	7 g/kg	-

Irritation/Corrosion

5420L	
01201	

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Octadecan-1-ol, ethoxylated	Skin - Moderate irritant	Man	-	48 hours 20 Percent	-
Octadecan-1-ol, ethoxylated	Skin - Moderate irritant	Man	-	48 hours 20 Percent	-
Ethyl alcohol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.0666666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol	-	1	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Section 11. Toxicological information

aracteristics
ort and long term exposure
ical hazards.

Not available.

Section 12. Ecological information

United States

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 µg/l Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna	96 hours 48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
	Acute LC50 42000 µg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Fish - Oncorhynchus mykiss Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	4 days 96 hours 12 weeks

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Ethyl alcohol	-0.35	-	low

Mobility in soil

5420L

Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not Regulated	-	-	-		-
TDG Classification	Not regulated.	-	-	-		
Mexico Classification	Not regulated.	-	-	-		
ADR/RID Class	Not regulated.	-	-	-		
IMDG Class	Not regulated.	-	-	-		
IATA-DGR Class	Not regulated.	-	-	-		-

PG* : Packing group

Section 15. Regulatory information

U.S. Federal regulations	TSCA 8(a) PAIR: 4-(4-hydroxy-4-methylpentyl)cyclohex-3-enecarbaldehyde; cinnamaldehyde; 2-(4-tert-butylbenzyl)propionaldehyde TSCA 8(a) CDR Exempt/Partial exemption: Not determined	
	United States inventory (TSCA 8b): Not determined.	
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Not listed	
Clean Air Act Section 602 Class I Substances	Not listed	
Clean Air Act Section 602 Class II Substances	Not listed	
DEA List I Chemicals (Precursor Chemicals)	Not listed	
DEA List II Chemicals (Essential Chemicals)	Not listed	
<u>SARA 302/304</u>		

5420L

Section 15. Regulatory information

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Octadecan-1-ol, ethoxylated	3.80	No.	No.	No.	Yes.	No.
Octadecan-1-ol, ethoxylated	3.80	No.	No.	No.	Yes.	No.
Ethyl alcohol	2.00	Yes.	No.	No.	Yes.	No.

State regulations Massachusetts

: The following components are listed: ETHYL ALCOHOL

New York

: None of the components are listed.

New Jersey Pennsylvania

The following components are listed: ETHYL ALCOHOLThe following components are listed: DENATURED ALCOHOL

California Prop. 65

This product does not contain chemicals known to the State of California to cause cancer.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

t

Not listed.

Canada

WHMIS (Canada)	: Class D-2B: Material causing other toxic effects (Toxic).
Canadian lists	
Canadian NPRI	: The following components are listed: Ethanol
CEPA Toxic substances	: None of the components are listed.
Canada inventory	: Not determined.
This product has been class	ified in accordance with the hazard criteria of the Controlle

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

<u>Mexico</u>

Classification

Section 15. Regulatory information



Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

H	S	to	ry	

Date of printing	: 3/12/2015.
Date of issue/Date of revision	: 3/12/2015.
Date of previous issue	: No previous validation.
Version	: 0.01
References	: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 3/12/2015. Date of previous issue : No previous validation. Version : 0.01 10/	Date of issue/Date of revision	: 3/12/2015.	Date of previous issue	: No previous validation.	Version	: 0.01	10/10
---	--------------------------------	--------------	------------------------	---------------------------	---------	--------	-------