KIK CUSTOM PRODUCTS

SAFETY DATA SHEET

Page **1** of **7**

KIK – B-9814

	Prepared to OSHA, ACC, ANS	I, NOHSC, WHM	IIS, 2001/58 & 1272/20	08/EC Standards	SDS Revision: 1.0	SDS Revision Date: 9-1-	-2016		
		1.	PRODUCT & (COMPANY	IDENTIFICATION				
1.1	Product Name:	Kenra Higł	n Grip 20 Hairspra	ay					
1.2	Chemical Name:	-	•	-					
1.3	Synonyms:		Grip 20 Hairspray 55%V	OC – B-9814					
1.4	Trade Names:	High Grip 20 H	lairspray						
1.5	Product Uses/ Restrictions	Professional a	nd Cosmetic Use						
1.6	Distributor's Name:	KIK Custom Pr	oducts						
1.7	Distributor's Address:		2740 Middlebury Street, Elkhart, Indiana 46515						
1.8	Emergency Phone:	Poison Cont	son Control Center (Medical): (866) 366-5048; CHEMTREC: +1 (<u>800) 424-9300 /+1 (703)527-3887</u>						
1.9	Business Phone / Fax:	+1 (574) 295-0	0000 / +1 (574) 295-170	9					
			2. HAZARD	S IDENTIFIC	CATION				
2.1	Hazard Identification:	This product is	classified as a HAZARD	OUS SUBSTANCE	and as DANGEROUS GOOI	DS according to the			
		WARNING! F	LIQUID AND VAPOR. C	PRESSURIZED CO AUSES EYE IRRITA	ONTAINER: MAY BURST IF ATION.	HEATED. HIGHLY			
			Level 1 Aerosol; Categ						
			ients (H): H-223– Flam s eye irritation.	mable Aerosol. H	229–Pressurized container	. may purst if heated.			
			<u>Statement</u> (P):						
				faces, sparks, ope	n flames and other ignitior	n sources. No Smoking.			
			spray on an open flam		-	0	$\langle \mathcal{M} \rangle$		
			pierce or burn, even af						
			preathing vapors/spray.				•		
			ly in well-ventilated are						
					and keep comfortable for b	0 – IF INHALED; Remove person to fresh air and keep comfortable for breathing.			
		2305+2351+3		an fan aan ianal matanitaa Dan					
		present, conti	nue rinsing.	-	er for several minutes. Rer	nove contact lenses, if			
		present, conti P337+P313 – I	nue rinsing. f eye irritation persists:	Get medical advi	ce/attention.				
		present, conti P337+P313 – I P410+P412 – I	nue rinsing. f eye irritation persists: Protect from sunlight. D	Get medical advi o no expose to te	ce/attention. emperature exceeding 48°C	C (120 °F).			
		present, conti P337+P313 – I P410+P412 – I	nue rinsing. f eye irritation persists: Protect from sunlight. D	Get medical advi o no expose to te	ce/attention.	C (120 °F).			
		present, conti P337+P313 – P410+P412 – P501 – Dispos	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container	Get medical advi to no expose to te to licensed and p	ce/attention. emperature exceeding 48°C permitted disposal or recyc	C (120 °F). ling facility.			
Su	bstance / Chemical Name(s)	present, conti P337+P313 - P410+P412 - P501 - Dispos 3.	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION	Get medical advisor on expose to termination of the second	ce/attention. emperature exceeding 48°C permitted disposal or recyc IENT INFORMAT	C (120 °F). ling facility.			
	bstance / Chemical Name(s)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No.	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No.	Get medical advi to no expose to te to licensed and p I & INGRED %	ce/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other	C (120 °F). ling facility.			
	UOROETHANE (R-152a)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1	Get medical advi to no expose to te to licensed and p I & INGRED % 30– 50	ce/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220	C (120 °F). ling facility.			
	UOROETHANE (R-152a) Butane	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7	Get medical advi to no expose to te to licensed and p I & INGRED %	ice/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220	C (120 °F). ling facility.			
	UOROETHANE (R-152a)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1	Get medical advisor on expose to terms to licensed and point of the second seco	ce/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220	C (120 °F). ling facility.			
	UOROETHANE (R-152a) Butane	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 4. FIRST	Get medical advisor on expose to terms of the licensed and point of th	ice/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225	C (120 °F). ling facility.			
DIFL	UOROETHANE (R-152a) Butane	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu	Get medical advisor on expose to terms to licensed and point of the second seco	ice/attention. emperature exceeding 48°C permitted disposal or recyce DIENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallowed	C (120 °F). ling facility. ION d, drink plenty of water o			
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 4. FIRST If ingested, do not indu IMMEDIATELY. If the p	Get medical advisor on expose to terest to licensed and point of the second sec	ice/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water co	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water	or milk to ar		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 4. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C	Get medical advisor on expose to terms of the licensed and provide the licensed and provide the licensed and provide the licensed and provide the licensed advisor. The license of the lic	ice/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water of st Poison Control Center of	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe	or milk to ar r. Provide ar		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at	Get medical advisor on expose to terms of the licensed and provide the licensed and provide the licensed and provide the licensed and provide the licensed advisor. The license of the lic	ice/attention. emperature exceeding 48°C permitted disposal or recyce IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water co	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe	or milk to ar r. Provide ar		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed.	Get medical advisor on expose to terror to licensed and provide the second seco	ice/attention. emperature exceeding 48°C permitted disposal or recycle IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water of st Poison Control Center of ial was ingested and the an	C (120 °F). ling facility. ION d, drink plenty of water o r milk. Never give water local emergency numbe nount of the substance to	or milk to ar r. Provide ar hat was		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr	Get medical advisor on expose to ter to licensed and p I & INGRED % 30–50 5 - 15 20 - 40 AID MEASI ace vomiting! If p patient is vomiting contact the neares t which the mater	ice/attention. emperature exceeding 48°C permitted disposal or recyclo IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water of the poison Control Center of rial was ingested and the and stin, rinse thoroughly with lage	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed	or milk to ar r. Provide ar hat was I by a thorou		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected	Get medical advisor on expose to ter to licensed and p I & INGRED % 30–50 5 - 15 20 - 40 AID MEASI ace vomiting! If p patient is vomiting contact the neares which the mater	ice/attention. emperature exceeding 48°C permitted disposal or recyclo IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water of the poison Control Center of rial was ingested and the and sin, rinse thoroughly with lar y of soap and water. Remo	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed we contaminated clothing	or milk to ar r. Provide ar hat was I by a thorou g and wash		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before ruse	Get medical advisor on expose to tere to licensed and period of the second seco	ice/attention. emperature exceeding 48°C permitted disposal or recyclessing IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallowed g, continue to offer water of ial was ingested and the and the and sin, rinse thoroughly with ling y of soap and water. Remo	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immed	or milk to ar r. Provide ar hat was I by a thorou g and wash liately.		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5 Ingestion:	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before ruse If product get in the ey	Get medical advisor on expose to tere to licensed and performance of the second	ice/attention. emperature exceeding 48°C permitted disposal or recycle IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallowed g, continue to offer water of tal was ingested and the and stin, rinse thoroughly with ling y of soap and water. Remode Insess or swelling persists, co- pious amounts of lukewarm	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immediant	or milk to ar r. Provide ar hat was I by a thorou g and wash liately. nutes. Raise		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before ruse If product get in the ey and lower eyelid(s) wh	Get medical advisor on expose to tere to licensed and performance of the second	ice/attention. emperature exceeding 48°C permitted disposal or recyclessing IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallowed g, continue to offer water of ial was ingested and the and the and sin, rinse thoroughly with ling y of soap and water. Remo	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immediant	or milk to ar r. Provide ar hat was I by a thorou g and wash liately. nutes. Raise		
DIFL	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5 Ingestion:	nue rinsing. f eye irritation persists: Protect from sunlight. D e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before ruse If product get in the ey and lower eyelid(s) wh medical attention.	Get medical advisor on expose to terrest to licensed and provide the second sec	ice/attention. emperature exceeding 48°C permitted disposal or recycle IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallowed g, continue to offer water of the st Poison Control Center of tial was ingested and the and kin, rinse thoroughly with ling y of soap and water. Remode liness or swelling persists, co pious amounts of lukewarm sure thorough irrigation. If	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immediant	or milk to an r. Provide an hat was I by a thorou g and wash diately. nutes. Raise		
4.1	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B)	present, conti P337+P313 – I P410+P412 – I P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5 Ingestion: Skin: Eyes: Inhalation: Ingestion:	nue rinsing. f eye irritation persists: Protect from sunlight. De e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 COMPOSITION A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before russ If product get in the ey and lower eyelid(s) wh medical attention. Remove victim to fresh If product is swallowed	Get medical advisor on expose to terms of the licensed and provide the licensed and provide the licensed and provide the licensed and provide the licensed advisor of the license the lice	ice/attention. emperature exceeding 48°C permitted disposal or recycle IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallowed g, continue to offer water of tal was ingested and the and stin, rinse thoroughly with ling y of soap and water. Remode Insess or swelling persists, co- pious amounts of lukewarm	c (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe nount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immed on water for at least 15 min problems persist seek im	or milk to ar r. Provide ar hat was I by a thorou g and wash liately. nutes. Raise mediate		
	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B) First Aid:	present, conti P337+P313 – P410+P412 – P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5 Ingestion: Skin: Eyes: Inhalation: Ingestion:	nue rinsing. f eye irritation persists: Protect from sunlight. De e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 COMPOSITION A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before russe If product get in the ey and lower eyelid(s) wh medical attention. Remove victim to fresh If product is swallowed depression.	Get medical advisor on expose to terest to licensed and provide the second seco	ice/attention. emperature exceeding 48°C permitted disposal or recycle IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water of st Poison Control Center or ial was ingested and the and kin, rinse thoroughly with he y of soap and water. Remode iness or swelling persists, co- bious amounts of lukewarm sure thorough irrigation. If infortable for breathing. tea, vomiting and/or diarrh	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe mount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immed on water for at least 15 min problems persist seek im ea and central nervous sy	or milk to ar r. Provide ar hat was I by a thorou g and wash liately. nutes. Raise mediate ystem		
4.1	UOROETHANE (R-152a) Butane Ethanol (SD Alcohol 40B) First Aid:	present, conti P337+P313 – I P410+P412 – I P501 – Dispos 3. CAS No. 75-37-6 106-97-8 64-17-5 Ingestion: Skin: Eyes: Inhalation: Ingestion:	nue rinsing. f eye irritation persists: Protect from sunlight. De e of contents/container COMPOSITION EINECS No. 200-866-1 203-448-7 200-578-6 COMPOSITION A. FIRST If ingested, do not indu IMMEDIATELY. If the p unconscious person. C estimate of the time at swallowed. If irritation occurs & pr washing of the affected thoroughly before ruse If product get in the ey and lower eyelid(s) wh medical attention. Remove victim to fresh If product is swallowed depression. May be irritating to ski	Get medical advisor on expose to ter to licensed and p I & INGRED % 30–50 5 - 15 20 - 40 AID MEASI ce vomiting! If p patient is vomiting contact the neares t which the mater roduct is on the sk d area with plenty e. If irritation, rec res, flush with cop ile flushing to ensu- n air and keep cor d, may cause naus	ice/attention. emperature exceeding 48°C permitted disposal or recyclo IENT INFORMAT Other Flam. Gas 1; H220 Flam. Gas 1; H220 Flam. Liq. 2; H225 URES roduct has been swallower g, continue to offer water of the poison Control Center or ial was ingested and the and kin, rinse thoroughly with he y of soap and water. Remo liness or swelling persists, co ious amounts of lukewarm sure thorough irrigation. If infortable for breathing.	C (120 °F). ling facility. ION d, drink plenty of water o or milk. Never give water local emergency numbe mount of the substance the ukewarm water, followed we contaminated clothing onsult a physician immed on water for at least 15 min problems persist seek im ea and central nervous sy	or milk to ar r. Provide ar hat was I by a thorou g and wash diately. nutes. Raise mediate		

Page **2** of **7**

SAFETY DATA SHEET

KIK CUSTOM PRODUCTS

KIK – B-9814

F	Prepared to OSHA, ACC, ANS	SI, NOHSC, WHI	MIS, 2001/58 & 1272/2008/EC Standards SDS R	evision: 1.0	SDS Revision Date:	9-1-2016
		Inhalation:	Vapors of this product may be moderately irritating to respiratory system. Symptoms of overexposure can in difficulty breathing. Inhalation of concentrated vapor drowsiness, dizziness, headaches, nausea).	clude coughing	g, wheezing, nasal	congestion, and
.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and cent	ral nervous sys	tem depression.	
		<u>Skin:</u>	Prolonged contact with skin may result in bleaching ar skin reactions (e.g., rashes, welts, dermatitis) in some overexposure may include redness, itching, and irritat	nd irritation of s sensitive indivi ion of affected	skin. The product duals. Symptoms areas.	of skin
		Eyes:	Overexposure in eyes, may cause redness, itching and may cause mild eye irritation including stinging, water	ing and rednes	is.	
		Inhalation:	Symptoms of overexposure can include coughing, whe			
.4	Acute Health Effects:	drowsiness, o	itation to eyes and skin near affected areas. Additionall lizziness, headaches and nausea.		-	
.5	Chronic Health Effects:	irritating to s	r chronic health effects are expected to occur from a sir kin and mucous membrane of the eye and respiratory s some sensitive individuals. May also induce skin sensiti atitis.	ystem. Overex	posure may trigge	r asthma-like
.6	Target Organs:	Eyes, skin, re	spiratory system.			
l.7	Medical Conditions	Acute health	hazards may be delayed. Most common symptoms	HEALTH		1
	Aggravated by Exposure		ting properties to eyes, respiratory system and skin.	FLAMMABILI	ТҮ	3
		-	natological conditions (such as eczema) and respiratory	PHYSICAL HA	ZARDS	0
		conditions (se	uch as bronchial asthma and/or bronchitis) may be	PROTECTIVE	EQUIPMENT	В
		exacerbated.	rbated.		SK IN	
.1	Fire and Explosion Hazards:	 Level 1 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120° F (48°C). Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture 				
		and release f	lammable liquids and/or exposed gases if exposed to th bol by spraying them with water until the fire has been e	e heat of fire. I		
.2	Extinguishing Methods:		pam, CO_2 , Dry Chemical	0		
5.3	Firefighting Procedures:	demand_ and water spray t runoff from f natural water pressure self	, wear MSHA/NIOSH approved self-contained breathing d full protective gear. Keep containers cool until well af to cool fire-exposed surfaces and to protect personnel. ire control or dilution from entering sewers, drains, drin rway. Firefighters must use full bunker gear including N -contained breathing apparatus to protect against poter ition products and oxygen deficiencies.	ter the fire is ou Fight fire upwir king water sup IOSH-approved	ut. Use nd. Prevent pply, or any d positive	
			6. ACCIDENTIAL RELEASE MEASUR	ES		
5.1	Spills:	Equipment (F Small spills W combustible not use wate (e.g., plastic f Large spills: K release. Isola	ng any spill or leak, individuals involved in spill cleanup	must wear app ng gloves and p luct and place i . Sweep up ma ainer or plastic way from spill. onnel out of are	protective eyewear into a container fo aterial using non-sp liner within anoth Stay upwind and ea. Stop spill or re	. Use a non- r later disposal. oarking materials er container. away from spill c lease if it can be
		7.	HANDLING AND STORAGE INFORM	ATION		
7.1	Work & Hygiene Practices	container(s).	rink, or smoke while handling this product. Contents ur When used as intended, no additional protective equip ssible. Wash unintentional residues with soap and warr	ment is necess		

KIK CUSTOM PRODUCTS

SAFETY DATA SHEET

Page **3** of **7**

KIK – B-9814

	Prepared to OSHA, ACC, ANS	I, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 9-1-2016	
7.2	Storage and Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F (48°C). Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 1.	
7.3	7.3 Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.		
1			

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits:		AC	GIH		NOHSC			OSHA		OTHER
	Ppm (mg/m ³)	Chemical Name(s)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		Ethanol (SD Alcohol 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
		DIFLUOROETHANE (R-152a)	1000	NA	1000	NA	NA	NE	NA	NA	
		Butane	1000	NA	1000	NF	NA	800	NA	NA	
8.2	Ventilation & Engineering	General mechanical (e.g., fans)	or natur	al ventila	ntion is suf	ficient whe	n this prod	uct is in ı	use. Use	local or	general
	Controls	exhaust ventilation to effective	ly remov	e and pr	event buil	dup of vapo	ors or mist (generate	d from tl	he handl	ing of this
		product.									
8.3	Respiratory Protection:	No special respiratory protection	on is requ	uired und	ler typical	circumstan	ces of use of	or			
		handling. In instances where d		•	0		•				
		protection is needed, use only							5.		
		State regulations, or the Canad	ian CAS S	Standard	Z94.4-93	and applica	ble standar	ds of			
		Canadian Provinces, EC membe									
8.4	Eye Protection:	None required under normal co	onditions	of use.	Avoid eye	contact. Sa	afety glasse	es should			
		be used when handling or using	g large qu	uantities	of this pro	duct (e.g.,	<u>></u> 1 gallon (3.8 L)).		Ĕ	
8.5	Hand Protection:	None required under normal co	onditions	of use.	However,	may cause	skin irritati	on is son	ne		
		sensitive individuals. When handling large quantities (e.g., \geq 1 gallon (3.8 L)), wear rubber,						er,			
		nitrile or impervious plastic gloves.								y	
8.6	Body Protection:	No apron required when handl	ing small	quantiti	es. When	handling la	rge quantit	ies (e.g.,	<u>></u>		
		5 lbs.), eye wash station and de	luge sho	wers sho	ould be ava	ailable. Up	on complet	ion of			
		work activities involving large c	luantities	s of this p	product, w	ash any exp	bosed areas	5			
		thoroughly with soap and wate	r.								

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol, misty spray
9.2	Odor:	Fresh Sweet odor
9.3	Odor Threshold	NA
9.4	pH:	NA
9.5	Melting/Freezing Point	NA
9.6	Initial Boiling Point/ Boiling	NA
	Range:	
9.7	Flashpoint:	-30 °F (-34 °C) TCC for propellant only; 35.6 °F (2 °C) EPA method 1010 Concentrate only
9.8	Upper/Lower Flammability	NA
	limits	
9.9	Vapor Pressure:	@ 20 °C (68° F) – Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar
9.10	Vapor Density	>1
9.11	Relative Density:	0.84 – 0.94
9.12	Solubility:	Soluble
9.13	Partition Coefficient	NA
	(log Pow):	
9.14	Autoignition Temperature:	NA
9.15	Decomposition	NA
	Temperature.	
9.16	Viscosity:	Aerosol at ambient temperature
9.17	Other Information:	Evaporation Rate >1: Percent Volatile 55%
1		



Page **4** of **7**

KIK – B-9814

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

		10. STABILITY & REACTIVITY				
10.1	Stability:	ity: Stable at normal temperatures.				
10.2	Hazardous Decomposition	Dxides of carbon (CO, CO ₂) and sulfur (SO ₂)				
	Products:					
10.3	Hazardous Polymerization:	Will not occur.				
10.4		Excessive heat, direct sunlight, flames, heat sources and incompatible substances.				
10.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.				
	1	11. TOXICOLOGICAL INFORMATION				
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES				
11.2	Toxicity Data:	his product was not tested on animals.				
11.3	Acute Toxicity:	See Section 4.4				
11.4	Chronic Toxicity:	See Section 4.5				
11.5	- T	NA				
11.6	/	This product is not reported to cause reproductive toxicity in humans.				
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.				
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.				
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.				
44 7	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.				
11.7	Irritancy of Product:	See Section 4.3				
11.8	Biological Exposure	NA				
11.0	Indices:					
11.9	Physician Recommendations:	Treat symptomatically.				
	Recommendations.					
		12. ECOLOGICAL INFORMATION				
12.1	Environmental Stability:	There is no specific data available for this product.				
12.2	Effects on Plants & Animals					
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.				
		13. DISPOSAL CONSIDERATIONS				
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and				
		appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with				
		local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed fac or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.				
13.2	Special Considerations:	local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed fac				
13.2	Special Considerations:	local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed fac or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.				
13.2	Special Considerations:	local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed fac or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.				
	Special Considerations: 49 CFR (GND):	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or				
14.1	49 CFR (GND):	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020				
14.1		Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or				
14.1	49 CFR (GND): IATA (AIR)	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 I=L)				
14.1 14.2 14.3	49 CFR (GND): IATA (AIR) IMDG (OCN):	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 I=L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)				
14.1 14.2 14.3	49 CFR (GND): IATA (AIR) IMDG (OCN):	local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed fac or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 I=L)UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)				
14.1 14.2 14.3 14.4	49 CFR (GND): IATA (AIR) IMDG (OCN): TDGR (Canadian GND):	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 I=L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"				
14.1 14.2 14.3 14.4 14.5	49 CFR (GND): IATA (AIR) IMDG (OCN): TDGR (Canadian GND): ADR/RID (EU):	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE" UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)				
14.1 14.2 14.3 14.4 14.5 14.6	49 CFR (GND): IATA (AIR) IMDG (OCN): TDGR (Canadian GND):	Iocal, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed factor waste hauler must provide treatment, transport, storage and disposal of hazardous waste. U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001) 14. TRANSPORTATION INFORMATION UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 I=L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"				



Page **5** of **7**

KIK – B-9814

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

		15. REGULATORY INFOR	MATION	
	SARA Reporting Requirements:	This product does not contain any substance subject to S	ATA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the	he components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Ir	iventory.	
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2270 kg; 5000 lbs		
15.5	Other Federal Requirements:	This product complies with the appropriate sections of th (Cosmetics)	ne Food and Drug Administration's 21 CFR Subchapter G.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard information required by the CPR. The components of the the components of this product are listed on the Prioritie Aerosol)	e product are listed on the DSL/NDSL. None of	
15.7	State Regulatory Information:	<u>hanol:</u> is found on the following state criteria lists FL, MA, MN, NJ, PA, and WA <u>ttane</u> can be found on the following state criteria lists: MA, MN, NJ, PA, and WA. Ifluoroethane can be found on the following state criteria lists: MA and NJ o other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the following ate criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances st (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous ubstances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right- b-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).		
15.8	Other Requirements:	The primary components of this product are listed in Anr <u>Butane:</u> Flammable (F+). <u>Risk Phrases</u> (R): 12 – Extreme Keep out of reach of children. Keep in cool storage area ventilated place. Keep away from sources of ignition – N instructions before use. In case of accident, or if you feel <u>Ethanol</u> : Flammable (F). Risk Phrases (R): 11 – Flammabl children. Keep container tightly closed. Keep away from s	ely Flammable. <u>Safety Phrases</u> (S): 2-9-16-53-45 – below 120°F (48°C). Keep container in a well- lo smoking. Avoid exposure – obtain special ill, unwell, seek medical advice immediately. e. Safety Phrase (S): 2-7-16 – Keep out of reach of	
		16. OTHER INFORMA	TION	
16.1	Other Information:	AND VAPORS. CAUSES EYE IRRITATION. Keep away from sources. No Smoking. Do not spray on an open flame or Avoid breathing vapor/spray. Wash thoroughly with soa Wear eye protection. Protect from sunlight. Do not exp Remove person to fresh air and keep comfortable for brea	TAINER: MAY BURST IF HEATED, HIGHLY FLAMMABLE LIQUID m heat, hot surfaces, sparks open flames and other ignition o ther ignition source. Do not pierce or burn, even after use. p and water after handling. Use only in a well ventilated area. ose to temperature exceeding 48°C (120°F). IF INHALED: eathing. IF IN EYES: Rinse cautiously with water for several lo. Continue rinsing. If eye irritation persists: Get medical OF REACH OF CHILDREN.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.		
16.3	Disclaimer:	See last page of this Safety Data Sheet. This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete=ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.		
16.4	Prepared By:	KIK Custom Products 2730 Middlebury Street Elkhart, Indiana USA http://www.kikcorp.com	KIK CUSTOM PRODUCTS	



Page **6** of **7**

KIK – B-9814

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

Flammable	Explosive	Oxidizer
Pressurized	Corrosive	Toxic
Harmful/Irritating	Health Hazard	Environment
Face Shield and Protective	Apron	Dust Mask
Eyewear Control of the second	Protective Clothing	Full Suit
Boots	Safety Glasses	Gloves



Page **7** of **7**

KIK – B-9814

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

Full Face Respirator	Reactive	Irritant / Harmful
Biohazard	Oxidizing	Flammable
Infectious	Corrosive	Compressed
Toxic	Irritation	