

B-9820

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1. SDS Revision Date: 09/01/2016

	1. PRODUCT & COMPANY IDENTIFICATION					
1.1	Product Name:	Kenra Whip Grip Mousse 9				
1.2	Chemical Name:	Aerosol Foam				
1.3	Synonyms:	Whip Grip Mousse B-9820				
1.4	Trade Names:	Kenra Whip Grip Mousse 9				
1.5	Product Uses & Restrictions	Professional and Cosmetic Use				
1.6	Distributor's Name:	KIK Custom Products				
1.7	Distributor's Address:	2740 Middlebury Street, Elkhart, Indiana 46515				
1.8	Emergency Phone:	Poison Control Center (Medical): (866) 366-5048; CHEMTREC: +1 (800) 424-9300 /+1 (703)527-3887				
1.9	Business Phone / Fax:	+1 (574) 295-0000 / +1 (574) 295-1709				

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

<u>Classification:</u> Aerosol level 1; Category 2 Flammable aerosol; Eye Irrit. 2

<u>Hazard Statements</u> (H): H-223 – Flammable Aerosol. H229 – Pressurized container: may burst if heated. H320 – Causes eye irritation.

<u>Precautionary Statement</u> (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P410+P412 – Protect from sunlight. Do not expose to temperature exceeding 50°C (122 °F). P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.



3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
ISOBUTANE	75-28-5	200-857-2	1 - 5	Flam. Gas 1; H220
PROPANE	74-98-6	200-827-9	1 - 5	Press. Gas 1; Flam. Gas 1; H220

4. FIRST AID MEASURES

			4. I INST AID WEASONES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
		Eyes:	Moderately irritating to the eyes.
		Inhalation:	Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion,



B-9820

		and difficulty breathing. Inhalation of concentrated vapors can cause nervous system depression							
			(e.g., drowsiness, dizziness, headaches, nausea).						
4.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and	central nervo	us system depre	ession.			
		Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause							
		Skin:	allergic skin reactions (e.g., rashes, welts, dermat			uals. Syn	nptoms of skir		
		overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes, may cause redness, itching and watering (risk of serious damage to eyes)							
		Eyes:	Contact may cause mild eye irritation including stinging, watering and redness.						
		Inhalation:	Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing.						
.4	Acute Health Effects:	drowsiness, dizz	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.						
			hronic health effects are expected to occur from a						
1.5	Chronic Health Effects:	_	kin and mucous membrane of the eye and respirat						
			me sensitive individuals. May also induce skin sens	sitization and	respiratory hype	ersensiti	vity. Possible		
.6	Target Organs:	allergic dermati Eyes, skin, respi							
i.7	Medical Conditions		zards may be delayed. Most common symptoms	HEALTH			1		
.,	Aggravated by Exposure		g properties to eyes, respiratory system and skin.	FLAMMABIL	ITY		3		
	7 1		ological conditions (such as eczema) and	PHYSICAL HA			0		
		respiratory con	ditions (such as bronchial asthma and/or	PROTECTIVE	EQUIPMENT		В		
		bronchitis) may	be exacerbated.	EYES	SKIN				
.1	Fire and Explosion Hazards:	containers to pr	(NFPA 30B). Aerosols may burst at temperatures a event possible bursting. Aerosols may be projectil	e hazards whe	en bursting. If				
5.2	Extinguishing Methods: Firefighting Procedures:	containers to pr aerosols are but flammable liqui spraying them w Water Fog, Foat As in any fire, w demand_ and fu spray to cool fir from fire contro waterway. Fire contained breat		e hazards wheners may ruptifire. Keep coning apparatus (after the fire it fire upwind. water supply, approved pos	en bursting. If ure and release stainers cool by (pressureis out. Use wate Prevent runoff, or any natural sitive pressure so	er	1 0		
5.2	Extinguishing Methods: Firefighting Procedures:	containers to pr aerosols are but flammable liqui spraying them v Water Fog, Foal As in any fire, w demand_ and fo spray to cool fir from fire control waterway. Fire contained breat decomposition	event possible bursting. Aerosols may be projectil rsting, stay clear until bursting is complete. Contain ds and/or exposed gases if exposed to the heat of fivith water until the fire has been extinguished. m, CO ₂ , Dry Chemical ear MSHA/NIOSH approved self-contained breathin all protective gear. Keep containers cool until well e-exposed surfaces and to protect personnel. Fighal or dilution from entering sewers, drains, drinking fighters must use full bunker gear including NIOSH-hing apparatus to protect against potential hazard products and oxygen deficiencies. 5. ACCIDENTIAL RELEASE MEASU	e hazards wheners may ruptifire. Keep congapparatus (after the fire it fire upwind. water supply, approved posous combustic	en bursting. If ure and release stainers cool by (pressure-is out. Use water Prevent runoff, or any natural sitive pressure soon or	er elf-	1 0		
5.2 5.3 6.1	Extinguishing Methods:	containers to praerosols are but flammable liqui spraying them we water Fog, Foal As in any fire, we demand_ and fit spray to cool fir from fire control waterway. Fire contained breat decomposition Before cleaning Equipment (PPE Small spills West combustible made Do not use water materials (e.g., container. Large spills: Kee release. Isolate	event possible bursting. Aerosols may be projectil rsting, stay clear until bursting is complete. Contain ds and/or exposed gases if exposed to the heat of fivith water until the fire has been extinguished. m, CO ₂ , Dry Chemical ear MSHA/NIOSH approved self-contained breathin all protective gear. Keep containers cool until well e-exposed surfaces and to protect personnel. Fighter or dilution from entering sewers, drains, drinking fighters must use full bunker gear including NIOSH-hing apparatus to protect against potential hazard products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASU any spill or leak, individuals involved in spill cleanured.	e hazards wheners may ruptifire. Keep congress may ruptifire. May ruptifire. Suppose a ruptifire. Suppose may from s	en bursting. If ure and release stainers cool by (pressuresis out. Use water Prevent runoff, or any natural sitive pressure soon or appropriate Person of protective ey use into a contain oup material usiner or plastic limpill. Stay upwing farea. Stop spil	er elf- ewear. ner for laing non-ser withind and aw I or relea	Use a non- ater disposal. sparking n another way from spill o ase if it can be		
5.2	Extinguishing Methods: Firefighting Procedures:	containers to praerosols are but flammable liqui spraying them we water Fog, Foal As in any fire, we demand_ and fuspray to cool fir from fire control waterway. Fire contained breat decomposition Before cleaning Equipment (PPE Small spills Weat combustible made Do not use water materials (e.g., container. Large spills: Keet release. Isolated done with mining warrant.	event possible bursting. Aerosols may be projectilesting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of fivith water until the fire has been extinguished. In, CO2, Dry Chemical ear MSHA/NIOSH approved self-contained breathing protective gear. Keep containers cool until well e-exposed surfaces and to protect personnel. Fighal or dilution from entering sewers, drains, drinking fighters must use full bunker gear including NIOSH-hing apparatus to protect against potential hazard products and oxygen deficiencies. S. ACCIDENTIAL RELEASE MEASU any spill or leak, individuals involved in spill cleanumble. In appropriate personal protective equipment inclusterial such as vermiculite or sand to soak up the proper or a material such as "speedy dry" to soak up materials by the properties of the properties	e hazards wheners may ruptifire. Keep congression of the fire in the fire upwind. Water supply, approved posous combustion. JRES In must wear and ding gloves are oduct and planterial. Sweep plastic contain plastic contain of the fire including respince in the	en bursting. If ure and release stainers cool by (pressuresis out. Use water Prevent runoff, or any natural sitive pressure soon or appropriate Person of protective ey use into a contain oup material usiner or plastic limpill. Stay upwing farea. Stop spil	er elf- ewear. ner for laing non-ser withind and aw I or relea	Use a non- ater disposal. sparking n another vay from spill o sse if it can be		
5.2	Extinguishing Methods: Firefighting Procedures:	containers to praerosols are but flammable liqui spraying them we water Fog, Foat As in any fire, we demand_ and fit spray to cool fir from fire control waterway. Fire contained breat decomposition Before cleaning Equipment (PPE Small spills West combustible made Do not use water materials (e.g., container. Large spills: Keerelease. Isolated done with mining warrant.	event possible bursting. Aerosols may be projectil rsting, stay clear until bursting is complete. Contain ds and/or exposed gases if exposed to the heat of fivith water until the fire has been extinguished. m, CO ₂ , Dry Chemical ear MSHA/NIOSH approved self-contained breathing and protective gear. Keep containers cool until well e-exposed surfaces and to protect personnel. Fightill or dilution from entering sewers, drains, drinking fighters must use full bunker gear including NIOSH-hing apparatus to protect against potential hazard products and oxygen deficiencies. 5. ACCIDENTIAL RELEASE MEASU any spill or leak, individuals involved in spill cleanurally. The appropriate personal protective equipment inclusterial such as vermiculite or sand to soak up the protect or a material such as "speedy dry" to soak up material such as "speedy dry" to soak up material such as "speedy dry" to soak up material such as and least or and place into a princompatible materials (e.g., organics such as oil immediate hazard area and keep unauthorized penal risk. Wear appropriate protective equipment in the protective equip	e hazards wheners may ruptifire. Keep confirmed apparatus (after the fire into the fire upwind), water supply, approved posous combustion. JRES Ip must wear adding gloves arroduct and platerial. Sweep plastic containts away from spreamed out of including respination.	en bursting. If ure and release stainers cool by (pressure-is out. Use water Prevent runoff, or any natural sitive pressure so on or appropriate Period protective eyuce into a contain or up material usiner or plastic limited in the pill. Stay upwing farea. Stop spill tratory protection	er elf- ewear. ner for laing non-sner withind d and aw l or releason as cor	Use a non- ater disposal. sparking n another vay from spill o ase if it can be nditions		



B-9820

7.2	Storage and Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 2.									
.3	Special Precautions:	ions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.									
		8. EXPOSU	DE CON	TDOLCO	DEDCO	NIAL D	DOTECT	TION			
1	Francisco Lineites	8. EXPUSU			PERSO		KUIEC		NCI I A	OTUED	
3.1	Exposure Limits: Ppm (mg/m³)		AC	GIH		NOHSC		C	SHA	OTHER	
	i piii (iiig/iii)	Chemical Name(s)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ISOBUTANE	600	750	NF	NF	NA	NA	NA	NA	
		PROPANE	1000	NA	1000	NF	NF	1000	NA	2100	
3.2	Ventilation & Engineering Controls	General mechanical exhaust ventilation to product.									
.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
3.4	Eye Protection:	None required under normal conditions of use. Avoid eye contact. Safety glasses should be used when handling or using large quantities of this product (e.g., ≥ 1 gallon (3.8 L)).									
3.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., \geq 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.									
3.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs.), eye wash station and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									
		9. P	ΗΥSICΔΙ	. & CHEN	ΛΙζΔΙ Ρ	ROPFI	RTIFS				
0.1	Appearance:	Aerosol, white foam		<u>. </u>	/II C/ (L I	L.	*****				
.2	Odor:	Fresh Floral	'								
.3	Odor Threshold	NA									
.4	pH:	5.0 – 7.0									
.5	Melting/Freezing Point	NA									
.6	Initial Boiling Point/ Boiling Range:	NA									
.7	Flashpoint:	-30 °F (-34 °C) TCC fo	or propellant	only.							
.8	Upper/Lower	NA									
.9	Flammability limits Vapor Pressure:	@ 20 °C (68° F) – Ca	n nreccure n	nt to evened	190 ncia @	55 °C /121	°E\ 12 // ha	or.			
	Vapor Pressure:	@ 20 C (68 F) = Ca	ii pressure n	or to exceed	TOO hale @	22 C (131	. r) 12.4 Da	71			
	Relative Density:	095 – 1.005									
	Solubility:	Soluble									
	Partition Coefficient (log Pow):	NA									
.14	Autoignition Temperature:	NA									
.15	Decomposition Temperature.	NA									
.16	Viscosity:	Aerosol at ambient t	temperature								
17	Other Information:	Evaporation Rate >1	: Percent Vo	latile 6%							



B-9820

	10. STABILITY & REACTIVITY				
Stability:	Stable at normal temperatures.				
Hazardous					
Decomposition	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)				
Products:					
Hazardous	Will not occur.				
	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.				
	11. TOXICOLOGICAL INFORMATION				
Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES YES				
Toxicity Data:	This product was not tested on animals. Toxicology data, found in scientific literature, is available and not presented in this document.				
Acute Toxicity:	See Section 4.4				
Chronic Toxicity:	See Section 4.5				
Suspected Carcinogen:	No.				
	This product is not reported to cause reproductive toxicity in humans.				
	This product is not reported to produce mutagenic effects in humans.				
	This product is not reported to produce embryotoxic effects in humans.				
	This product is not report to cause teratogenic effects in humans.				
	This product is not report to cause reproductive effects in humans.				
	See Section 4.3				
Indices:	NA				
Physician Recommendations:	Treat symptomatically.				
	12. ECOLOGICAL INFORMATION				
Environmental Stability:	There is no specific data available for this product.				
Effects on Plants & Animals	There is no specific data available for this product.				
Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.				
T	13. DISPOSAL CONSIDERATIONS				
Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and				
	appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with				
	local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.				
Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)				
Special considerations.	O.S. El A Hazardous Waste Characteristic Ignitable (D001)				
	14. TRANSPORTATION INFORMATION				
49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL \leq 1.0 L) – until 12/31/2020				
2 IATA (AIR) UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or					
I IATA (AIK)					
I IATA (AIK)	ID8000, CONSUMER COMMODITY, ORM-D (IP VOL \leq 0.5 I=L)				
IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L)				
	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L); or				
IMDG (OCN): TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)				
IMDG (OCN): TDGR (Canadian GND): ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L); or				
IMDG (OCN): TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"				
	Hazardous Decomposition Products: Hazardous Polymerization: Conditions to Avoid Incompatible Substances Routes of Entry: Toxicity Data: Acute Toxicity: Chronic Toxicity: Suspected Carcinogen: Reproductive Toxicity: Mutagenicity: Embryotoxicity: Teratogenicity: Reproductive Toxicity: Irritancy of Product: Biological Exposure Indices: Physician Recommendations: Environmental Stability: Effects on Plants & Animals Effects on Aquatic Life: Waste Disposal: Special Considerations:				





B-9820

15.1	SARA Reporting Requirements:	Linis product does not contain any substance subject to SALA little III. section 313 reporting requirements.					
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.					
15.3		The components of this product are listed on the TSCA Inventory.					
	·	NA					
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics)					
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)					
15.7	State Regulatory Information:	Isobutane is found on the following state criteria lists: Massachusetts Hazardous Substances List (MA), Pennsylvar Right-to-Know list (PA), New Jersey Right-to-Know List (NJ). Propane can be found on the following state criteria lists: MA, MN, PA, WA and NJ.					
	No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).						
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Isobutane:</u> Flammable (F). <u>Risk Phrases</u> (R) 12 – Highly Flammable. <u>Safety Phrases</u> (S): 2-9-16 – Keep out of reach of children. Keep container in a well-ventilated area. Keep away from sources of ignition – No smoking. <u>Propane</u> : : Flammable (F). Risk Phrases (R) 12 – Highly Flammable. Safety Phrases (S): 2-9-16 – Keep out of reach of children. Keep container in a well-ventilated area. Keep away from sources of ignition – No smoking.					
		16. OTHER INFORMATI	ION				
16.1	Other Information:		INER: MAY BURST IF HEATED, HIGHLY FLAMMABLE LIQUID eat, hot surfaces, sparks open flames and other ignition her ignition source. Do not pierce or burn, even after use, and water after handling. Use only in a well ventilated area. It to temperature exceeding 50 °C (122 °F). IF INHALED: hing. IF IN EYES: Rinse cautiously with water for several				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3		This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete=ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.					
16.4	Prepared By:	KIK Custom Products 2730 Middlebury Street Elkhart, Indiana USA http://www.kikcorp.com					




B-9820

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.

SDS Revision Date: 09/01/2016





B-9820

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.

SDS Revision Date: 09/01/2016

Full Face Respirator	Reactive	Irritant / Harmful
Biohazard	Oxidizing	Flammable
Infectious	Corrosive	Compressed
Toxic	Irritation	