

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/15/2015 Revision date: 08/23/2016 Supersedes: 12/03/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture

Trade name : LIVING PROOF CONTROL HAIRSPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cosmetics

1.3. Details of the supplier of the safety data sheet

Living Proof, Inc.

301 Binney Street, 1st Floor Cambridge, MA 02142 T: 617-621-1800 F: 617-621-1880 QA@livingproof.com livingproof.com

1.4. Emergency telephone number

Emergency number : Chemtrec - +1-800-424-9300 or +1 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1 H222 - Extremely flammable aerosol

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol

H229 – Pressurised container. May burst if heated.

Precautionary statements (GHS-US) : P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source P251 - Pressurized container: Do not pierce or burn, even after use

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Ethyl alcohol	(CAS No) 64-17-5	<50	Flam. Liq. 2, H225 Carc. 1A, H350 (Alcoholic beverages only; not applicable to this product)

Full text of H-phrases: see section 16

INGREDIENTS: Alcohol Denat., Isobutane, Propane, Water/Eau/Aqua, Polyurethane-14, Octylacrylamide/Acrylates/Butylaminoethyl Methacrylate Copolymer, AMP-Acrylates Copolymer, PPG-5-Ceteth-20, Polyglyceryl-10 Pentaoleate, Fragrance/Parfum, Panthenol, Citral, Triethyl Citrate, Aminomethyl Propanol, Butylphenyl Methylpropional, Citronellol.

09/15/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person; If affected person feels unwell, seek

medical advice (show the label where possible).

First-aid measures after inhalation : If affected person is experiencing breathing difficulty, allow affected person to breathe fresh air.

Allow affected person to rest.

First-aid measures after skin contact : If adverse skin reaction occurs, remove affected clothing and wash all exposed skin area with

mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water; Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Not expected to be a primary route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/injuries after inhalation : None under normal use. May cause respiratory irritation.

Symptoms/injuries after skin contact : None under normal conditions.

Symptoms/injuries after eye contact : None under normal conditions. Mild eye irritation.

Symptoms/injuries after ingestion : None under normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Cool closed containers exposed to fire with water spray. In closed containers, pressure build

up could result in distortion, blowing and in extreme cases bursting of the container.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

Reactivity : Heating will cause rise in pressure with risk of bursting. Avoid ignition sources. Avoid

temperature above 50°C.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering

environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes. Do not breathe vapors. Hygiene measures : Do not eat, drink or smoke when using this product.

09/15/2015 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

Incompatible materials : Sources of ignition.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethyl alcohol (64-17-5)			
ACGIH	ACGIH STEL (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	

8.2. Exposure controls

Personal protective equipment : None needed.
Hand protection : None needed.
Eye protection : None necessary.
Skin and body protection : None needed.
Respiratory protection : None needed.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : clear.
Color : yellowish
Odor : characteristic
Odor threshold : No data available

pH : 8.7 - 9.2

Melting point No data available : No data available Freezing point Boiling point No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available : No data available Explosive properties Oxidizing properties : No data available Vapor pressure 40.88 mm Hg No data available Relative density

Relative vapor density at 20 °C : > 1

Specific gravity / density : 0.82 - 0.85 a/cm3 Solubility : Miscible with water. Log Pow No data available Auto-ignition temperature No data available : No data available Decomposition temperature Viscosity No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic

9.2. Other information

VOC content : 45 - 50 %
Gas group : Compressed gas

09/15/2015 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

Reactivity

Heating will cause rise in pressure with risk of bursting. Avoid ignition sources. Avoid temperature above 50°C.

Chemical stability 10.2.

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. **Conditions to avoid**

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

Information on toxicological effects 11.1.

Acute toxicity : Not classified

Ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg (historical information; not tested on animals for cosmetics)
LC50 inhalation rat (mg/l)	124.7 mg/l/4h (historical information; not tested on animals for cosmetics)
ATE US (oral)	7060.000 mg/kg body weight (historical information; not tested on animals for cosmetics)
ATE US (vapors)	124.700 mg/l/4h (historical information; not tested on animals for cosmetics)
ATE US (dust, mist)	124.700 mg/l/4h (historical information; not tested on animals for cosmetics)
Skin corrosion/irritation	: Not classified

pH: 8.7 - 9.2

Serious eye damage/irritation : Not classified pH: 8.7 - 9.2

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified.

Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans (Alcoholic beverages only; not applicable to this product)
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified : Not classified Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) : Not classified Aspiration hazard Not classified

Symptoms/injuries after inhalation : None under normal use. May cause respiratory irritation.

Symptoms/injuries after skin contact : None under normal conditions.

: None under normal conditions. Mild eye irritation. Symptoms/injuries after eye contact

Symptoms/injuries after ingestion : None under normal use.

SECTION 12: Ecological information

12.1. **Toxicity**

Ethyl alcohol (64-17-5) (historical information; not tested on animals for cosmetics)		
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	

Persistence and degradability

No additional information available

09/15/2015 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)	
Log Pow	-0.32

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : LTD QTY - Limited quantity



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Symbols : Limited quantities:

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

TDG

No additional information available

UN-No. (IMDG) : 1950

Proper Shipping Name (IMDG) : AEROSOLS, LTD QTY

Class (IMDG) : 2 - Gases


Air transport

Transport by sea

UN-No. (IATA) : ID 8000

Proper Shipping Name (IATA) : Consumer Commodity

Class (IATA) : 9



09/15/2015 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65: This product does not contain substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

Ethyl alcohol (64-17-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes (Alcoholic beverages only; Not applicable to this product	Yes	No	No	

Ethyl alcohol (64-17-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

tert-Butyl alcohol (75-65-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

LP-RM0094 Hydrofluorocarbon 152a (200-866-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 09/15/2015

Data sources

: DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H-phrases listed in Sections 2-15:

Carc. 1A	Carcinogenicity Category 1A	H222	Extremely flammable aerosol
Flam. Aerosol 1	Flammable aerosol Category 1	H225	Highly flammable liquid and vapor
Flam. Liq. 2	Flammable liquids Category 2	H350	May cause cancer
		H229	Pressurised container. May burst if heated

09/15/2015 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

: 3 - Liquids and solids that can be ignited under almost all NFPA fire hazard

ambient conditions.

: 1 - Normally stable, but can become unstable at elevated NFPA reactivity temperatures and pressures or may react with water with

some release of energy, but not violently.



HMIS III Rating

Physical

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature

conditions. Includes flammable liquids with flash points below 73 F and boiling points above

100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

09/15/2015 EN (English US) 7/7