# Material Safety Data Sheet

(Complies with ANSI Z400.1-1998)

Product Name: IN CONTROL Medium Hold Hair Spray, 55% VOC Product Code: 290-0435 MSDS # NEU001 SW-802A Issued: 01/06/12

| Section 1. Chemical Pro                            | oduct and  | d Company    | Identification |                 |  |
|--|------------|--------------|----------------|-----------------|--|
| Product Name: IN CONTROL Medium Hold Hair          | Spray, 55% | 6 VOC        |                |                 |  |
| Product Code: 290-0435                             |            |              |                |                 |  |
| Product Class: Aerosol Hair Spray                  |            |              |                |                 |  |
| For Further  | r Informat | ion Contact  | -              |                 |  |
| Neuma Research LLC                                 | Mon-Fri    | Telephone:   | 1 800 333 0707 | 8 am to 5 pm PT |  |
| 668 N. Coast Hwy.                                  |            | Fax:         | 1 310 669 9950 |                 |  |
| Laguna Beach, CA 92651                             |            | Web Site:    | www.N          | eumaBeauty.com  |  |
| For Che  | mical Eme  | ergencies:   |                |                 |  |
| Spill, Leak, Fire or Accident                      | Anytim     | e Telephone: | 1 800 333 0707 | North America   |  |
| Call: Eric Aquino M-F 8am-5pm                      |            |              | 1 800 333 0707 | outside U.S.    |  |
| Telephone: (310) 900-4112 or 1 800 900 4100, x-112 |            |              |                |                 |  |
|  |            |              |                |                 |  |

| Section 2. Composition and Information on Ingredients |         |                |        |           |      |          |      |              |
|---|---------|----------------|--------|-----------|------|----------|------|--------------|
| Hazardaya Componentar                                 | CAS #   | Vapor Pressure | Weight | ACGIH TLV |      | OSHA PEL |      | Unita        |
| Hazardous Components:                                 | CA3 #   |                | %      | TWA       | STEL | TWA      | STEL | <u>Units</u> |
| Specially Denatured Alcohol                           | 64-17-5 | 44 mmHg@ 68 °F | ≤55    | 1000      |      | 1000     |      | ppm          |
| Hydrofluorocarbon 152a                                | 75-37-6 | 64 psig@ 70 °F | ≤45    | 1000      |      | 1000     |      | ppm          |
|   |         |                |        |           |      |          |      |              |
|   |         |                |        |           |      |          |      |              |

NE = not established for this material.

\*\* = Components marked with double asterisk are present above De minimus cut off level and subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### Section 3. Hazard Identification

| Emergency Overview: | <i>Warning: Flammable. Contents under pressure. Container may burst if heated</i> . Do not place in hot water, or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperature over 120 °F. Do not use in presence of open flame or spark or other sources of ignition. KEEP OUT OF REACH OF CHILDREN. Avoid getting into eyes. Use only as directed. <i>Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.</i> |
|---------------------|--|
|                     | Potential Health Effects:  |
| Eye Contact:        | Contact may cause mild eye irritation including stinging, watering, and redness.   |
| Skin Contact:       | Practically non-irritating to skin. Prolonged or repeated contact may result in deffating and drying to the skin which may result in skin irritation and dermatitis.   |
| Inhalation:         | Contains asphyxiant gases. Intentional inhalation of gases may cause headache, fatigue, weakness, mental confusion, mood disturbances, and decreased coordination and judgment. Severe overexposure may produce more serious symptoms, including coma and death.   |
| Ingestion:          | No harmful or chronic effects are expected to occur from a single accidental ingestion. Intentional and continuous ingestion can cause serious effects on liver and kidney. Contains denatured alcohol.  |
| Chronic Effects:    | None when used as directed.  |

|            | Section 4. First Aid Measures   |  |  |  |  |
|------------|---|--|--|--|--|
|            | Flush or rinse eye with tempered water while holding eyelid open. Remove contact lenses, if worn. If irritation or redness persists seek medical attention. |  |  |  |  |
| Skin:      | Clean affected area(s) thoroughly by washing with mild soap and water, pat dry. If irritation or redness develops and persists, seek medical attention.     |  |  |  |  |
| Inhalation | If breathing difficulties develop, move victim away from source of exposure and into fresh air, give oxygen as necessary. Seek immediate medical attention. |  |  |  |  |
| Ingestion: | DO NOT induce vomiting. Have a conscious person drink two glasses of water. Seek medical attention.   |  |  |  |  |

|                      | Section 5. Fire Fighting Measures  |  |  |
|----------------------|--|--|--|
|                      |  |  |  |
| Aerosol Level        | <i>Level 2 Aerosol</i> (REF: to NFPA 30B, Section 1-7 of August 6, 1998). Code for the Manufacture and<br>Storage of Aerosol Products.   |  |  |
|                      | Aerosols may burst at temperatures above 120 °F. Contents under pressure. Cool uninvolved containers to<br>prevent possible bursting.  |  |  |
| Extinguishing Media: | Use extinguishing agent suitable for type of surrounding fire.   |  |  |
|                      | The use of self-contained breathing apparatus is recommended for fire fighters. <i>Fight fire upwind</i> . Containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure buildup which could result in container rupture. Keep containers cooled with water and remove them from danger if it can be done with minimal risk. Aerosols can be projectiles when bursting. If aerosols are bursting, stay clear until bursting is complete. |  |  |

#### Section 6. Accidental Release Measures

### Large Spills:

Keep sources of ignition and hot metal surfaces isolated from spill. Stay upwind and away form spill/release. Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Water may be useful in minimizing or dispersing vapors. Keep out of water supplies.

| Section 7. Handling and Storage. |  |  |
|----------------------------------|--|--|
| Handling:                        | Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if likelihood of eye contact. Wash unintentional residue with soap and water.  |  |
| Storage:                         | Store aerosol containers in cool, dry, well-ventilated areas away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from any incompatible material (see section 10). Protect container(s) against physical damage. To avoid unintentional spraying keep protective cap in place when not in use. |  |

|                       | Section 8. Exposure Controls / Personal Protection  |  |  |  |
|-----------------------|---|--|--|--|
| Engineering Controls: | A well ventilated room with adequate air circulation. Use local and general exhaust ventilation to effectively remove and prevent buildup of vapors/mist generated from the handling of this product. |  |  |  |
| Respiratory:          | If used with adequate ventilation, no protective equipment is necessary.  |  |  |  |
| Skin:                 | Not required based on the hazard of the material.   |  |  |  |
| Eye/Face:             | While contact with this material is not expected to cause appreciable irritation, the use of approved eye protection to safeguard against potential eye contact is considered good practice.          |  |  |  |
|                       | A source of clean water should be available in the work area for flushing eyes and skin. Impervious   |  |  |  |
| Equipment:            | clothing should be worn as needed.  |  |  |  |

| Section 9. Physical and Chemical Properties. |                                      |   |  |  |
|--|--------------------------------------|---|--|--|
| C  | oncentrate Only:                     | Finish Product:                             |  |  |
| Appearance:                                  | Light yellow or straw colored liquid | <i>Vapor Pressure:</i> 60 - 70 psig @ 70 °F |  |  |
| Boiling Range:                               | < 100 °F (38 °C)                     |   |  |  |
| Flash Point:                                 | 48 °F                                |   |  |  |
| Specific Gravity:                            | 0.814 (water=1)                      |   |  |  |
| pH:  | 9.45                                 |   |  |  |
| Weight per Gallon:                           | 6.79 #/gal                           |   |  |  |
| Solubility (water):                          | Soluble                              |   |  |  |

| Section 10. Stability and Reactivity |  |  |
|--------------------------------------|--|--|
| Chemical Stability:                  | Stable under normal conditions of storage and handling.  |  |
| Conditions to Avoid:                 | High temperatures, above 120 °F, open flames and sparks.   |  |
|                                      | Avoid contact with strong oxidizing and reducing agents. Strong acids and bases. (Household Ammonia, |  |
| Materials                            | Drain Openers etc.)  |  |
| Hazardous<br>Decomposition Products: | Combustion may produce carbon monoxide, carbon dioxide and other unidentified organic compounds.     |  |
| Hazardous<br>Polymerization:         | Will not occur.  |  |

#### Section 11. Toxicological Information

No definitive information found on carcinogenicity, mutagenicity, target organs or developmental toxicity.

Not found

## Section 12. Ecological Information

Section 13. Disposal Considerations

Along with properly characterizing all waste materials, consult state and local regulations regarding the proper disposal of this material.

|                     | Section 14. Transport Information            |  |  |
|---------------------|--|--|--|
| 1. DOT (Ground)     |  |  |  |
| Shipping Name:      | Consumer Commodity                           |  |  |
| Hazard Class:       | ORM-D  |  |  |
| 2. IMDG (Overseas)  |  |  |  |
| Shipping Name:      | Aerosols                                     |  |  |
| Class:              | 2.1  |  |  |
| UN No.:             | 1950   |  |  |
| 3. IATA (Air)       |  |  |  |
| Shipping Name:      | Consumer Commodity                           |  |  |
| Class:              | 9  |  |  |
| ID No.:             | ID8000                                       |  |  |
| Label:<br>rackaging | Miscellaneous Dangerous Goods Class 9<br>910 |  |  |

Section 15. Regulatory Information

Toxic Chemicals List under SARA Section 313 of the Title III and 40 CFR Part 372.

Chemicals under California Proposition 65

None

None

Flammability Classification 16 CFR, Ch II Subch. C, Part 1500.45

Flammable

Code of Manufacture and Storage of Aerosol Products NFPA 30B

Level 2 Aerosol

Section 16. Documentary Information

Issue Date: 01/06/12 Revised: NEW Product Code: 290-0435

Disclaimer of Expressed and Implied Warranties.

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.