

# PETER COPPOLA

## MATERIAL SAFETY DATA SHEET

PC LEGACY STEEL KERATIN CONCEPT HoId HS 55%

1 of 3

### Section I: General Information

Peter Coppola Beauty, LLC  
7000 W. Camino Real, Suite 200  
Boca Raton, FL 33433

Emergency Phone: CHEMTREC  
(800) 424-9300  
Information Phone: (815) 634-5100  
Date Prepared: 1/19/09  
File:

Product is predominantly an alcoholic solution of a hair fixative resin expelled by halogenated hydrocarbon propellants.

NMFC Classification: \*Toilet Preparations, N.O.I., In Boxes, NMFC Item 60000, RVNX, Class 70

NFPA Class II Aerosols

### Section II: Hazardous Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity/Common Name) | OSHA PEL | ACGIH TLV | %      |
|---|----------|-----------|--------|
| SD Alcohol (Comprised of)                                     |          |           | < 55.0 |
| (Ethyl Alcohol CAS# 64-17-5)                                  |          | 1000 ppm  | 99.7)  |
| (*T-butyl Alcohol CAS# 75-65-0)                               |          | 100 ppm   | 0.1)   |
| 2-Amino-2-Methyl-1-propanol CAS# 124-68-5                     |          | N/K       | < 1.0  |
| 2   |          |           |        |
| Ethane, 1,1-Difluoro CAS# 75-37-6                             |          | N/E       | < 45.0 |

\* These materials subject to requirements of Section 311, 312 and/or 313 of SARA TITLE III.

Hazard Ratings: Health - 1      Fire - 3      Reactivity - 0      Other - 0

(N/K = Not Known      N/E = Not Established      N/A = Not Applicable)

### Section III: Physical/Chemical Characteristics

Boiling Point (of conc.): 175F      Melting Point: N/A  
Specific Gravity (of conc.): 0.82  
Vapor Pressure of Container (psig @ 70F): 45-55  
(Internal pressure will increase with temperature.)  
Vapor Density (AIR=1): N/E      Evaporation Rate (H2O=1): > 1  
Solubility in Water: Complete  
Appearance and Odor: Concentrate (conc.) is clear to pale yellow non-viscous fragrancd liquid.

### Section IV: Fire and Explosion Hazard Data

Flash Point: 65F T.O.C. \*      Flammable Limits: LEL 3.3\* UEL 19\*  
Extinguishing Media: CO2 or dry chemical for small fires. Foam for large fires.  
Special Fire Fighting Procedures: Addition of water fog will aid in reducing burning rate. Use of NIOSH self-contained breathing apparatus in confined areas. Use water spray to cool fire-exposed containers.  
Unusual Fire and Explosion Hazards: Flammable vapors may travel along floor to be ignited by distant ignition sources. Containers exposed to fire may



Eye Protection: None necessary when product is used as directed. Always avoid contact with eyes.  
Work/Hygienic Practices: Normal safe working practices.

The information contained herein is based on the data available to us and is believed to be correct to the best of our ability. However, Chicago Aerosol, LLC makes no warranty, expressed or implied, regarding the accuracy of this data nor assumes any responsibility for injury from the intentional or non-intentional misuse of this product.