REDKEN

SAFETY DATA SHEET

1. Identification

Product identifier REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

Other means of identification

SDS number 00-12-0000618

Recommended use Personal care product used for cosmetic effect.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

US Address: L'Oreal USA Products, Inc

133 Terminal Avenue Clark. NJ 07066

USA

Canadian Address: L'Oreal Canada

4895 rue Hickmore

Ville St-Laurent, H4T 1K5

Canada

Emergency Phone #: 1-800-535-5053 (International: 352-323-3500)

In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further Information: 1-732-499-2741

Poison Control #: 412-390-3326

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER
1218122RK1 Version #: 01 Issue date: 09-12-2019

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ETHANOL		64-17-5	20
MYRISTYL ALCOHOL		112-72-1	2

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Not available.

Most important

symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Material name: REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA	Table Z-1 Limits for Air	r Contaminants	(29 CFR 1910.1000)	
_	· ·	_		

Components	Туре	Value	
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	
ETHANOL (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

1000 ppm

acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Applicable for industrial settings only. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing.

Respiratory protection Applicable for industrial settings only. If engineering controls do not maintain airborne

concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be

worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state
Color
Color
Colorless.

Odor
Characteristic.

Odor threshold
PH
Not available.

Melting point/freezing point
Not available.

SDS US

Initial boiling point and boiling > 95 °F (> 35 °C)

range

Flash point 93.2 °F (34.0 °C) Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

No adverse effects due to eye contact are expected.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

<u>Acute</u> Oral

ATEmix 540500 mg/kg

Components **Species Test Results**

ETHANOL (CAS 64-17-5)

Acute

Dermal

LD50 Rabbit > 20000 mg/kg

Inhalation

Vapor

LC50 Rat 124.7 mg/l, 4 h OECD 403

Oral

LD50 Rat 10470 mg/kg OECD 401

MYRISTYL ALCOHOL (CAS 112-72-1)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

Dust

LC50 Rat > 1.5 mg/l, 1 h

Oral

LD50 Rat > 2000 mg/kg OECD 401

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. No adverse effects due to

skin contact are expected.

Irritation Corrosion - Skin

MYRISTYL ALCOHOL **OECD 404**

> Result: Not Irritating Species: Human

FTHANOL **OECD 404**

Result: Not Irritating Species: Rabbit

Serious eye damage/eye

eye contact are expected.

irritation

Due to partial or complete lack of data the classification is not possible. No adverse effects due to

Irritation Corrosion - Eye

OECD 405 ETHANOL

Result: Irritating Species: Rabbit

MYRISTYL ALCOHOL **OECD 405**

> Result: Irritating Species: Rabbit

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible. Skin sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization

ETHANOL OECD 406

Result: Not Sensitizing Species: Guinea pig

MYRISTYL ALCOHOL **OECD 406**

> Result: Not Sensitizing Species: Guinea pig

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Mutagenicity

ETHANOL Result: In vitro and in vivo tests did not show mutagenic

effects.

MYRISTYL ALCOHOL Result: In vitro and in vivo tests did not show mutagenic

effects.

Carcinogenicity Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the

classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard.

Developmental effects

MYRISTYL ALCOHOL > 2000 mg/kg bw/d OECD 422

Result: NOAEL Species: Rat

ETHANOL > 20000 ppm OECD 414, No effects on development

Result: NOAEL Species: Rat

Reproductivity

MYRISTYL ALCOHOL > 2000 mg/kg bw/d OECD 422, Based on test data for

structurally similar materials.

Result: NOAEL Species: Rat

ETHANOL 20700 mg/kg bw/d OECD 416, No effects on fertility

Result: NOAEL Species: Rat

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

Due to partial or complete lack of data the classification is not possible.

repeated exposure

ETHANOL 1730 mg/kg bw/d OECD 408, Oral

Result: NOAEL Species: Rat

MYRISTYL ALCOHOL 3548 mg/kg bw/d OECD 408, Based on test data for structurally

similar materials. Result: NOAEL Species: Rat Test Duration: 90 d

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
ETHANOL (CAS 64-17	7-5)		
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h
Chronic			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212
MYRISTYL ALCOHOL	(CAS 112-72-1)		
Aquatic			
Acute			
Algae	EL50	Desmodesmus subspicatus	2.9 mg/l, 96 h OECD 201
Crustacea	EC50	Daphnia magna	3.2 mg/l, 96 h OECD 202
Fish	LC50	Oncorhynchus mykiss	> 1 mg/l, 96 h OECD 203
Chronic			
Crustacea	NOEC	Daphnia magna	0.0016 mg/l, 21 d OECD 211
sistence and degradal	bility		

Material name: REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

Biodegradability

Percent degradation (Aerobic biodegradation)

ETHANOL 84 %

Result: Readily Biodegradable

Test Duration: 20 d 92 % ISO 10708

Result: Readily Biodegradable

Test Duration: 28 d

Bioaccumulative potential

MYRISTYL ALCOHOL

Partition coefficient n-octanol / water (log Kow)

ETHANOL -0.31 MYRISTYL ALCOHOL 6.03

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code This product is ignitable (D001) RCRA hazardous wastes when intended for disposal.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Materials associated with this document meet the criteria for US Department of Transportation exemption found at 49 CFR 173.150(g).

Packages containing limited quantities of retail products in volumes in accordance with the tables listed below maybe offered under the conditions of the exemption.

US Domestic Transportation Per 49 CFR 173,150(g) exemptions:

	>70% Ethyl Alcohol (v/v) (w/w)			
	Inner Packaging	Net Contents	Gross Weight	Marking
Liquids	8 fl. oz.	192 fl. oz.	65 lbs.	None
	≤70% Ethyl Alcohol (v/v) (w/w)			
Liquids (glass)	8 fl. oz.	192 fl. oz.	65 lbs.	None
	16 fl. oz.	192 fl. oz.	65 lbs.	Contains Ethyl Alcohol
Liquids (non- glass)	16 fl. oz.	192 fl. oz.	65 lbs.	None
	1 gallon	192 fl. oz.	65 lbs.	Contains Ethyl Alcohol
	General Conditions			
	Inner packagings must be secured and cushioned within the			

DOT

FINISHED GOODS

UN number UN1266

UN proper shipping name PERFUMERY PRODUCTS, Limited Quantity

Class 3 Packing group III

Transport hazard class(es)

Label(s) Limited Quantity

Packaging exceptions 150 LTD QTY Net Inner Capacity 5.0 L

BULK

UN number UN1266

UN proper shipping name PERFUMERY PRODUCTS, MARINE POLLUTANT (MYRISTYL ALCOHOL)

Class 3 Packing group III

Environmental hazards

Marine pollutant Yes

1218122RK1 Version #: 01 Issue date: 09-12-2019

Material name: REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

Transport hazard class(es)

Label(s) 3

Special provisions B1, IB3, T2, TP1

Packaging non bulk 203

IATA

FINISHED GOODS

UN number ID8000

UN proper shipping name CONSUMER COMMODITY

Class

Packing group Not applicable.

ERG Number 9L

BULK

UN number UN1266

UN proper shipping name PERFUMERY PRODUCTS

Class 3
Packing group III

Environmental hazards

Marine pollutant Yes ERG Number 3L

IMDG

FINISHED GOODS

UN number UN1266

UN proper shipping name PERFUMERY PRODUCTS, Limited Quantity

Class 3 Packing group III

Environmental Hazards

Marine pollutant No.

Transport hazard class(es)

Label(s) Limited Quantity

EmS F-E, S-D LTD QTY Net Inner Capacity 5.0 L

BULK

UN number UN1266

UN proper shipping name PERFUMERY PRODUCTS, MARINE POLLUTANT (MYRISTYL ALCOHOL)

Class 3
Packing group III

Environmental hazards

Marine pollutant Yes EmS F-E, S-D

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHANOL (CAS 64-17-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHANOL (CAS 64-17-5) Low priority

16. Other information, including date of preparation or last revision

Issue date 09-12-2019

Version # 01

NFPA ratings Health: 0

Flammability: 3 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

1218122RK1 Version #: 01 Issue date: 09-12-2019 9 /