

Prepared to OSHA, ACC, ANSI, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 01/01/2006

1. PRODUCT IDENTIFICATION

1.1	Product Name: OSIS ELASTIC FLEXI HOLD HAIR SPRAY
1.2	Chemical Name: AEROSOL
1.3	Synonyms: NA
1.4	Trade Names: 16109, 16110
1.5	Product Use: PROFESSIONAL OR SUNDRY USE ONLY
1.6	Distributor's Name: SCHWARZKOPF, INC.
1.7	Distributor's Address: 6047 BRISTOL PARKWAY, SUITE 200, CULVER CITY, 90230 USA
1.8	Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-3887
1.9	Business Phone: +1 (310) 641-4600

2. HAZARD IDENTIFICATION

2.1	Hazard Identification: WARNING: Flammable. Contents under pressure. Container may burst if heated. Do not place on hot water, or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 120 °F. Do not use near open flame, sparks or other sources of ignition. KEEP OUT OF REACH OF CHILDREN. Avoid getting into the eyes. Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.						
2.2	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure: INGESTION: May cause a burning sensation of the mouth and throat, abdominal pain, gastrointestinal irritation, nausea, vomiting and diarrhea. May also cause kidney damage, cardiac arrhythmia and Central Nervous System effects (see inhalation). Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Can be fatal if inhaled or ingested. SKIN & EYES: May cause irritation, redness and tearing. Vapors may be irritating to the eyes. May cause irritation, defatting, drying and cracking of skin. Prolonged and repeated contact may lead to dermatitis. INHALATION: Vapors may be irritating to nose, throat and respiratory tract. Excessive inhalation of vapors may cause kidney damage, cardiac arrhythmia and Central Nervous System effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.						
2.4	Symptoms of Overexposure: Contact may cause mild eye irritation including stinging, watering and redness. Intentional inhalation of gases may cause headache, fatigue, weakness, mental confusion, mood disturbances and decreased coordination and judgment.						
2.5	Acute Health Effects: Intentional inhalation of gases may cause headache, fatigue, weakness, mental confusion, mood disturbances and decreased coordination and judgment.						
2.6	Chronic Health Effects: No harmful or chronic health effects are expected to occur from a single accidental ingestion. Intentional and continuous ingestion can cause serious effects on liver and kidneys. Contains denatured alcohol.						
2.7	Target Organs: Eyes & skin.						

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)					
					ACGIH - ppm		OSHA - ppm		OTHER	
					TLV	STEL	PEL	STEL		IDLH
DENATURED ALCOHOL	64-17-5	KQ6300000	200-578-6	≤ 55.0	1000	NA	1000	NA	NA	
1,1-DIFLUOROETHANE	75-37-6	KI1410000	200-866-1	≤ 45.0	NA	NA	NA	NA	NA	

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used
NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

Prepared to OSHA, ACC, ANSI, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 01/01/2006

4. FIRST AID MEASURES

4.1 First Aid:

INGESTION: If ingested, do not induce vomiting. Drink plenty of water or milk. If the patient is vomiting, continue to offer plenty of water or milk. Never give water or milk to an unconscious person. If large quantities are ingested, contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time and amount of the substance that was swallowed. Get medical attention immediately.

EYES: If product is in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. If problem persists, consult a physician.

SKIN: If redness, dryness or other signs of irritation to the skin develop, remove contaminated clothing and wash affected skin areas with plenty of warm water and soap. If irritation persists, consult a physician.

INHALATION: Remove victim to fresh air at once. Give oxygen as necessary.

4.2	Medical Conditions Aggravated by Exposure: None known.	HEALTH		2
		FLAMMABILITY		3
		REACTIVITY		0
		PROTECTIVE EQUIPMENT		B
		EYES	SKIN	

5. FIREFIGHTING MEASURES

5.1	Flashpoint & Method: NA
5.2	Autoignition Temperature: NA
5.3	Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA
5.4	Fire & Explosion Hazards: Level 2 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete.
5.5	Extinguishing Methods: Water Fog, Foam, Dry Chemical, CO₂
5.6	Firefighting Procedures: As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boilover. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.



6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:
Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

Large Spills: Keep sources of ignition and hot metal surfaces isolated from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Water may be useful in minimizing or dispersing vapors. Keep out of water supplies.

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.
7.2	Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use.
7.3	Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls: General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product.
8.2	Respiratory Protection: None required if used in a well-ventilated area. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrants a respirator's use.
8.3	Eye Protection: Avoid eye contact. Use approved safety glasses or goggles.
8.4	Hand Protection: Rubber or latex gloves.
8.5	Body Protection: Avoid contact with skin, eyes and clothing.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	0.815
9.2	Boiling Point:	≤ 100 °F (≤ 38 °C)
9.3	Melting Point:	NA
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure:	55-65 psig @ 70 °F
9.6	Molecular Weight:	NA
9.7	Appearance & Color:	Aerosol, alcoholic odor.
9.8	Odor Threshold:	ND
9.9	Solubility:	Soluble in water
9.10	pH	NA
9.11	Viscosity:	NA
9.12	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability: This product is stable.
10.2	Hazardous Decomposition Products: Oxides of carbon (CO, CO₂) and sulfur (SO₂)
10.3	Hazardous Polymerization: Will not occur.
10.4	Conditions to Avoid: Open flames, sparks, high heat and direct sunlight.
10.5	Incompatible Substances: None known.

Prepared to OSHA, ACC, ANSI, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 01/01/2006

11. TOXICOLOGICAL INFORMATION

11.1	Toxicity Data: The product has not been tested for specific toxicity data.
11.2	Acute Toxicity: See section 2.5
11.3	Chronic Toxicity: See section 2.6
11.4	Suspected Carcinogen: NO
11.5	Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity: This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity: This product is not reported to produce teratogenic effects in humans.
	Reproductive Toxicity: This product is not reported to produce reproductive effects in humans.
11.6	Irritancy of Product: See Section 2.3
11.7	Biological Exposure Indices: NE
11.8	Physician Recommendations: Treat symptomatically.

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability: There is no specific data available for this product.
12.2	Effects on Plants & Animals: There is no specific data available for this product.
12.3	Effects on Aquatic Life: There is no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal: Dispose of in accordance with federal, state and local regulations.
13.2	Special Considerations: U.S. EPA Characteristic Waste: D001 (characteristic - ignitable)

14. TRANSPORTATION INFORMATION

The basic description (proper shipping name, hazard class & division, ID Number, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D
14.2	IATA (AIR): ID8000, CONSUMER COMMODITY, 9
14.3	IMDG (OCN): UN1950, AEROSOLS, 2, LTD QTY
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE"
14.5	ADR/RID (EU): UN1950, AEROSOLS, 2, LTD QTY
14.6	SCT (MEXICO): UN1950, AEROSOLE, 2, CANTIDAD LIMITADA





Prepared to OSHA, ACC, ANSI, WHMIS & 2001/58 EC Standards



MSDS Revision: 1.0

MSDS Revision Date: 01/01/2006

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements: NA	
15.2	SARA Threshold Planning Quantity: NA	
15.3	TSCA Inventory Status: All chemical substances of this product are listed on the TSCA inventory or are otherwise exempted from inventory status.	
15.4	CERCLA Reportable Quantity (RQ): NA	
15.5	Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
15.6	Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.	
15.7	State Regulatory Information: Ethanol is covered under specific state criteria. No components of this product are listed on the California Proposition 65 lists.	
15.8	67/548/EEC (European Union) Requirements: The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: Ethanol: Flammable (F): R: 11-20/21/22-36/37/38 - Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes, respiratory system and skin. S: 7-16-24/25-36/37/39-45 - Keep container tightly closed. Keep away from sources of ignition -- No smoking. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately.	

16. OTHER INFORMATION

16.1	Other Information: For external use only. Use only as directed. Discontinue use immediately if irritation develops.	
16.2	Terms & Definitions: See page 6 of this MSDS.	
16.3	Disclaimer: This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Schwarzkopf's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for: Schwarzkopf, Inc. 6047 Bristol Parkway, Suite 200 Culver City, CA 90230 USA Tel: +1 (310) 641-4600 Fax: +1 (310) 641-4601 http://www.schwarzkopf.com	
16.5	Prepared by: ShipMate, Inc. 18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504 310-370-3600 phone 310-370-5700 fax http://www.shipmate.com	

Prepared to OSHA, ACC, ANSI, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 01/01/2006

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health


FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or S.O.P. for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Eye Protection	Gloves
Boots	Synthetic Apron	Full Suit	Dust Respirator
Vapor Respirator	Dust & Vapor Respirator	Full Face Respirator	Airline Hood/Mask or

Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

FLAMMABILITY LIMITS IN AIR:


Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₀₁ or TC, TC₀₁, LC₀₁, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
CPR	Canada's Controlled Product Regulations

EC INFORMATION:

C	E	F	N	O	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

WHMIS INFORMATION:

A	B	C	D1	D2	D3	E	F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive