



**Customer No.:** 222397  
**Shipping Address:**  
21551 Prairie Street  
Chatsworth, CA 91311  
(818) 435-0800

## WEATHER PROOF HAIRSPRAY

### Section I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**MSDS FIRST PREPARATION DATE:** January 18, 2012

**REVISION DATE:** N/A

**SUPERSEDES:** N/A

**FORMULA:** 175-74D

**PREPARED AND REVISED BY:** Alison Robinson

**GENERIC/CHEMICAL NAME:** Hair Spray

**PRODUCT TYPE/CHEMICAL FAMILY:** NA

**PRODUCT CODE:** 15AHS04;15AHS01

**SYNONYMS:** None

**CONTACT ADDRESS:** Sexy Hair Concepts, 21551 Prairie Street, Chatsworth, CA 91311

#### EMERGENCY PHONE NUMBERS:

**CHEMTREC:** Domestic North America 800-424-9300; International: 703-527-3887 (collect calls accepted)

### Section II - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Percent	Exposure Limits in Air	
			TLV ppm	PEL ppm
Butane	106-97-8	10 – 30%	800	1000
Isobutane	72-28-5	0.1 – 5%	800	800
Alcohol Denat.	64-17-5	30 -60%	1000	1000
Hydrofluorocarbon 152a	75-37-6	20 -60%	Not Established	

### Section III - HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS

**EYE CONTACT:** Liquid and vapor may cause mild to severe eye irritation.

**SKIN CONTACT:** Repeated contact may cause irritation and drying of the skin. Contact with propellant may cause freeze burns.

**INHALATION:** Vapor may cause irritation to the upper respiratory tract

**INGESTION:** If ingested, may cause gastrointestinal irritation. In aerosol form, ingestion is not likely.

### Section IV - FIRST AID

**EYE CONTACT:** Flush eyes with plenty of water to ensure complete flushing. If irritation persists, seek medical attention

**SKIN CONTACT:** Clean affected areas thoroughly with mild soap and water. If irritation persists, seek medical attention.

**INHALATION:** Remove victim to fresh air immediately. If breathing is difficult, seek medical attention.

**INGESTION:** Drink enough water to dilute. Consult a physician immediately.

## **Section V - FIRE FIGHTING MEASURES**

**FLASH POINT:** -30°F TCC (Propellant Only)

**AUTOIGNITION TEMPERATURE:** N/A

**FLAMMABILITY LIMITS IN AIR (% V):** LEFL = 1.8%; UEL= 9.5%

**EXTINGUISHING MEDIA:** Carbon Dioxide, Foam, Dry Chemical, Water

**SPECIAL FIRE FIGHTING PROCEDURES:** Fire should be fought from a safe distance. Firefighters should wear full face, self-containing breathing apparatus and full protective clothing.

**UNUSUAL FIRE & EXPLOSION HAZARDS:** Closed containers exposed to excessive heat may rupture. Do not crush or puncture containers.

## **Section VI - ACCIDENTAL RELEASE MEASURES**

**SPILL ON LAND (LARGE SPILL):** Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without risk. Minimize breathing of vapors. Minimize skin contact. Ventilate confined spaces. For small spills implement the following cleanup procedures: Prevent material from entering sewers, watercourses, or low areas. Contain spilled material with sand or earth. Do not use combustible materials such as sawdust. Observe precautions for volatile, combustible vapors from absorbed material. For large spills implement the preceding cleanup procedures and, if in public area, keep public away and advise authorities. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

**SPILL ON WATER (LARGE SPILL):** Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or scooping up floating material. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

## **Section VII - STORAGE AND HANDLING**

**STORAGE TEMPERATURE:** Ambient

**STORAGE/TRANSPORT PRESSURE:** 180 psig @131°F Max

**LOADING/UNLOADING TEMPERATURE:** Ambient

**STORAGE AND HANDLING:** Keep away from excessive heat, open flames, sparks, and other possible source of ignition. Do not store in damaged or unmarked containers or storage devices. For warehouse storage, pallets and cases should be placed to avoid damage or rupture from material handling equipment.

## **Section VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:** None Required.

**VENTILATION:** Use with adequate ventilation

**PROTECTIVE CLOTHING:** Not necessary except as a good industrial practice.

**EYE PROTECTION:** Not necessary except as a good industrial practice.

**OTHER PRECAUTIONS:** Avoid excessive inhalation. Read and follow all label directions and cautions. Use only as directed.

## **Section IX - PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Clear Liquid  
**STATE:** Aerosol  
**ODOR:** Standard  
**PERCENT VOLATILE:** 55%  
**SPECIFIC GRAVITY:** 0.80 – 0.82  
**VISCOSITY:** Aerosol @ambient  
**EVAPORATION RATE:** N/A  
**VAPOR PRESSURE mm Hg @ 20°C:** Can pressure not to exceed 180 psig @131° F  
**BOILING POINT:** Unknown  
**VAPOR DENSITY (Air=1):** >1  
**SOLUBILITY IN WATER:** Soluble  
**pH VALUE:** ND  
**MELTING/FREEZING POINT:** ND

### **Section X - REACTIVITY**

**STABILITY:** Stable under normal conditions of storage and handling  
**CONDITIONS TO AVOID INSTABILITY:** Do not store containers in direct sunlight or where conditions will heat them above 120° F  
**HAZARDOUS POLYMERIZATION:** Will not occur  
**CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION:** N/A  
**MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY:** Strong oxidizing agents

### **Section XI - TOXICOLOGICAL INFORMATION**

No specific toxicological data is available for this product. Please refer to Section III for available information on potential health effects.

### **Section XII - ECOLOGICAL INFORMATION**

No specific ecological data are available for this product. Please refer to Section VI for information regarding accidental releases and Section XV for regulatory reporting information

### **Section XIII - DISPOSAL CONSIDERATIONS**

All recovered material should be packaged, labeled, transported, disposed and reclaimed in conformance with federal, state and local regulations. May be disposed of by controlled incineration. Do not contaminate any lakes, streams, ponds, or underground water supplies. Empty containers may be disposed of as normal refuse. Please recycle whenever possible. Dispose of according to all federal, state and local regulations.

### **Section XIV - TRANSPORT INFORMATION**

<b>U. S. DOT PROPER SHIPPING NAME:</b>	Consumer Commodity
<b>U. S. DOT HAZARD CLASS:</b>	ORM-D
<b>U. S. DOT LABELS REQUIRED:</b>	None
<b>U. S. DOT PLACARDS REQUIRED:</b>	None
<b>EMERGENCY RESPONSE GUIDE NUMBER:</b>	NAERG #171

---

<b>IATA PROPER SHIPPING NAME:</b>	Consumer Commodity ORM-D (Domestic) Aerosols, Flammable, N.O.S., UN1950 (Export)
<b>IATA HAZARD CLASS:</b>	<b>2.1</b>

**IATA LABELS REQUIRED:** Consumer Commodity ORM-D-Air (Domestic)  
Flammable Gas (Export)

**BILL OF LADING DESCRIPTION:** Consumer Commodity ORM-D-AIR, 9, ID8000  
(Domestic) Aerosols, Flammable, N.O.S., 2.1, UN  
1950 (Export)

**UN/NA CODE:** NA (Domestic)  
UN1950 (Export)

**PACKING INSTRUCTIONS:** 910 (Domestic)  
203/Y203 (Export)  
Authorization: Limited Quantity

**EMERGENCY RESPONSE GUIDE NUMBER:** 126

**EMERGENCY RESPONSE NUMBERS:** CHEMTREC:  
Domestic North America 800-424-9300  
International: 01-703-527-3887 (Collect calls  
accepted)

**IMDG PROPER SHIPPING NAME:** Aerosols

**IMDG HAZARD CLASS:** 2.1

**IMDG LABELS REQUIRED:** **CARTON MUST BE MARKED "AEROSOLS"**

**IMDG SECONDARY LABELS REQUIRED:** **Hollow Diamond with UN1950 Marked in Center**

**IMDG PLACARDS REQUIRED:** None

**BILL OF LADING DESCRIPTION:** Aerosol, 2, UN1950

**MARINE POLLUTANT:** No

**EMERGENCY RESPONSE GUIDE NUMBER:** 126

**EMS NUMBER:** 2 - 13

**MFAG NUMBER:** 620

**EMERGENCY RESPONSE NUMBERS:** CHEMTREC:  
Domestic North America 800-424-9300  
International: 01-703-527-3887 (Collect calls  
accepted)

**IMDG PAGE NUMBER:** 2102

**UN/NA CODE:** UN1950

### Section XV - REGULATORY INFORMATION

**TSCA:** Components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory

**SARA TITLE III, Section 311-312:** Acute, Fire, Sudden Release (Ethane,1,1-Difluoro-);Acute and Fire Hazard (Ethane,1,1-Difluoro-, Ethanol)

**SARA TITLE III, Section 313:** None noted

**CALIFORNIA PROPOSITION 65:** Not Regulated

### Section XVI - OTHER INFORMATION

**HAZARD RATING SYSTEMS:** This information is for people trained in: National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and/or National Fire Protection Association (NFPA 704) Identification of the Fire Hazards of Materials.

	NPCA-HMIS	NFPA 704	KEY:NPCA-HMIS/NFPA 704
HEALTH	1	NA	4=Severe/Extreme
FLAMMABILITY	3	NA	3=Serious/High
REACTIVITY	0	NA	2=Moderate/Moderate
			1=Slight/Slight
			0=Minimal/Insignificant

NOTE: The information presented herein for this product or its components has been compiled from different supplier sources considered to be dependable and is accurate to the best of our knowledge as to the proper use and handling of this product under normal conditions. However, no representation, warranty, or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Any use of this product which is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

#### EXPLANATION OF ABBREVIATIONS:

ACGIH - American Conference of Governmental Industrial Hygienists  
CAS# - Chemical Abstract System No.  
DOT -Department Of Transportation  
IMDG - International Maritime Dangerous Goods code  
NA - Not Applicable  
ND - Not Determined  
NFPA - National Fire Protection Association  
OSHA - Occupational Safety and Health Administration  
PEL - Permissible Exposure Limits  
ppm - Parts Per Million  
PMCC - Pensky-Martin Closed Cup (flash point)  
SARA - Superfund Amendments and Reauthorization Act Title I, II, III  
TLV - Threshold Limit Value

This MSDS has been formatted to be consistent with ANSI Standard Z400.1-1993