



Customer No.: 222397
Shipping Address:
 21551 Prairie Street
 Chatsworth, CA 91311
 (818) 718-6982

HEALTHY SEXY HAIR REINVENT COLOR CARE TOP COAT

Section I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS FIRST PREPARATION DATE: November 3, 2010
REVISION DATE: N/A
SUPERSEDES: N/A
FORMULA: **KAH-042910A**
PREPARED AND REVISED BY: Alison Robinson
GENERIC/CHEMICAL NAME:
PRODUCT TYPE/CHEMICAL FAMILY: N/A
PRODUCT CODE: **34TOP05; 34TOP16**
SYNONYMS: None
CONTACT ADDRESS: Sexy Hair Concepts, 21551 Prairie Street, Chatsworth, CA 91311
EMERGENCY PHONE NUMBERS:
CHEMTREC: Domestic North America 800-424-9300; International: 703-527-3887 (collect calls accepted)

Section II - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Percent	Exposure Limits in Air	
			TLV ppm	PEL ppm
None	None	None	None	None

Section III - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS
EYE CONTACT: May cause eye irritation and/or blurring vision.
SKIN CONTACT: May be irritating to extra-sensitive skin
INHALATION: Not Applicable
INGESTION: Harmful if swallowed. May cause gastrointestinal irritation.

Section IV - FIRST AID

EYE CONTACT: If material gets into the eyes, flush eyes immediately with clean water for at least 15 minutes. If available, use eye-cups or eye wash fountain. If symptoms persist, get medical attention.

SKIN CONTACT: Clean affected areas with mild soap and water. If symptoms persist, get medical attention. Launder contaminated clothing before re-use.

INHALATION: Not applicable

INGESTION: Give several glasses of water to dilute. Never give fluids or induce vomiting. Seek medical attention or Poison Control Center.

Section V - FIRE FIGHTING MEASURES

FLASH POINT: N/A

AUTOIGNITION TEMPERATURE: NA

FLAMMABILITY LIMITS IN AIR (% V): NA

EXTINGUISHING MEDIA: Water Fog, Sand/Earth, Foam, and Carbon Dioxide.

SPECIAL FIRE FIGHTING PROCEDURES: Must wear NIOSH approved self-containing breathing apparatus and protective clothing. Cool fire exposed container with water spray.

UNUSUAL FIRE & EXPLOSION HAZARDS: NA

Section VI - ACCIDENTAL RELEASE MEASURES

SPILL ON LAND: Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without risk. Minimize breathing of vapors. Minimize skin contact. Ventilate confined spaces. For small spills implement the following cleanup procedures: Prevent material from entering sewers, watercourses, or low areas. Contain spilled material with sand or earth.. For large spills implement the preceding cleanup procedures and, if in public area, keep public away and advise authorities. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Section VII - STORAGE AND HANDLING

STORAGE TEMPERATURE: Ambient

STORAGE/TRANSPORT PRESSURE: Ambient

LOADING/UNLOADING TEMPERATURE: Ambient

STORAGE AND HANDLING: Protect containers against physical damage. Keep closed until used. Store in a dry place at ambient temperatures. Keep out of reach of children.

Section VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: None Required.

VENTILATION: Normal Ventilation adequate for recommended uses.

PROTECTIVE CLOTHING: Not necessary except as a good industrial practice.

EYE PROTECTION: Avoid contact with eyes.

OTHER PRECAUTIONS: Read and follow all label directions and cautions. Use only as directed.

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Gel

STATE: Liquid

ODOR: Citrus Floral

PERCENT VOLATILE:

SPECIFIC GRAVITY: 1.000 +/-0.01

VISCOSITY: 16,000 – 24, 000 CPS

EVAPORATION RATE: Slower than Ether

VAPOR PRESSURE mm Hg @ 20°C: NA

BOILING POINT: Not determined
VAPOR DENSITY (Air=1): Heavier than Air
SOLUBILITY IN WATER: Miscible
pH VALUE: 5.00 – 5.50
MELTING/FREEZING POINT: 0°C

Section X - REACTIVITY

STABILITY: Stable under normal conditions of storage and handling
CONDITIONS TO AVOID INSTABILITY: Strong acids and oxidizing agents
HAZARDOUS POLYMERIZATION: Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS: May produce toxic fumes of oxides of carbon, sulfur and nitrogen; ammonia
MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Extreme temperatures

Section XI - TOXICOLOGICAL INFORMATION

No specific toxicological data is available for this product. Please refer to Section III for available information on potential health effects.

Section XII - ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section VI for information regarding accidental releases and Section XV for regulatory reporting information

Section XIII - DISPOSAL CONSIDERATIONS

All recovered material should be packaged, labeled, transported, disposed and reclaimed in conformance with federal, state and local regulations. Do not contaminate any lakes, streams, ponds, or underground water supplies. Empty containers may be disposed of as normal refuse. Please recycle whenever possible.

Section XIV - TRANSPORT INFORMATION

U. S. DOT PROPER SHIPPING NAME: Not Regulated
U. S. DOT HAZARD CLASS: None
U. S. DOT LABELS REQUIRED: None
U. S. DOT PLACARDS REQUIRED: None
EMERGENCY RESPONSE GUIDE NUMBER: None

IATA PROPER SHIPPING NAME: None
IATA HAZARD CLASS: None
IATA LABELS REQUIRED: None
BILL OF LADING DESCRIPTION: Healthy Sexy Hair Reinvent Color Care Top Coat
UN/NA CODE: None
PACKING INSTRUCTIONS: None
EMERGENCY RESPONSE GUIDE NUMBER: None
EMERGENCY RESPONSE NUMBERS: CHEMTREC:
Domestic North America 800-424-9300
International: 01-703-527-3887 (Collect calls accepted)

IMDG PROPER SHIPPING NAME:	None
IMDG HAZARD CLASS:	None
IMDG LABELS REQUIRED:	None
IMDG SECONDARY LABELS REQUIRED:	None
IMDG PLACARDS REQUIRED:	None
BILL OF LADING DESCRIPTION:	Healthy Sexy Hair Reinvent Color Care Top Coat
MARINE POLLUTANT:	No
EMERGENCY RESPONSE GUIDE NUMBER:	None
EMS NUMBER:	None
MFAG NUMBER:	None
EMERGENCY RESPONSE NUMBERS:	CHEMTREC: Domestic North America 800-424-9300 International: 01-703-527-3887 (Collect calls accepted)
IMDG PAGE NUMBER:	None
UN/NA CODE:	None

Section XV - REGULATORY INFORMATION

TSCA: Components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory **SARA TITLE III, Section 311-312:** Acute, Fire, Sudden Release (Ethane,1,1-Difluoro-); Acute and Fire Hazard Ethane,1,1-Difluoro-, Ethanol)

SARA TITLE III, Section 313: None noted

CALIFORNIA PROPOSITION 65: Not Regulated

Section XVI - OTHER INFORMATION

HAZARD RATING SYSTEMS: This information is for people trained in: National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and/or National Fire Protection Association (NFPA 704) Identification of the Fire Hazards of Materials.

	NPCA-HMIS	NFPA 704	KEY:NPCA-HMIS/NFPA 704
HEALTH	1	NA	4=Severe/Extreme
FLAMMABILITY	0	NA	3=Serious/High
REACTIVITY	0	NA	2=Moderate/Moderate 1=Slight/Slight 0=Minimal/Insignificant

NOTE: The information presented herein for this product or its components has been compiled from different supplier sources considered to be dependable and is accurate to the best of our knowledge as to the proper use and handling of this product under normal conditions. However, no representation, warranty, or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Any use of this product which is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

EXPLANATION OF ABBREVIATIONS:

ACGIH - American Conference of Governmental Industrial Hygienists

CAS# - Chemical Abstract System No.

DOT -Department Of Transportation

IMDG - International Maritime Dangerous Goods code

NA - Not Applicable

ND - Not Determined

NFPA - National Fire Protection Association

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limits

ppm - Parts Per Million

PMCC - Pensky-Martin Closed Cup (flash point)

SARA - Superfund Amendments and Reauthorization Act Title I, II, III

TLV - Threshold Limit Value

This MSDS has been formatted to be consistent with ANSI Standard Z400.1-1993