

Customer No.: 222397 Shipping Address: 20621 Prairie Avenue Chatsworth, CA 91311 (818) 435-0800

STYLE SEXY HAIR FRENZY

Section I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS FIRST PREPARATION DATE: August 7, 2013

REVISION DATE: SUPERSEDES:

FORMULA: AM60-7A

PREPARED AND REVISED BY: Teresa Romero GENERIC/CHEMICAL NAME: Styling Pomade PRODUCT TYPE/CHEMICAL FAMILY: NA

PRODUCT CODE: 18FRENZY02; 18FRENZY02N; 18FRENZY02N-CA

SYNONYMS: None

CONTACT ADDRESS: Sexy Hair Concepts, 9232 Eton Avenue, Chatsworth, CA 91311

EMERGENCY PHONE NUMBERS:

CHEMTREC: Domestic North America 800-424-9300; International: 703-527-3887 (collect calls

accepted)

Section II - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Percent	Exposure Limits in Air	
			TLV ppm	PEL ppm
Ethanol	64-17-5	2.0	1000	1000

Section III - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT: May cause eye irritation and/or blurring of vision.

SKIN CONTACT: None known

INHALATION: Unlikely to pose problems when used as directed. **INGESTION**: If ingested, may cause nausea and vomiting.

Section IV - FIRST AID

EYE CONTACT: Flush with plenty of water for 15 minutes, if irritation persists, get medical attention. **SKIN CONTACT**: If irritation is experienced, wash exposed area thoroughly with water. Remove all contaminated clothing and launder. If irritation persists, get medical assistance.

INHALATION: Not applicable.

INGESTION: Do not induce vomiting, give several glasses of water to dilute. Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Seek medical attention or call Poison Control Center.

Section V - FIRE FIGHTING MEASURES

FLASH POINT: ND

AUTOIGNITION TEMPERATURE: ND FLAMMABILITY LIMITS IN AIR (% V): ND

EXTINGUISHING MEDIA: Carbon Dioxide, Foam, Dry Chemical, Water-fog, sand/earth.

SPECIAL FIRE FIGHTING PROCEDURES: Keep containers cool by spraying them with water until the fire has been extinguished. A self-contained breathing apparatus and protective clothing should be worn when fighting fires.

UNUSUAL FIRE & EXPLOSION HAZARDS: ND

Section VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Caution! Floor may become slippery. Absorb spilled material with inert material such as sawdust, sand, or earth. Final cleaning may require use of steam, solvents, or detergents. Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without risk. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Leaking containers should be placed in open containers, outdoors, away from any source of ignition, until all pressure has been released.

Section VII - STORAGE AND HANDLING

STORAGE TEMPERATURE: Ambient

STORAGE/TRANSPORT PRESSURE: Ambient LOADING/UNLOADING TEMPERATURE: Ambient

STORAGE AND HANDLING: Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. Store at temperatures below 75°F. DO NOT handle or store near an open flame, heat, or other source of ignition. DO NOT pressurize, cut, heat, or weld empty containers. DO NOT reuse containers. Keep out of reach of children.

Section VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: NA

VENTILATION: Normal Ventilation adequate for recommended uses.

PROTECTIVE CLOTHING: NA

EYE PROTECTION: NA

OTHER PRECAUTIONS: Keep product in tightly closed containers. Keep product away from children's reach. Keep product away from source of heat and open flames. . Read and follow all label directions and cautions. Use only as directed

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Light bluish-violet paste like.

STATE: Paste

ODOR: Characteristic - Fruity **PERCENT VOLATILE**: ND

SPECIFIC GRAVITY: Approx. 0.9336

VISCOSITY: NA

EVAPORATION RATE: ND

VAPOR PRESSURE mm Hg @ 20°C: ND

BOILING POINT: ND

VAPOR DENSITY (Air=1): ND

SOLUBILITY IN WATER: Appreciable

pH VALUE: 4.0 - 5.0

Section X - REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID INSTABILITY: Extreme temperatures.

HAZARDOUS POLYMERIZATON: Will not occur

CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION: ND MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: ND

Section XI - TOXICOLOGICAL INFORMATION

No specific toxicological data is available for this product. Please refer to Section III for available information on potential health effects.

Section XII - ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section VI for information regarding accidental releases and Section XV for regulatory reporting information

Section XIII - DISPOSAL CONSIDERATIONS

All recovered material should be packaged, labeled, transported, disposed and reclaimed in conformance with federal, state and local regulations. Do not contaminate any lakes, streams, ponds, or underground water supplies. Empty containers may be disposed of as normal refuse. Please recycle whenever possible.

Section XIV - TRANSPORT INFORMATION

U. S. DOT PROPER SHIPPING NAME: Not Regulated

U. S. DOT HAZARD CLASS: None
U. S. DOT LABELS REQUIRED: None
U. S. DOT PLACARDS REQUIRED: None
EMERGENCY RESPONSE GUIDE NUMBER: None

IATA PROPER SHIPPING NAME: Not regulated.

IATA HAZARD CLASS: None IATA LABELS REQUIRED: None

BILL OF LADING DESCRIPTION: Short Frenzy Bulked Up Texture

UN/NA CODE: None
PACKING INSTRUCTIONS: None
EMERGENCY RESPONSE GUIDE NUMBER: None

EMERGENCY RESPONSE NUMBERS: CHEMTREC:

Domestic North America 800-424-9300 International: 01-703-527-3887 (Collect calls

accepted)

IMDG PROPER SHIPPING NAME: Not Regulated.

IMDG HAZARD CLASS:NoneIMDG LABELS REQUIRED:NoneIMDG SECONDARY LABELS REQUIRED:NoneIMDG PLACARDS REQUIRED:None

BILL OF LADING DESCRIPTION: Short Frenzy Bulked Up Texture

MARINE POLLUTANT:

EMERGENCY RESPONSE GUIDE NUMBER:

EMS NUMBER:

None

MFAG NUMBER:

None

EMERGENCY RESPONSE NUMBERS:

CHEMTREC:

Domestic North America 800-424-9300 International: 01-703-527-3887 (Collect calls

accepted)

IMDG PAGE NUMBER: None UN/NA CODE: None

Section XV - REGULATORY INFORMATION

TSCA: Components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory **SARA TITLE III, Section 311-312**: Acute, Fire, Sudden Release (Ethane,1,1-Difuoro-); Acute and Fire Hazard Ethane,1,1-Difuoro-, Ethanol)

SARA TITLE III, Section 313: None noted

CALIFORNIA PROPOSITION 65: Not Regulated

Section XVI - OTHER INFORMATION

HAZARD RATING SYSTEMS: This information is for people trained in: National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and/or National Fire Protection Association (NFPA 704) Identification of the Fire Hazards of Materials.

	NPCA-HMIS	NFPA 704	KEY:NPCA-HMIS/NFPA 704
HEALTH FLAMMABILITY REACTIVITY	1 1 0	NA NA NA	4=Severe/Extreme 3=Serious/High 2=Moderate/Moderate 1=Slight/Slight
			0=Minimal/Insignificant

NOTE: The information presented herein for this product or its components has been compiled from different supplier sources considered to be dependable and is accurate to the best of our knowledge as to the proper use and handling of this product under normal conditions. However, no representation, warranty, or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Any use of this product which is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

EXPLANATION OF ABBREVIATIONS:

ACGIH - American Conference of Governmental Industrial Hygienists

CAS# - Chemical Abstract System No.

DOT -Department Of Transportation

IMDG - International Maritime Dangerous Goods code

NA - Not Applicable

ND - Not Determined

NFPA - National Fire Protection Association

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limits

ppm - Parts Per Million

PMCC - Pensky-Martin Closed Cup (flash point)

SARA - Superfund Amendments and Reauthorization Act Title I, II, III

TLV - Threshold Limit Value

This MSDS has been formatted to be consistent with ANSI Standard Z400.1-1993