

Customer No.: 222397 **Shipping Address:**

20621 Prairie Avenue Chatsworth, CA 91311

(818) 435-0800

STYLE SEXY HAIR PLAY DIRTY DRY WAX

Section I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS FIRST PREPARATION DATE: August 7, 2013

REVISION DATE: SUPERSEDES: FORMULA: 116-25A

PREPARED AND REVISED BY: Teresa Romero GENERIC/CHEMICAL NAME: Spray Wax PRODUCT TYPE/CHEMICAL FAMILY: NA

PRODUCT CODE: 18PLAY04; 18PLAY04N; 18PLAY04N-HW; 18PLAY05

SYNONYMS: None

CONTACT ADDRESS: Sexy Hair Concepts, 21551 Prairie, Chatsworth, CA 91311

EMERGENCY PHONE NUMBERS:

CHEMTREC: Domestic North America 800-424-9300; International: 703-527-3887 (collect calls

accepted)

Section II - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Percent	Exposure Limits in Air	
_			TLV ppm	PEL ppm
Ethanol	64-17-5	38.0	1000	1000
Hydrofluorocarbon 152a	75-37-6	50.0	1000	ND

Section III - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Direct contact of product with eyes may cause irritation, and may result in irreversible damage.

SKIN CONTACT: Repeated contact may cause irritation and drying of the skin. Contact with propellant may cause freeze burns.

INHALATION: Vapor may cause irritation to the upper respiratory tract.

INGESTION: If ingested, may cause nausea and vomiting. If in aerosol form, ingestion is not likely.

Section IV - FIRST AID

EYE CONTACT: If irritation or redness due to vapors develops, move victim away from exposure and into fresh air. If material gets into the eyes, flush eyes immediately with clean water for at least 15 minutes. If available, use eye-cups or eye wash fountain. If symptoms persist, get medical attention.

SKIN CONTACT: Clean affected areas with mild soap and water. Remove contaminated clothing, including shoes, and launder before reuse or discard.

INHALATION: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, get medical attention. If victim is not breathing immediately begin artificial respiration. Get medical attention.

INGESTION: Product is not likely to be ingested. If this occurs, treat systematically. Never give fluids or induce vomiting if the victim is unconscious or having convulsions.

Section V - FIRE FIGHTING MEASURES

FLASH POINT: < 73°F TCC

AUTOIGNITION TEMPERATURE: NA

FLAMMABILITY LIMITS IN AIR (% V): Not known.

EXTINGUISHING MEDIA: Carbon Dioxide, Foam, Dry Chemical, Water

SPECIAL FIRE FIGHTING PROCEDURES: Fire should be fought from a safe distance. Keep

containers cool by spraying them with water until the fire has been extinguished.

UNUSUAL FIRE & EXPLOSION HAZARDS: Containers may rupture and release flammable liquids and /or gasses if exposed to the heat of fire.

Section VI - ACCIDENTAL RELEASE MEASURES

SPILL ON LAND (LARGE SPILL): Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without risk. Minimize breathing of vapors. Minimize skin contact. Ventilate confined spaces. For small spills implement the following cleanup procedures: Prevent material from entering sewers, watercourses, or low areas. Contain spilled material with sand or earth. Do not use combustible materials such as sawdust. Observe precautions for volatile, combustible vapors from absorbed material. For large spills implement the preceding cleanup procedures and, if in public area, keep public away and advise authorities. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SPILL ON WATER (LARGE SPILL): Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or scooping up floating material. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SMALL SPILLS: Leaking containers should be placed in open containers, outdoors, away from any source of ignition, until all pressure has been released.

Section VII - STORAGE AND HANDLING

STORAGE TEMPERATURE: Ambient

STORAGE/TRANSPORT PRESSURE: 180 psig @ 131°F Max

LOADING/UNLOADING TEMPERATURE: Ambient

WORK AND HYGIENE PRACTICES: Wash hands thoroughly after using this product and before eating, drinking, or smoking.

STORAGE AND HANDLING: Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. DO NOT handle or store near an open flame, heat, or other source of ignition. DO NOT pressurize, cut, heat, or weld empty containers. DO NOT reuse containers.

Section VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: None Required when used with adequate ventilation.

VENTILATION: Normal Ventilation adequate for recommended uses.

PROTECTIVE CLOTHING: Not necessary except as a good industrial practice.

EYE PROTECTION: Not necessary except as a good industrial practice.

OTHER PRECAUTIONS: Avoid excessive inhalation. Read and follow all label directions and cautions. Use only as directed

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Opaque white foam.

STATE: Aerosol ODOR: Characteristic

PERCENT VOLATILE: Approx. 86%

SPECIFIC GRAVITY: 0.884 (prior to addition of propellant)

VISCOSITY: Aerosol @ ambient EVAPORATION RATE: ND

VAPOR PRESSURE mm Hg @ 20°C: Can pressure not to exceed 180 psig @ 131°F

BOILING POINT: Unknown **VAPOR DENSITY (Air=1)**: > 1

SOLUBILITY IN WATER: Soluble in water.

Section X - REACTIVITY

STABILITY: Stable under normal conditions of storage and handling

CONDITIONS TO AVOID INSTABILITY: Do not store containers in direct sunlight or where

conditions will heat them above 120°F.

HAZARDOUS POLYMERIZATON: Will not occur

CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION: Not Applicable

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents.

Section XI - TOXICOLOGICAL INFORMATION

No specific toxicological data is available for this product. Please refer to Section III for available information on potential health effects.

Section XII - ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section VI for information regarding accidental releases and Section XV for regulatory reporting information

Section XIII - DISPOSAL CONSIDERATIONS

All recovered material should be packaged, labeled, transported, disposed and reclaimed in conformance with local, county, state, and federal regulations. May be disposed of by controlled incineration. Do not contaminate any lakes, streams, ponds, or underground water supplies. Empty containers may be disposed of as normal refuse. Please recycle whenever possible. Dispose of in accordance with federal, state and local regulations.

Section XIV - TRANSPORT INFORMATION

U. S. DOT PROPER SHIPPING NAME: Consumer Commodity

U. S. DOT HAZARD CLASS: ORM-D
U. S. DOT LABELS REQUIRED: None
U. S. DOT PLACARDS REQUIRED: None
EMERGENCY RESPONSE GUIDE NUMBER: NAERG# 171

IATA PROPER SHIPPING NAME: Consumer Commodity ORM-D (Domestic)

Aerosols, Flammable, N.O.S., UN1950 (Export)

IATA HAZARD CLASS:

IATA LABELS REQUIRED: Consumer Commodity ORM-D-AIR (Domestic)

Flammable Gas (Export)

BILL OF LADING DESCRIPTION: Consumer Commodity ORM-D-AIR, 9, ID8000

(Domestic)

Aerosols, Flammable, N.O.S., 2.1, UN1950 (Export)

UN/NA CODE: NA (Domestic)

UN1950 (Export) 910 (Domestic)

PACKING INSTRUCTIONS: 910 (Domestic) 203/Y203 (Export)

Authorization: Limited Quantity

EMERGENCY RESPONSE GUIDE NUMBER: 126

EMERGENCY RESPONSE NUMBERS: CHEMTREC:

Domestic North America 800-424-9300 International: 01-703-527-3887 (Collect calls

accepted)

IMDG PROPER SHIPPING NAME: Aerosols **IMDG HAZARD CLASS:** 2.1

IMDG LABELS REQUIRED: CARTON MUST BE MARKED "AEROSOLS" Hollow Diamond with UN1950 Marked in Center

IMDG PLACARDS REQUIRED: None

BILL OF LADING DESCRIPTION: Aerosol, 2, UN1950

MARINE POLLUTANT:NoEMERGENCY RESPONSE GUIDE NUMBER:126EMS NUMBER:2-13MFAG NUMBER:620

EMERGENCY RESPONSE NUMBERS: CHEMTREC:

Domestic North America 800-424-9300 International: 01-703-527-3887 (Collect calls

accepted)

IMDG PAGE NUMBER:2102UN/NA CODE:UN1950

Section XV - REGULATORY INFORMATION

TSCA: Components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory **SARA TITLE III, Section 311-312**: Acute, Fire, Sudden Release (Dimethyl Ether DME); Acute and Fire Hazard (Dimethyl Ether DME, Ethanol)

SARA TITLE III, Section 313: None noted

CALIFORNIA PROPOSITION 65: Not Regulated

Section XVI - OTHER INFORMATION

HAZARD RATING SYSTEMS: This information is for people trained in: National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and/or National Fire Protection Association (NFPA 704) Identification of the Fire Hazards of Materials.

	NPCA-HMIS	NFPA 704	KEY:NPCA-HMIS/NFPA 704
HEALTH	1	NA	4=Severe/Extreme 3=Serious/High 2=Moderate/Moderate 1=Slight/Slight 0=Minimal/Insignificant
FLAMMABILITY	4	NA	
REACTIVITY	1	NA	

NOTE: The information presented herein for this product or its components has been compiled from different supplier sources considered to be dependable and is accurate to the best of our knowledge as to the proper use and handling of this product under normal conditions. However, no representation, warranty, or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Any use of this product which is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

EXPLANATION OF ABBREVIATIONS:

ACGIH - American Conference of Governmental Industrial Hygienists

CAS# - Chemical Abstract System No.

DOT -Department Of Transportation

IMDG - International Maritime Dangerous Goods code

NA - Not Applicable

ND - Not Determined

NFPA - National Fire Protection Association

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limits

ppm - Parts Per Million

PMCC - Pensky-Martin Closed Cup (flash point)

SARA - Superfund Amendments and Reauthorization Act Title I, II, III

TLV - Threshold Limit Value

This MSDS has been formatted to be consistent with ANSI Standard Z400.1-1993