



Customer No.: 222397
Shipping Address:
 21551 Prairie Street
 Chatsworth, CA 91311
 (818) 435-0800

**SHORT SEXY HAIR
 ROCKED-OUT
 PLIABLE MOLDING CLAY**

Section I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS FIRST PREPARATION DATE: October 31, 2008
REVISION DATE: N/A
SUPERSEDES: N/A
FORMULA: TB-162-14
PREPARED AND REVISED BY: Joe Mendoza
GENERIC/CHEMICAL NAME: Hair Molding Clay
PRODUCT TYPE/CHEMICAL FAMILY: NA
PRODUCT CODE:
SYNONYMS: None
CONTACT ADDRESS: Sexy Hair Concepts, 21551 Prairie Street, Chatsworth, CA 91311

EMERGENCY PHONE NUMBERS:
 CHEMTREC: Domestic North America 800-424-9300; International: 703-527-3887 (collect calls accepted)

Section II - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Percent	Exposure Limits in Air	
			TLV ppm	PEL ppm
None	None	None	None	None

Section III - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS
EYE CONTACT: May cause eye irritation and/or blurred vision.
SKIN CONTACT: Not Known
INHALATION: Not Known
INGESTION: If ingested, may cause nausea and vomiting.

Section IV - FIRST AID

EYE CONTACT: If material gets into the eyes, flush eyes immediately with clean water for at least 15 minutes. If available, use eye-cups or eye wash fountain. If symptoms persist, get medical attention.
SKIN CONTACT: Clean affected areas with mild soap and water. If symptoms persist, get medical attention.
INHALATION: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, get medical attention. If victim is not breathing immediately begin artificial respiration. Get medical attention.

INGESTION: Give several glasses of water to dilute. Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Seek medical attention or Poison Control Center.

Section V - FIRE FIGHTING MEASURES

FLASH POINT: N/A

AUTOIGNITION TEMPERATURE: N/A

FLAMMABILITY LIMITS IN AIR (% V): N/A

EXTINGUISHING MEDIA: Carbon Dioxide, Foam, Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Not known.

UNUSUAL FIRE & EXPLOSION HAZARDS: N/A

Section VI - ACCIDENTAL RELEASE MEASURES

SPILL ON LAND: Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without risk. Minimize breathing of vapors. Minimize skin contact. Ventilate confined spaces. For small spills implement the following cleanup procedures: Prevent material from entering sewers, watercourses, or low areas. Contain spilled material with sand or earth. Do not use combustible materials such as sawdust. Observe precautions for volatile, combustible vapors from absorbed material. For large spills implement the preceding cleanup procedures and, if in public area, keep public away and advise authorities. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Leaking containers should be placed in open containers, outdoors, away from any source of ignition, until all pressure has been released.

Section VII - STORAGE AND HANDLING

STORAGE TEMPERATURE: Ambient

STORAGE/TRANSPORT PRESSURE: Ambient

LOADING/UNLOADING TEMPERATURE: Ambient

STORAGE AND HANDLING: Keep container closed. Do not store in heat or direct sunlight.

Section VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: None Required. If vapors are generated, respirator required.

VENTILATION: Normal Ventilation adequate for recommended uses.

PROTECTIVE CLOTHING: Not necessary except as a good industrial practice.

EYE PROTECTION: Avoid contact with eyes.

OTHER PRECAUTIONS: Avoid excessive inhalation. Read and follow all label directions and cautions. Use only as directed.

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Semi-solid styling clay to match standard..

STATE: Semi-solid

ODOR: Characteristic

PERCENT VOLATILE: >25% as water

SPECIFIC GRAVITY: min. 0.95

VISCOSITY: min 600,000 cps

EVAPORATION RATE: N/A

VAPOR PRESSURE mm Hg @ 20°C: N/A

BOILING POINT: 100° C
VAPOR DENSITY (Air=1): N/A
SOLUBILITY IN WATER: Dispersible
pH VALUE: Min. 5.00
MELTING/FREEZING POINT: 0°C

Section X - REACTIVITY

STABILITY: Stable under normal conditions of storage and handling
CONDITIONS TO AVOID INSTABILITY: High temperature.
HAZARDOUS POLYMERIZATION: Will not occur
CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION: N/A
MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: None known.
HAZARDOUS DECOMPOSITION PRODUCTS: Under severe heat or ignition will generate carbon monoxide, oxides of nitrogen, and other organic breakdown fumes.

Section XI - TOXICOLOGICAL INFORMATION

No specific toxicological data is available for this product. Please refer to Section III for available information on potential health effects.

Section XII - ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section VI for information regarding accidental releases and Section XV for regulatory reporting information

Section XIII - DISPOSAL CONSIDERATIONS

All recovered material should be packaged, labeled, transported, disposed and reclaimed in conformance with federal, state and local regulations. Do not contaminate any lakes, streams, ponds, or underground water supplies. Empty containers may be disposed of as normal refuse. Please recycle whenever possible.

Section XIV - TRANSPORT INFORMATION

U. S. DOT PROPER SHIPPING NAME:	Not Regulated
U. S. DOT HAZARD CLASS:	None
U. S. DOT LABELS REQUIRED:	None
U. S. DOT PLACARDS REQUIRED:	None
EMERGENCY RESPONSE GUIDE NUMBER:	None

IATA PROPER SHIPPING NAME:	None
IATA HAZARD CLASS:	None
IATA LABELS REQUIRED:	None
BILL OF LADING DESCRIPTION:	Rocked-Out Pliable Molding Clay
UN/NA CODE:	None
PACKING INSTRUCTIONS:	None
EMERGENCY RESPONSE GUIDE NUMBER:	None
EMERGENCY RESPONSE NUMBERS:	CHEMTREC: Domestic North America 800-424-9300 International: 01-703-527-3887 (Collect calls accepted)

IMDG PROPER SHIPPING NAME:	None
-----------------------------------	------

IMDG HAZARD CLASS: None
IMDG LABELS REQUIRED: None
IMDG SECONDARY LABELS REQUIRED: None
IMDG PLACARDS REQUIRED: None
BILL OF LADING DESCRIPTION: Rocked-Out Pliable Molding Clay
MARINE POLLUTANT: No
EMERGENCY RESPONSE GUIDE NUMBER: None
EMS NUMBER: None
MFAG NUMBER: None
EMERGENCY RESPONSE NUMBERS: CHEMTREC:
 Domestic North America 800-424-9300
 International: 01-703-527-3887 (Collect calls accepted)
IMDG PAGE NUMBER: None
UN/NA CODE: None

Section XV - REGULATORY INFORMATION

TSCA: Components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory
SARA TITLE III, Section 311-312: Acute, Fire, Sudden Release (Ethane,1,1-Difluoro-); Acute and Fire Hazard Ethane,1,1-Difluoro-, Ethanol)
SARA TITLE III, Section 313: None noted
CALIFORNIA PROPOSITION 65: Not Regulated

Section XVI - OTHER INFORMATION

HAZARD RATING SYSTEMS: This information is for people trained in: National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and/or National Fire Protection Association (NFPA 704) Identification of the Fire Hazards of Materials.

	NPCA-HMIS	NFPA 704	KEY:NPCA-HMIS/NFPA 704
HEALTH	1	NA	4=Severe/Extreme
FLAMMABILITY	0	NA	3=Serious/High
REACTIVITY	0	NA	2=Moderate/Moderate 1=Slight/Slight 0=Minimal/Insignificant

NOTE: The information presented herein for this product or its components has been compiled from different supplier sources considered to be dependable and is accurate to the best of our knowledge as to the proper use and handling of this product under normal conditions. However, no representation, warranty, or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Any use of this product which is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

EXPLANATION OF ABBREVIATIONS:

ACGIH - American Conference of Governmental Industrial Hygienists
 CAS# - Chemical Abstract System No.
 DOT -Department Of Transportation

IMDG - International Maritime Dangerous Goods code
NA - Not Applicable
ND - Not Determined
NFPA - National Fire Protection Association
OSHA - Occupational Safety and Health Administration
PEL - Permissible Exposure Limits
ppm - Parts Per Million
PMCC - Pensky-Martin Closed Cup (flash point)
SARA - Superfund Amendments and Reauthorization Act Title I, II, III
TLV - Threshold Limit Value

This MSDS has been formatted to be consistent with ANSI Standard Z400.1-1993