



Material Safety Data Sheet

Section 01 – Product Identification

TIGI Linea, LP
1655 Waters Ridge Dr.
Lewisville, TX 75057
469 528-4300
800 259-8596

In case of medical emergencies, please contact your local poison control center.
Transportation Emergency Telephone: CHEMTREC #: 1800 424-9300 (24 Hours)

Trade Name: **TIGI Catwalk Curlesque Lightweight Mousse**

Section 02 – Hazards Identification

WARNING: Warning: Extremely Flammable. Pressurized Container: Protect from sunlight and do not expose to temperatures exceeding 50 °C (120 °F). Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material. Keep away from sources of ignition – No smoking. Keep out of reach of children. Avoid spraying in eyes. Use only as directed. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

HAZARD RATINGS: Health: 1, Fire: 2, Physical Hazards: 1
Ratings are based on a 0-4 scale, with 0 representing minimal and 4 representing significant hazards or risks.

Section 03 – Composition/Information on Ingredients

Ingredients as defined by 29 CFR 1910.1200:

CHEMICAL NAME	CAS NUMBER	% RANGE
Dimethyl Ether	115-10-6	1-3
Isobutane	75-28-5	1-3
Propane	74-98-6	1-3

Section 04 – First Aid Measures

Eye Contact: Rinse thoroughly with water.

Skin Contact: Discontinue use if rash or irritation occurs. Rinse with water

Ingestion: Do not induce vomiting. Drink a glass of milk or water.

Inhalation: Move individual to fresh air.

NOTE: If symptoms persist, seek medical attention.

 Section 05 – Fire Fighting Measures

HAZARD CLASSIFICATION: Flammable. See Section XIV for Shipping Classifications.

FLASHPOINT: Not applicable.

NFPA CLASSIFICATION: Aerosol Level 1 per NFPA 30B.

EXTINGUISHING MEDIA: Water mist/spray, carbon dioxide, foams or dry chemicals

SPECIAL FIREFIGHTING PROCEDURES: Since pressurized aerosol cans may explode when exposed to excessive heat, protect from excessive heat with water spray.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen; hydrocarbons & derivatives.

CONTENTS UNDER PRESSURE: Yes. Exposure to temperature > 120°F/50°C may cause bursting.

EXPLOSIVE: Yes.

 Section 06 – Accidental Release Measures

SPILLS, LEAKS: Small or household quantities may be cleaned up and disposed of in normal household trash. For large (industrial) releases, eliminate all sources of ignition and ventilate the area with equipment rated for use in a flammable environment.

 Section 07 – Handling & Storage

HANDLING PRECAUTIONS: Contents under pressure. Do not puncture or incinerate container. Do not use when smoking or in presence of fire, open flame, sparks or heat.

STORAGE REQUIREMENTS: Do not store at temperatures above 120°F/50°C or in enclosed places that could overheat.

 Section 08 – Exposure Control / Personal Protection

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL
Dimethyl Ether	115-10-6	None established	None established
Isobutane	75-28-5	TWA=1000 ppm	None established
Propane	74-98-6	TWA=1000 ppm	TWA=1000 ppm, 1800 mg/m3

PERSONAL PROTECTION

FOR ROUTINE CONSUMER USE: No special precautions necessary. Use only as directed.

FOR INDUSTRIAL ACTIVITIES: Use protective eyewear, gloves, clothing and general ventilation.

 Section 09 – Physical & Chemical Properties (continued)

FORM: Foam in pressurized metal can

COLOR: Foam is white or lightly tinted

ODOR: Characteristic

Section 09 – Physical & Chemical Properties (continued)

SOLUBILITY: Not available

SPECIFIC GRAVITY: Not available

PRESSURE: 50-59 PSIG at 70°F/21°C. 92-102 PSIG at 130°F/54°C.

MELTING POINT: Not available

VISCOSITY: Not available

pH: Not available

EVAPORATION RATE: Not available

PERCENT VOLATILE: Not available

PERCENT VOC: 6%

Section 10 – Stability & Reactivity

STABLE:

Yes

HAZARDOUS DECOMPOSITION PRODUCTS:

None known

INCOMPATIBLE WITH:

Strong oxidizers, acids or bases. Do not expose to heat or in enclosed places that could overheat.

SPECIAL CONDITIONS TO AVOID:

Open flames, high temperatures, sunlight or impact

CORROSIVE TO STEEL, ALUMINUM:

No

Section 11 – Toxicological Information

ACUTE EFFECTS

EYE CONTACT: May cause redness or irritation.

SKIN CONTACT: Overexposure may cause a skin reaction such as redness.

INGESTION: May cause nausea, vomiting and diarrhea.

RESPIRATORY: Not an expected route of exposure but may cause irritation if inhaled.

CHRONIC EFFECTS: None expected

CARCINOGEN CLASSIFICATIONS

NTP: None

IARC: None

OSHA: None

Section 12 – Ecological Information

This product is safe for the environment at the concentrations predicted under normal use conditions.

Section 13 – Disposal Considerations

Disposal by Consumer: Contents under pressure. Do not puncture or incinerate. Waste generated in the course of normal consumer use is not subject to RCRA. Consumer waste should be disposed of in accordance with all applicable local, state and federal regulations.

Disposal by Manufacturer/Vendors: Waste meets the federal definition of hazardous waste due to the ignitability characteristic (D0001) as defined at 40 CFR § 261.21. Hazardous Waste Generator may dispose of individual consumer containers in drums or other appropriate containers. Generator cannot incinerate waste without puncturing and releasing flammable gas from all pressurized consumer packaging using the appropriate aerosol disposal equipment to ensure worker safety.

Section 14 – Transport Information

For Shipping in consumer packaging	Land/Air Cargo (US DOT/ICAO)	Air Passenger (IATA)	Water (IMO/IMDG)
Proper shipping name:	Consumer Commodity	Consumer Commodity	Aerosols
Hazard name:	ORM-D/ORM-D-AIR	9	2
UN/ID #:	None	ID8000	UN1950
Packing Group:	None	None	None
Label Required:	None	Miscellaneous	None

EMERGENCY GUIDE NUMBER: ID8000 Consumer Commodity = 171
 UN1950 Aerosol = 126

DOT HAZARDOUS SUBSTANCE RO: None/no reportable quantities

DOT MARINE POLLUTANTS: None/no reportable quantities

IATA - Substances Forbidden from Air Transport: None/no reportable quantities

IATA - Subst. Forbidden from Passenger Transport: Dimethyl Ether, Isobutane, Propane

Section 15 – Regulatory Information

TSCA: Not applicable

RCRA: See Section XIII - Disposal Considerations

CAA HAPS or Ozone Depletors: None/no reportable quantities

CERCLA/SARA 302 Hazardous Substances: None/no reportable quantities

CERCLA/SARA 311/312 Hazard Categories: None/no reportable quantities

CERCLA/SARA 313 Emissions Reporting: None/no reportable quantities

CERCLA RO: Isobutane, Propane and Dimethyl Ether - 100 lbs

CA 22 CCR Hazardous Wastes: None/no reportable quantities

CA Proposition 65 Listed Chemicals: None/no reportable quantities

IL, MA, NJ, PA, RI State RTK, Hazardous & Other Notifications: Dimethyl Ether, Isobutane, Propane

CANADIAN DSL/NDSL: All components comply with registration requirements

Section 16 – Other Information

ACGIH	American Conference of Governmental & Industrial Hygienists	IMO	International Maritime Organization
CAA	Clean Air Act	LVOC	Low Volatile Organic Compound
CARB	California Air Resources Board	N/A	Not Applicable
CAS	Chemical Abstract Service	NFPA	National Fire Protection Association
CCR	California Code of Regulations	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act	OSHA	Occupation Safety & Health Administration
CFR	Code of Federal Regulations	PEL	Permissible Exposure Limit
DOT	Department of Transportation	RCRA	Resource Conservation & Recovery Act
DSL/NDSL	Domestic Substances List/Non-Domestic Substances List	RQ	Reportable Quantity
EPCRA	Emergency Planning and Community Right-To-Know Act	RTK	Right-To-Know
EST	Eastern Standard Time	SARA	Superfund Amendments & Reauthorization Act
HAPS	Hazardous Air Pollutants	STEL	Short-Term Exposure Limit
HMIS	Hazardous Materials Information System	TBD	To Be Determined
HON	Hazardous Organic NESHAP (National Emission Standards for Hazardous Air Pollutants)	TCC	Tagliabue Closed Cup
HPC	Home & Personal Care	TLV	Threshold Limit Value
HVOC	High Volatile Organic Compound	TSCA	Toxic Substances Control Act
IARC	International Agency for the Research of Cancer	TWA	Time Weighted Average
IATA	International Air Traffic Association	TCLP	Toxicity Characteristic Leaching Procedure
ICAO	International Civil Aviation Organization	VOC	Volatile Organic Compounds
IMDG	International Maritime Dangerous Goods	WHMIS	Workplace Hazardous Materials Information System

DISCLAIMER: This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by the manufacture to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. The Manufacture assumes no responsibility for injury to the recipient or third persons or for any damage to any property resulting from misuse of the product.

Prepared by: TIGI
Jan-10