



Material Safety Data Sheet

Section 01 – Product Identification

TIGI Linea

1655 Waters Ridge Dr.
Lewisville, TX 75057
469 528-4300
800 259-8596

In case of medical emergencies, please contact your local poison control center.
Transportation Emergency Telephone: CHEMTREC #: 1800 424-9300 (24 Hours)

Trade Name: TIGI Catwalk Sleek Mystique Look-Lock Hairspray

Section 02 – Hazard Identification

WARNING: Extremely Flammable. Pressurized Container: Protect from sunlight and do not expose to temperatures exceeding 50°C/120°F. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – No smoking. Keep Out Of Reach Of Children. Avoid Spraying In The Eyes. Use only as directed. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

HAZARD RATINGS: Health: 1 Fire: 3 Physical Hazards: 1
Ratings are based on a 0-4 scale, with 0 representing minimal and 4 representing significant hazards or risks.

Section 03 – Composition / Information on Ingredients

Ingredients as defined by 29 CFR § 1910.1200:

| CHEMICAL NAME | CAS NUMBER | % RANGE |
|---------------------------|------------|---------|
| Dimethyl Ether | 115-10-6 | 25 – 35 |
| SD Alcohol 40-B (Ethanol) | 64-17-5 | 10 – 20 |

Section 04 – First Aid Measures

EYE CONTACT: Rinse thoroughly with water
SKIN CONTACT: Discontinue use if rash or irritation occurs. Rinse with water.
INGESTION: Do not induce vomiting. Drink a glass of milk or water.
INHALATION: move individual to fresh air.
NOTE: If symptoms persist, seek medical attention.

Section 05 – Fire Fighting Measures

HAZARD CLASSIFICATION: Flammable. See Section XIV for Shipping Classifications.
FLASHPOINT: Not applicable. Aerosol flame extension <18 inches/45 cm.
NFPA CLASSIFICATION: Aerosol Level 1 per NFPA 30B.
EXTINGUISHING MEDIA: Water mist/spray, carbon dioxide, foams or dry chemicals. **SPECIAL**
FIREFIGHTING PROCEDURES: Since pressurized aerosol cans may explode when exposed to excessive heat, protect from excessive heat with water spray.
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen; hydrocarbons & derivatives.
CONTENTS UNDER PRESSURE: Yes. Exposure to temperature > 130°F/55°C may cause bursting.
EXPLOSIVE: Yes.

Section 06 – Accidental Release Measures

SPILLS, LEAKS: Small or household quantities may be cleaned up and disposed of in household trash. For large (industrial) releases, eliminate all sources of ignition and ventilate the area with equipment rated for use in a flammable environment.

Section 07 – Handling & Storage

HANDLING PRECAUTIONS: Contents under pressure. Do not puncture or incinerate container. Do not use when smoking or in presence of fire, open flame, sparks or heat.

STORAGE REQUIREMENTS: Do not store at temperatures above 120°F/50°C or in enclosed places that could overheat.

Section 08 – Exposure Control / Personal Protection

| CHEMICAL NAME | CAS # | ACGIH TLV | OSHA PEL |
|----------------|----------|------------------|---------------------------|
| Dimethyl Ether | 115-10-6 | None established | None established |
| Ethanol | 64-17-5 | STEL=1000 ppm | TWA=1000 ppm , 1900 mg/m3 |

PERSONAL PROTECTION

FOR ROUTINE CONSUMER USE: Avoid inhalation. Avoid spraying in eyes. Use only as directed. Do not use on broken skin. Stop use if rash or irritation occurs.

FOR INDUSTRIAL ACTIVITIES: Use protective eyewear, gloves, clothing and general ventilation.

Section 09 – Physical & Chemical Properties

FORM: Liquid in pressurized metal can
ODOR: Characteristic
SPECIFIC GRAVITY: Not applicable
MELTING POINT: Not applicable
pH: Not applicable
PERCENT VOLATILE: Not applicable
COLOR: Not applicable
SOLUBILITY: Not applicable
PRESSURE: 38-54 PSIG at 70°F/21°C. 92-116 PSIG at 130°F/54°C.
VISCOSITY: Not available
EVAPORATION RATE: > 1
PERCENT VOC: < 55

Section 10 – Stability & Reactivity

STABLE: Yes
HAZARD DECOMPOSITION PRODUCTS: None known
INCOMPATIBLE WITH: Strong oxidizers, acids or bases. Do not expose to heat or in enclosed places that could overheat.
SPECIAL CONDITIONS TO AVOID: Open flames, high temperatures, sunlight or impact.
CORROSIVE TO STEEL, ALUMINUM: No.

Section 11 – Toxicological Information

ACUTE EFFECTS

EYE CONTACT: May cause redness or irritation.
SKIN CONTACT: Overexposure may cause a skin reaction such as redness. Do not use on broken skin.
INGESTION: May cause nausea, vomiting and diarrhea.
RESPIRATORY: Intentional misuse by deliberately concentrating and inhaling the contents can cause serious injury or death.

CHRONIC EFFECTS: None expected

CARCINOGEN CLASSIFICATIONS

NTP: None
IARC: None
OSHA: None

Section 12 – Ecological Information

This product is safe for the environment at the concentrations predicted under normal use conditions.

Section 13 – Disposal Considerations

Disposal by Consumer: Contents under pressure. Do not puncture or incinerate. Waste generated in the course of normal consumer use is not subject to RCRA. Consumer waste should be disposed of in accordance with all applicable local, state and federal regulations.

Disposal by Manufacturer/Vendors: Waste meets the federal definition of hazardous waste due to the ignitability characteristic (D0001) as defined at 40 CFR § 261.21. Hazardous Waste Generator may recover waste Ethanol for bulk liquid disposal (or recycling) pursuant to RCRA or may dispose of individual consumer containers in drums or other appropriate containers. Generator cannot incinerate waste without puncturing and releasing flammable gas from all pressurized consumer packaging using the appropriate aerosol disposal equipment to ensure worker safety.

Section 14 – Transport Information

| FOR SHIPMENT IN CONSUMER | DOMESTIC – ALL MODES | INTERNATIONAL - AIR | INTERNATIONAL - WATER |
|--------------------------|--------------------------------|---------------------|-----------------------|
| PACKAGING | (US DOT) | (IATA/ICAO) | (IMO/IMDG) |
| PROPER SHIPPING NAME: | Consumer Commodity | Consumer Commodity | Aerosols |
| HAZARD CLASS: | ORM-D & ORM-D-AIR (Cargo Only) | 9 | 2.1 |
| UN/ID #: | None | ID8000 | UN1950 |
| PACKING GROUP: | None | None | None |
| LABEL REQUIRED: | None | Miscellaneous | None |

EMERGENCY GUIDE NUMBER: ID8000 Consumer Commodity = 171
UN1950 Aerosol = 126

DOT HAZARDOUS SUBSTANCE RQ: None/no reportable quantities

DOT MARINE POLLUTANTS: None/no reportable quantities

IATA - Substances Forbidden from Air Transport: None/no reportable quantities

IATA - Subst. Forbidden from Passenger Transport: Dimethyl ether

Section 15 – Regulatory Information

TSCA: Not applicable

RCRA: See Section XIII - Disposal Considerations

CAA HAPS or Ozone Depletors: None/no reportable quantities

CERCLA/SARA 302 Hazardous Substances: None/no reportable quantities

CERCLA/SARA 311/312 Hazard Categories: None/no reportable quantities

CERCLA/SARA 313 Emissions Reporting: None/no reportable quantities

CERCLA RQ: Ethanol and Dimethyl Ether -100 lbs

CA 22 CCR Hazardous Wastes: Ethanol

CA Proposition 65 Listed Chemicals: None/no reportable quantities

IL, MA, NJ, PA, RI State RTK, Hazardous & Other Notifications: Ethanol, Dimethyl ether

Section 16 – Other Information

| | | | |
|--------|---|------|--|
| ACGIH | American Conference of Governmental & Industrial Hygienists | N/A | Not Applicable |
| CAA | Clean Air Act | NFPA | National Fire Protection Association |
| CAS | Chemical Abstract Service | NTP | National Toxicology Program |
| CCR | California Code of Regulations | OSHA | Occupation Safety & Health Administration |
| CERCLA | Comprehensive Environmental Response, Compensation & Liability Act | PEL | Permissible Exposure Limit |
| CFR | Code of Federal Regulations | RCRA | Resource Conservation & Recovery Act |
| DOT | Department of Transportation | RQ | Reportable Quantity |
| EPCRA | Emergency Planning and Community Right-To-Know Act | RTK | Right-To-Know |
| EST | Eastern Standard Time | SARA | Superfund Amendments & Reauthorization Act |
| HAPS | Hazardous Air Pollutants | STEL | Short-Term Exposure Limit |
| HMIS | Hazardous Materials Information System | TBD | To Be Determined |
| HON | Hazardous Organic NESHAP (National Emission Standards for Hazardous Air Pollutants) | TCC | Tagliabue Closed Cup |
| IARC | International Agency for the Research of Cancer | TLV | Threshold Limit Value |
| IATA | International Air Traffic Association | TSCA | Toxic Substances Control Act |
| ICAO | International Civil Aviation Organization | TWA | Time Weighted Average |
| IMDG | International Maritime Dangerous Goods | TCLP | Toxicity Characteristic Leaching Procedure |
| IMO | International Maritime Organization | VOC | Volatile Organic Compounds |

DISCLAIMER: This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by the manufacture to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. The Manufacture assumes no responsibility for injury to the recipient or third persons or for any damage to any property resulting from misuse of the product.

TIGI linea

MSDS Date: 7/29/2010