

Page 1 of 8

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

facility (TSDF)

SDS Revision: 1.2

SDS Revision Date: 7/6/2015

1.1	Product Name:	1. PRODUCT & COMPANY IDENTIFICATION HSI HAIR BLEACH
1.2	Chemical Name:	Persulfate Blend
1.3	Synonyms;	Blend R&D Development
1.4	Trade Names:	HSI HAIR BLEACH
1.5	Product Uses & Restrictions:	Professional Cosmetic Use Only
1.6	Distributor's Name:	Hair Systems, Inc.
1.7	Distributor's Address:	30 Park Avenue, Englishtown, NJ 07726 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 10069)
1.9	Business Phone / Fax:	+1 (732) 446-2202 / +1 (732) 446-7968

his product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

DANGER! MAY INTENSIFY FIRE; OXIDIZER. HARMFUL IF SWALLOWED. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING IRRITATION. DIFFICULTIES IF INHALED. MAY CAUSE RESPIRATORY IRRITATION.

Classification: Oxidizing Solid - Category 3; Acute Toxicity - Category 4; Skin Irritation - Category 2; Eye Irritation - Category 2A; Respiratory Sensitization - Category 1; Skin Sensitization -Category 1; Single Target Organ Toxicity (Single Exposure) - Category 3.

Hazard Statements (H): H272 - May intensify fire; oxidizer. H302 - Harmful if swallowed. H315 -Causes skin irritation. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.

Precautionary Statements (P): P210 - Keep away from heat/sparks/open flames/hot surfaces - No smoking. P220 - Keep/Store away from clothing/cotton/combustible materials. P261 - Avoid breathing dust/fumes. P264 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - If necessary, wear respiratory protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P302+P352 - IF ON SKIN: Wash with soap and water. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P321 -Specific treatment (see section 4 of the Safety Data Sheet or the product label). P330 - Rinse mouth. P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or a rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists get medical advice/attention. P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. P362+P364 - Take off contaminated clothing and wash before reuse. P370+P378 - In case of fire: Use CO2, Halon (if permitted), dry chemical, or foam for extinction. P403+P233 - Store in a well ventilated place. Keep container tightly closed. P405 -

Store locked up. P501 - Dispose of contents/container to licensed treatment, storage or disposal







3 COMPOSITION & INCREDIENT INCORMATION

								EXPO	SUREL	MITS IN	AIR (mg	a/m^3)	
	CAS No.	RTECS No.	EINECS No.	%	ACGIH ppm		NOHSC			OSHA			
							ppm			mag			
CHEMICAL NAME(S)					TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDI II	
POTASSIUM PERSULFATE	7727-21-1	SE0400000	231-781-8	10-30	(0.1)	NIA	NIF	110	NIC			IDLH NA	OTHER
- TOOLI ATE		cute Tox, 4; Skin	Irrit, 2; Eye Irrit, 2	2A; Resp. S	ens. 1; \$	Skin Se	ns. 1; S	TOTS	E 3; H2	72, H30	D2, H31	5, H317,	H319, H334
	1344-09-8	NA	215-687-4	1-20	INΙΔ				- "		D2, H31	5, H317,	H319, H334
	1344-09-8 Acute Tox. 4	NA ; Skin Irrit. 2; Eye	215-687-4	1-20	INΙΔ	Skin Se NA	ns. 1; S	NF	E 3; H2	72, H30 NA	02, H31 NA	5, H317,	H319, H334
SODIUM SILICATE SODIUM PERSULFATE	1344-09-8 Acute Tox. 4 7775-27-1	NA ; Skin Irrit. 2; Eye SE0535000	215-687-4 Dam. 1; H302, H	1-20 1315, H318	NA NA	NA	NF	NF (0.04)	NF	NA	02, H31 NA	5, H317,	H319, H334
SODIUM SILICATE	1344-09-8 Acute Tox. 4 7775-27-1	NA ; Skin Irrit. 2; Eye	215-687-4 Dam. 1; H302, H	1-20 1315, H318 1-15 5. 1; Eye Irri	NA NA	NA	NF	NF (0.04)	NF	NA	02, H31 NA	5, H317,	H319, H334



Page 2 of 8

epared to OSHA, ACC, ANSI	, NOHSC, WHMIS, GHS & EU Standards SDS Revision: 1.2 SDS Revision Date: 7/6/2015
T Europ Augu	4. FIRST AID MEASURES
Filst Aid;	If ingested, do not induce vomiting. Drink plenty of water or milk. If the patient is vomiting, continue offer plenty of water or milk. Never give water or milk to an unconscious person. If large quantities a ingested, contact the nearest Poison Control Center or local emergency number. Provide an estimate the time and amount of the substance that was swallowed. Get medical attention immediately. If product is in the eyes, flush with copious amounts of water for at least 15 minutes. Remove contained irrigation. If problem persists, consult a physician. Skin: If redness, dryness or other signs of irritation to the skin days leaves as well as a supersist of the skin days leaves.
	affected skin areas with plenty of warm water and soap. If irritation persists, consult a physician. Inhalation: Give oxygen as necessary and get medical attention.
	May cause irritation in mouth and throat. Swallowing may cause evolution of oxygen which may cause injury by distention of the esophagus or stomach. May cause nausea, vomiting and diarrhea. May cause irritation, redness, stinging and tearing. When bleach is mixed with peroxides or developed the resulting mixture may cause severe eye irritation and possible eye injury. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reaction (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Prolonged exposure may cause irritation in nose and throat with chest discomfort, coughing and difficul breathing.
	Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eye may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitic upon prolonged or repeated exposure.
Acute Health Effects:	Moderate irritation to skin near affected areas. This product causes serious eye irritation.
	The material may accentuate any pre-existing dermafitis condition
	Eyes, skin & respiratory system.
Medical Conditions Aggravated by Exposure:	Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. Existing dermatological conditions (such as eczema) and respiratory conditions (such as bronchial asthma and/or bronchitis) may be aggravated. HEALTH
	E CIDECIOUTING ME LOUIS
Fire & Explosion Hazards:	5. FIREFIGHTING MEASURES
Extinguishing Methods: Firefighting Procedures:	DANGER! MAY INTENSIFY FIRE; OXIDIZER. Upon decomposition, persulfates yield oxygen and may thereby stimulate combustion of flammable and combustible materials. Extinguish fires with media appropriate for the burning material. Product contains oxidizing materials. Residual product on towels, sponges or mops may cause fire. Rinse towels thoroughly before disposal. Rinse sponges and mops thoroughly before storage. Persulfate compounds may ignite and undergo decomposition in the presence of moisture and heat. Spray and flood decomposing material with large quantities of water. CO2, Halon (if permitted), Dry Chemical, Foam, as authorized. Water and/or foam – typically a Class A or Class B extinguisher should be sufficient for the product. However, selection of a fire extinguisher should also be appropriate to address the location of the fire and equipment involved. Flood with water and use water spray to cool fire-exposed containers and structures. This product is an oxidizer and may intensify fire. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personnel. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous decomposition products. Hazard Identification Number: 50
- M	6. ACCIDENTAL RELEASE MEASURES
	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. Small Spills: (e.g., ≤ 1.0 lbs (0.45 kg)). Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within
	Effects of Exposure: Symptoms of Overexposure: Acute Health Effects: Chronic Health Effects: Target Organs: Medical Conditions Aggravated by Exposure: Fire & Explosion Hazards: Extinguishing Methods:



9.17

Other Information

%VOC @ 21 °C (70 °F): 0

SAFETY DATA SHEET

Page 3 of 8

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards SDS Revision: 1.2 SDS Revision Date: 7/6/2015 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Avoid contact with flammable or combustible materials. Avoid contamination from any source, including metals, dust and organic materials. Keep bulk materials covered. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm 7.2 Storage & Handling: Keep this material away from heat, sparks and open flame. Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F (49 °C). Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use. Store away from incompatible materials (see Section 10). Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly. Do not allow stored material to come into contact with moisture (keep lids properly affixed on product stored in plastic tubs). Do not store metal utensils inside containers of product. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC $ppm (mq/m^3)$ OTHER CHEMICAL NAME(S) TIV STEL ES-TWA ES-STEL ES-PEAK PFI STEL POTASSIUM PERSULFATE (0.1)NA NF NF NF NA NA NA SODIUM PERSULFATE (0.1)NA NF (0.01)NF NA NA NA AMMONIUM PERSULFATE (0.1)NA NF NE 82 Ventilation & Engineering NF NA NA When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans), to keep exposure below the airborne exposure limits. Ensure that an eyewash station, sink or washbasin is available in case of Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.4 Eye Protection: Avoid contact. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.5 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear Hand Protection: latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection No special body protection is required under typical circumstances of use and handling. Wear appropriate protective clothing to prevent skin contact, (e.g., boots, lab coat, apron, coveralls) as needed. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance White to off white cream Bleach 93 Odor Threshold: NA 9.4 9.0-11.5 9.5 Melting Point/Freezing Point NA Initial Boiling Point/Boiling 9.6 NA Range: 9.7 Flashpoint NA 98 Upper/Lower Flammability NA Vapor Pressure NA 9.10 Vapor Density: NA 9.11 Relative Density: < 0.5 912 Solubility: 4.7 g in 100 mL water 9.13 Partition Coefficient (log Pow): NA Autoignition Temperature: NA Decomposition Temperature NA Viscosity

HAIR SYSTEMS INC.

SAFETY DATA SHEET

Page 4 of 8

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards SDS Revision: 1.2 SDS Revision Date: 7/6/2015 10. STABILITY & REACTIVITY Unstable. Gradually decomposes losing oxygen. Decomposes more rapidly at higher temperatures. Metals other than Stability: stainless steel are apt to cause decomposition of persulfate solutions. Generates heat when mixed with acid. May react with ammonium salt solutions resulting in evolution of ammonia gas. Liberation of oxygen gas may result in dangerous If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic 10.2 Hazardous Decomposition Products: gases (e.g., CO, CO₂, and SO₂). Liberation of gas (e.g., oxygen) may result in dangerous pressures. Decomposed by moisture to form oxygen and ozone. Burning may produce nitrogen oxides, sulfur oxides, and sulfuric acid 10.3 Hazardous Polymerization: Conditions to Avoid: 10.4 Open flames, sparks, high heat and direct sunlight. Moisture, combustible material, heat, flame, ignition sources, shock, friction, powdered metals, phosphorus, hydrides, organic matter, halogens, acids, alkalis, and incompatibles Reducing agents, organics, some acids, flammable materials. Do not use metallic bowls or utensils when mixing this Incompatible Substances: product. Avoid contamination with moisture, combustible or organic materials (e.g., sawdust, damp paper towels). 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry Absorption: YES 11.2 Ingestion: YES Toxicity Data This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product but is not presented in this document. 113 Acute Toxicity: Moderate irritation to skin near affected areas. This product causes serious eye irritation. Chronic Toxicity: The material may aggravate any pre-existing skin condition (e.g., dermatitis). This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Suspected Carcinogen: 11.5 No 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure 11.8 Biological Exposure Indices: Physician Recommendations: Treat symptomatically 12. ECOLOGICAL INFORMATION The components of this product will slowly degrade over time into a variety of organic compounds. Environmental Stability environmental data available for the components of this product are available, but are not presented in this Safety Data Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life: This product was not tested on animals. Specific aquatic test data is available for the some of the components of this product, but are not presented in this Safety Data Sheet. 13. DISPOSAL CONSIDERATIONS Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. Special Considerations U.S. EPA Waste Number: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, sodium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg); or CONSUMER COMMODITY, ORM-D - until 01/01/2021 14.2 IATA (AIR): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, sodium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 1.0 kg) 14.3 IMDG (OCN) UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, sodium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg) 14.4 TDGR (Canadian GND): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, sodium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 5.0 kg) UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, sodium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg) 14.8 SCT (MEXICO) UN1479, SOLIDO COMBURENTE, N.E.P. (persulfato de potasio, persulfato de sodio, persulfato de ammonia), 5.1, III

(CANTIDAD LIMITADA, IP VOL ≤ 5.0 kg)



Page 5 of 8

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.2

SDS Revision Date: 7/6/2015

UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, sodium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg)



Page 6 of 8

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards SDS Revision: 1.2 SDS Revision Date: 7/6/2015 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning Qty: There are no specific Threshold Planning Quantities for the components of this product. 15.3 TSCA Inventory Status The components of this product are listed on the TSCA Inventory 15.4 CERCLA Reportable Quantity: 15.5 Other Federal Requirements: This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS C, D2B (Oxidizing Agent, Other Toxic Effects) 15.7 State Regulatory Information: Potassium Persulfate is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), and Pennsylvania Right-to-Know List (PA). Sodium Persulfate is found on the following state criteria lists: NJ and PA. Ammonium Persulfate is found on the following state criteria lists: NJ and PA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY). Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI) Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC Potassium Persulfate: Oxidizer, Harmful (O, Xn). Risk Phrases (R): 8-22-36/37/38-42/43 - Contact with combustible material may cause fire. Harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. <u>Safety Phrases</u> (S): (2)-3-7-17-22-24-26-37-51 - Keep out of the reach of children. Keep in a cool place. Keep container tightly closed. Keep away from combustible material. Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Use only in well-ventilated areas. Sodium Persulfate: Oxidizer, Harmful (O, Xn). Risk Phrases (R): 8-22-36/37/38-42/43 — Contact with combustible material may cause fire. Harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. Safety Phrases (S): (2)-3-7-17-22-24-26-37-51 - Keep out of the reach of children. Keep in a cool place. Keep container tightly closed. Keep away from combustible material. Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Use only in well-ventilated areas. Ammonium Persulfate: Oxidizer, Harmful (O, Xn). Risk Phrases (R): 8-22-36/37/38-42/43 - Contact with combustible material may cause fire. Harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. Safety Phrases (S): (2)-3-7-17-22-24-26-37-51 - Keep out of the reach of children. Keep in a cool place. Keep container tightly

closed. Keep away from combustible material. Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Use only in

well-ventilated areas.



Page 7 of 8

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.2 SDS Revision Date: 7/6/2015

		AC OTHER INC	0.000
16.1	Other Information:	16. OTHER INF	ORMATION
		ASTHMA SYMPTOMS OR BREATHING DIFF Keep away from heat/sparks/open flam clothing/cotton/combustible materials. Avoid bre warm water thoroughly after handling. Do not e well-ventilated area. Contaminated work clot gloves/protective clothing/eye protection/face pr Call a POISON CENTER or doctor/physician if y Remove victim to fresh air and keep at rest in a water for several minutes. Remove contact le CENTER or doctor/physician if you feel unwell product label) Rinse mouth. If skin irritation occ medical advice/attention. If eye irritation persis Call a POISON CENTER or doctor/physician	eathing dust/fumes. Wash hands and exposed skin areas with soap and eat, drink or smoke when using this product. Use only outdoors or in a hing should not be allowed out of the workplace. Wear protective rotection. If necessary, wear respiratory protection. IF SWALLOWED you feel unwell. IF ON SKIN: Wash with soap and water. IF INHALED a position comfortable for breathing. IF IN EYES: Rinse cautiously with ness if present and easy to do – continue rinsing. Call a POISON I. Specific treatment (see section 4 of the Safety Data Sheet or the purs: Get medical advice/attention. If skin irritation or a rash occurs: Get aget medical advice/attention. If experiencing respiratory symptoms if ake off contaminated clothing and wash before reuse. In case of fire
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	THE COT OF REACH OF CHILDREN
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA regulations must be reviewed for applicability to this pro reliable and accurate as of this date; however, accurate either expressed or implied, are provided. The informa	's Hazard Communication Standard, 29 CFR §1910.1200. Other governmen duct. To the best of Hair Systems knowledge, the information contained herein is cy, suitability or completeness is not guaranteed and no warranties of any type ation contained herein relates only to the specific product(s). If this product(s) is must be considered. Data may be changed from time to time. Be sure to consult
16.4	Issued by:	Hair Systems, Inc. 30 Park Avenue Englishtown, NJ 07726 USA Tel: +1 (732) 446-2202 Fax: +1 (732) 446-7968 http://www.hairsystemsinc.com	HAIR SYSTEMS INC. Processors & Packagous of Quality Wast Case Products



Page 8 of 8

REACTIVITY

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.2

SDS Revision Date: 7/6/2015

FLAMMABILITY

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:


CAS No.	Chemical Abstract Service Number
EXPOSURE	LIMITS IN AIR:
ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average
	J

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

	A			-	
-	В		0	4:5	
	С		(1)		
-	D	(1)		(E)	
	Ε	(3)	0	(3)	
-	F	(3)	0	4	(3)
				1	











00



Protective Clothing & Full Suit

Dust Respirator

Full Face Respirator

Dust & Vapor Half-Mask Respirator

Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR NR	No Results
ррт	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	TY LIMITS IN AIR:
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
ŲEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INF	ORMATION:
LD ₅₀	Lethal Dose (solids & liquids) w
LC ₅₀	Lethal concentration (gases) wh
ppm	Concentration expressed in part
TDio	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or TC, TC _o , LC _{io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of OilWater Distribution

REGULATORY INFORMATION:

REGULATO	DRY INFORMATION:
WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

0	(4)	(1)	(2)	1	(4)	(3)	(ñ)	
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F	
Compressed	npressed Flammable Oxidizing		Toxic	Irritation	Infectious	Corrosive	Reactive	

EC (67/548/EEC) INFORMATION:

17.2		W.	¥2	8	9	X	X
С	E	F	N	0	T	.Xi	Хn
Corrosive	Explosive	Flammable	Harmful .	Oxidizing	- Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			0	(3)	(9)		P. Style	(£)
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHISDS	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Correjaive	Toxic	Harmful Irritating	Health Hazard	Environment