

Page 1 of 6 **WS-009**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 11/30/2015

1.1	Product Name:	INFINITY FINISHING SPRAY, 55% VOC
1.2	Chemical Name:	Aerosol
1.3	Synonyms:	WH134000
1.4	Trade Names:	Infinity Finishing Spray, 55% VOC
1.5	Product Uses & Restrictions:	Cosmetic Use Only
1.6	Distributor's Name:	White Sands Hair Care, Inc.
1.7	Distributor's Address:	27631 La Paz Rd., Suite G, Laguna Niguel, CA 92677 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300
1.9	Business Phone / Fax:	+1 (949) 206-1300 / +1 (949) 206-1313
		2. HAZARDS IDENTIFICATION
2.1	Hazard Identification:	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.

Classification: Aerosol 2; Skin Sens. 1B; Eye Irrit. 2

Hazard Statements (H): H223 – Flammable aerosol. H229 – Pressurized container may burst if heated. H317 – May cause an allergic skin reaction. H320 – Causes eye irritation.

Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 – Do not spray on open flame or other ignition source. P251 – Do not pierce or burn, even after use. P261 – Avoid breathing fume/gas/mist/vapours/spray. P264 – Wash hands and exposed skin areas with soap and warm thoroughly after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eyewear. P302+P352 – IF ON SKIN: Wash with plenty warm water and soap. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists get

medical advice/attention. P362+P364 – Take off contaminated clothing and wash it before reuse. P370+P378 – In case of fire: Use Water, Foam, CO₂, Dry Chemical, Halon (if authorized), to extinguish. P403+P235 – Store in a well-ventilated place. Keep cool. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). P501 – Dispose of

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HATED.



3. COMPOSITION & INGREDIENT INFORMATION

contents/container to a licensed treatment, storage or disposal facility (TSDF).

								EXPO	SURE L	IMITS IN	AIR (m	g/m³)	
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ETHANOL (SD ALCOHOL 40D)	64-17-5	KQ6300000	200-578-6	30-60	1000	3000	1000	1800	NF	1000	1900	3300	
ETHANOL (SD ALCOHOL 40B)	Flam.Liq.2; H2	225											
DIELLIODOETLIANE (D. 450-)	75-37-6	KI4100000	200-866-1	30-60	1000	NA	1000	NF	NF	NA	NA	NA	
DIFLUOROETHANE (R-152a)	Flam. Gas 1; I	H220											

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.
		<u>Skin</u> :	If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea.
		Eyes:	Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.
		Inhalation:	None expected.



Page 2 of 6 **WS-009**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 11/30/2015 4. FIRST AID MEASURES – cont'd 4.3 Symptoms of Overexposure: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. 4.4 Acute Health Effects Moderate irritation to eyes. 4.5 Chronic Health Effects: No harmful or chronic health effects are expected to occur from a single accidental ingestion. 4.6 Target Organs: Eyes Medical Conditions 4.7 Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH Aggravated by Exposure: target organs (eyes, skin, and respiratory system). FLAMMABILITY 3 0 PHYSICAL HAZARDS PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES FLAMMABLE AEROSOL. Level 2 Aerosol (NFPA 30B). Aerosols may burst at temperatures Fire & Explosion Hazards: above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or/or exposed gases if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished. Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. When exposed to high temperatures, may produce hazardous decomposition products such as oxides of carbon (e.g., CO, CO₂) and nitrogen (e.g., NO_x) and smoke. Extinguishing Methods: 5.2 Water, Foam, CO₂, Dry Chemical, Halon (if authorized) 5.3 Firefighting Procedures: As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressuredemand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective 6.1 Spills: Equipment (PPE). For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: 7.1 Do not eat, drink, or smoke while handling this product. 72 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat and open flames. 7.3 Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ppm (mg/m³) CHEMICAL NAME(S) TLV STEL ES-TWA **ES-STEL ES-PEAK** PEL STEL IDLH ETHANOL (SD ALCOHOL 40B) 1000 3000 1000 1800 1000 1900 3300 NF DIFLUOROETHANE (R-152a) 1000 NA 1000 NF NF NA NA NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Controls: exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.



Page 3 of 6 **WS-009**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 11/30/2015 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd 8.4 Eye Protection: Avoid eye contact. Protective eyewear recommended. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling large quantities (of this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.5 Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: No special body protection is required under typical circumstances of use and handling. necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Clear liquid Alcohol odor 9.3 Odor Threshold NA 9.4 pH: NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 38 °C (100 °F) Range: 9.7 Flashpoint: NA 9.8 Upper/Lower Flammability LEL: 5.1% / UEL: 17.1% (R-152A) 9.9 Vapor Pressure: 55-65 psig @ 70 °F 9.10 Vapor Density: NA 9.11 Relative Density: 0.815 9.12 Solubility in Water: Soluble 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA 9.16 Viscosity: NA Other Information: 9.17 VOC: 55%. 6.8 lb/gal 10. STABILITY & REACTIVITY 10.1 Stability: This product is stable. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO₂) and sulfur (SO₂). **Products** 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid: Open flames, sparks and high heat. 10.5 Incompatible Substances: None known. 11. TOXICOLOGICAL INFORMATION Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES 11.1 Toxicity Data: 11.2 This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product. 11.3 Acute Toxicity: See section 4.4 Chronic Toxicity: See section 4.5 11.4 11.5 Suspected Carcinogen No. Reproductive Toxicity This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 4.3. Biological Exposure Indices: 11.8 NE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: 12.1 There is no specific data available for this product. 12.2 Effects on Plants & Animals: There is no specific data available for this product. 12.3 Effects on Aquatic Life: There is no specific data available for this product.



Page 4 of 6 **WS-009**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 11/30/2015 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13 1 Waste disposal must be in accordance with appropriate Federal, state, and local regulations. Special Considerations: 13.2 U.S. EPA Waste Number: D001 (characteristic - ignitable). 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/20 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (IP VOL ≤ 0.5 L) All Y UN1950, AEROSOLS, FLAMMABLE, 2.1 (IP VOL > 1.0 L) 14.3 IMDG (OCN): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) TDGR (Canadian GND): MARK PACKAGE ("LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or 14.4 "QUANT LTÉE" ≤ 1.0 L) or UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.5 ADR/RID (EU): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) SCT (MEXICO): UN1950, AEROSOLES, 2.1 (CANT. LTDA., IP VOL ≤ 1.0 L) ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. 15.1 SARA Reporting Requirements SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 CERCLA Reportable Quantity 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics). This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B5, D2B (Flammable Aerosol, Other Toxic Effects) 15.7 State Regulatory Information: Ethanol is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), California Proposition 65 ((CA65) ethanol in alcoholic beverages) and Washington Permissible Exposures List (WA). <u>Difluoroethane</u> can be found on the following state criteria lists: MA and NJ. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC. Ethanol: Flammable (F). Risk Phrases (R): 11 - Flammable. Safety Phrases (S): 2-7-16 - Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition - No smokina. <u>Difluoroethane</u>: Extremely Flammable, Harmful (F+, Xi). <u>Risk Phrases</u> (R): R12-37-65-67 Extremely flammable. Irritating to respiratory system. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness or dizziness. <u>Safety Phrases</u> (S): S2-7-9-16-24/25-26-33-45-53 - Keep out of the reach of children. Keep container tightly closed. Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Take precautionary measures against static discharges. In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). Avoid exposure - obtain special

instructions before use.



Page 5 of 6 **WS-009**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 11/30/2015 16. OTHER INFORMATION Other Information: WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing fume/gas/mist/vapours/spray. Wash hands and exposed skin areas with soap and warm thoroughly after handling. If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN: Wash with plenty warm water and soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention. In case of fire: Use Water, Foam, CO₂, Dry Chemical, Halon (if authorized) to extinguish. Store in a well-ventilated place. Keep cool. Use only as directed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). Discontinue use immediately if irritation develops. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & White Sands Hair Care's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: White Sands Hair Care, Inc. 27631 La Paz Rd., Suite G. Laguna Niguel, CA 92677 USA Tel: +1 (949) 206-1300 White Sands Fax: +1 (949) 206-1313 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA

Training & Consulting

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com



Page 6 of 6 **WS-009**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 11/30/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

EXPOSURE LIMITS IN AIR:						
ACGIH American Conference on Governmental Industrial Hygienists						
C Ceiling Limit						
ES Exposure Standard (Australia)						
IDLH Immediately Dangerous to Life and Health						
COLLA III C. Commention of Confedence of III all the Administration						

OSHA U.S. Occupational Safety and Health Administration PEL Permissible Exposure Limit STEL Short-Term Exposure Limit TLV Threshold Limit Value TWA Time Weighted Average

CAS No. | Chemical Abstract Service Number

FIRST AID MEASURES:


Cardiopulmonary resuscitation - method in which a person whose heart has
stopped receives manual chest compressions and breathing to circulate blood
and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		
1 Slight Hazard			
2 Moderate Hazard			
3	Severe Hazard		
4	Extreme Hazard		

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:







Splash Goggles













Full Face Respirator



Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit		
mg/m3	milligrams per cubic meter		
NA Not Available			
ND	Not Determined		
NE	Not Established		
NF	Not Found		
NR	No Results		
ppm parts per million			
SCBA	Self-Contained Breathing Apparatus		

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:							
Autoignition	Autoignition Minimum temperature required to initiate combustion in air with no other						
Temperature	source of ignition						
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that wil							
explode or ignite in the presence of an ignition source							
UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that w							
	explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
W	Use No Water			
ОХ	Oxidizer			
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC	TC Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NOHSC	National Occupational Health and Safety Commission (Australia)			
NDSL	Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			
WGK	Wassergefährdungsklassen (German Water Hazard Class)			
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System			

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0		(2)		\odot	®		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

15.00 m		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\Diamond		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment